Prime-IC line-layout tournament: terminal run report

Run start: 2026-11-01 01:21 UTC
Source: `b4d751706eb2244314ebc9b84ba9545485ba4ac7`
Native SHA-256: `0784fe47212d64dd2ee81510d3c28d2f604782086500135a3114c61738f854b7`
Outcome: both preregistered EKS jobs terminated failed; performance decision unavailable.




Figure 1: Failure evidence and bounded diagnostic flow

The diagram is descriptive. It contains no timing or inferred speed result. Its editable source is `failure-flow.dot`, with an SVG copy at `failure-flow.svg`.

Requested scope and evidence status

- **Two concurrent EKS sessions — verified complete.** Workflow runs 41260778029 and 41260778856 bind the exact source and native binary.
- **Unchanged scientific gates — preserved but not completed.** Both Jobs failed before a successful payload was authenticated; no threshold changed.
- **End-to-end speed decision — blocked.** Neither run returned an authenticated session directory or comparison.
- **Zero outcome-driven retries — verified complete.** Exactly the two frozen trials ran and both failures are retained.
- **Privacy-preserving diagnosis — implemented but not yet run.** The fixed workflow emits only allowlisted failure metadata and hash-verifies every downloaded payload object that has a retained manifest.

Observed execution

Both workflows passed their contract and credential-free build jobs. EKS Jobs `gh-41260778029-1` and `gh-41260778856-1` then returned launcher state `failed`, remote-result exit 23 and GitHub wrapper exit 26. The public receipts contain Job UIDs but empty successful Pod UID and results URI fields.

The public evidence does not distinguish payload execution, native audit, L2, A/A, owner instrumentation or infrastructure failure. The private launcher prefixes retain `status.json`, `objects.json`, logs and any uploaded payload artifacts. Raw records and stderr remain private.

Excluded local diagnostic

The exact retained binary planned 360 executions and, under explicit `--allow-busy`, verified all 360 outcomes and reproduced all 320 replay-eligible records. Every execution graded L0 because this host lacks the required PSI evidence. Those observations are correctness diagnostics only; their wall values are not admitted and are not graphed or promoted.

Evidence-preserving diagnosis

The follow-up workflow is read-only and fixed to the two recorded workflow, Job, launcher, request, source and binary identities. It validates the normalized request hash, downloads only allowlisted diagnostic objects, checks each object against the retained `SHA256SUMS`, and publishes a compact classification. It does not run the binary, submit or retry a Job, print raw logs, or upload raw measurements.

Sources checked

- `taskq/deploy/eks-karpenter/HARNESS.md`: request identity, failure states and private-result boundary.
- `taskq/deploy/eks-karpenter/ACCESS.md`: existing GitHub OIDC role and scoped S3 read route.
- `taskq/deploy/eks-karpenter/remote/run-request`: exact launcher receipt and artifact locations.
- GitHub OIDC with AWS: short-lived workflow identity; no static key is introduced.

Claim and graph boundaries

This failed run supplies no admitted quantitative comparison. The index-calculus scoreboard, leaderboard, progress timeline and lab browser were checked and left unchanged because there is no verified numeric result to add. No `benchmarks/` entry is created because no performance measurement was admitted.

The relation-yield pruning instrumentation from PR #3091 is a separate merged engineering deliverable. This run report does not convert that instrumentation, the line-layout implementation, or workflow success into an end-to-end speedup.