Callable retained-session exporter: eight entrypoint controls passed

Task T-1548. 3 November 2026.

Entrypoint	Typed request + executable/request hash binding
Controls	8 CLI tests passed; prior12 retained
Terminal	35.912 seconds; three exits0; groups empty
Custody	Caller supplies authentic pins; no promotion

Ordinary software evidence only. Bounded software entrypoint validation. T-1548.

A standalone Rust CLI now invokes the checked retained-session exporter on supplied retained native files. Its strict typed request contains explicit caller-supplied FreshOwnerPins and controller custody hash. The CLI binds the exact request and executing binary, requires fresh absolute output, emits a hash-linked invocation receipt on success and a nonzero JSON error on failure. Failed partial output is retained and cannot be overwritten by retry.

The unchanged exporter uses actual fresh custody, SessionResourceJournal closure and typed diagnostic validation. Request and executable identity establish software/input joins, not external owner authentication. Success retains owner_authentication_verified=false and null worker allocation, active worker and exact kernel exit metrics. No worker, observer, image build or scientific payload was launched.

One separately released ordinary software sequence compiled the CLI and test harness sequentially, then passed all eight selected entrypoint controls in 35.911771 seconds. Four inherited custody tests were intentionally filtered; their unchanged prior twelve-control result remains the dependency. Tests cover successful request/binary/report joins and unknown metrics, wrong request and executable hashes, wrong external pins, unknown nested fields and duplicate flags/keys, output freshness, request symlink/size bounds, and partial-output preservation after actual native validation fails.

The outer ceiling was 120 seconds including cleanup, with hard 8 GiB address-space and 512 MiB per-file bounds. Aggregate output was monitored against 1 GiB rather than enforced by a filesystem quota. Both compilers and the test process exited zero, were reaped, and left empty process groups; jobserver descriptors closed. Seven source files, 888 external bindings and 464 dependency aliases matched before and after. No pending signal or uncertain launch remained.

Independent prelaunch review added exact dependency alias membership/readlink/target enforcement and corrected a stale controls metadata hash. Those corrections precede execution. Previous exporter recipes pinned dependency target bytes without alias mapping; their historical evidence remains unchanged. The CLI fixture opens only sibling visibility on the checked fixture prefix. Production validator and exporter bodies are unchanged.

CLI binary SHA256: 0adc482456c3bd1c214fadae789cbdb857a6862207a7ab4a3b44e937d32984ee. Receipt SHA256: d1d44adf84d8a87a55b8a41487670df6a82316ef5132b205c25a41bd4baaf447. USAGE.md specifies the request and separates CLI identity from worker and controller pins. Real retained-session custody must be provided independently before this entrypoint is used for acceptance.