
1. Prime-field ECDLP: three leads

Development and formalization follow-up · 29 October 2026

This work adds native development paths and checked structural proofs. No measured scientific panel or ECDLP speedup is established here.



1.1. Symmetric PKM

The new native successor accepts actual curve targets, constructs the symmetric system, visits F4 solutions, factors their root polynomials, lifts points and verifies signed sums. Construction and extraction are separate intervals. Unrestricted field branching is retained in the counters. Repeated abscissae remain outside this representation; arithmetic counters are partial.

The original construction comes from crypto PR2650 at `adde64fdc22d51dc180fe0b9f30a2d28adf992fe`. The historical instruments and records are preserved. The follow-up is an oracle implementation, not a complete factor-base logarithm and target-descent pipeline.

1.2. Five-sum replay

The exact prior source is PR2852 at `42e460293269d149f4ead6929476fcc993babfea`. The frozen raw sessions are store-backed. The ordinary unauthenticated object request returned HTTP 403. No independent replay, recomputed performance result or validation admission is claimed.

1.3. Hecke target interface

The native control consumes certified known-log points and an arbitrary public target, checks labels and n-torsion, tries bounded generic shifts, and verifies any recovered scalar. It separates setup and online ledgers. No new Hecke relation constructor or efficient natural target attachment is supplied. The D79 generalized-curve importer and coordinate certificates remain an explicit next step. The development fixture is not a D79 performance study.

2. Lean proof boundary

Lean 4.34.1, Mathlib revision `d13f23b723b8a846827a245b89c10fc7d3f11612`.

Eight named structural theorems in `lean/ThreeLeads.lean`:

1. A finite distinct-root factor polynomial divides $X^d - 1$ exactly when every proposed root has dth power one.
2. Repeated squaring gives x^{2^t} in a commutative monoid.
3. Certified table labels and an injective scalar encoding make a hit correct.
4. Valid scalar-row combinations reproduce their combined right-hand side.
5. A natural target attachment with nonzero target coefficient yields recovery.
6. A kernel perturbation preserves all rows while changing a nonzero coordinate.
7. A router with s shifts and a known-log set of size b covers at most sb targets. Include the identity if it is recognized implicitly.
8. The table-family exponent $\frac{k}{2k-1}$ exceeds $\frac{1}{2}$ for integer $k \geq 1$.

`lake build` succeeded. The consumer proof gate passed with zero trusted exceptions. A separate `lake env leanchecker ThreeLeads` completed with exit 0. Transitive axiom output names only `propext`, `Classical.choice`, and `Quot.sound`. See the exact receipts in `validation/` and the full proof map in `README.md`.

These are standard structural implications, not a claimed new complexity theorem. The scalar-to-point and natural-attachment premises are explicit. No theorem connects Rust execution to the formal objects, bounds PKM solving degree, proves fast Hecke target attachment, or establishes sub-square-root prime-field ECDLP.

3. Execution impediments and resumption

The checkpoint gate refused experiment launch. Its upload transport has no configured AWS profile or checkpoint token in this environment. The Isolab skill requires preserving that gate. GitHub access alone does not supply the checkpoint or artifact-store credential. No gate was relaxed and no scientific panel was silently replaced by local development tests.

`NEXT.md` preserves the three execution contracts: exact-source five-sum replay, complete-cost PKM comparison with an external solver, and fresh arbitrary-target Hecke tests with matched generic controls. `PROBLEM.md` names each missing bridge and its exit condition. Development validation outcomes are retained separately.

4. Sources

PKM primary text: https://people.maths.ox.ac.uk/petit/files/16PKC_primeECDLP.pdf . Internal sources: crypto PR2632, PR2650, PR2852; cryptanalysis PR1274, PR1278, PR1281; `src/cryptanalysis/f4_fp.rs`; and the pinned Mathlib dependency. No canonical performance/curve graph is changed because no new measured cost, curve, isogeny or admitted comparison is established.