
Mechanisms to distinguish in twist-assisted index calculus

Search round: 2026-10-24. This inventory preserves the broader research question while the registered runs finish. Proposed constructions below are not executed results or novelty claims.



Mechanisms already tested or currently running

Mechanism	What could improve	Required distinguishing control	Evidence boundary
Transport a relation by a cheap subgroup action	Number of represented copies	Canonical augmented rows and independent RREF	The parent study shows that jointly transported copies normalize to the same folded row
Add a known-log image to the factor base	Candidate domain and rank trajectory without extra image-log unknowns	Equal-size, disjoint generic image, here doubling	Completed 189+21 controls; more phi tuples do not produce more distinct rows or a consistent cold gain
Exploit phi's coordinate equation jointly	Polynomial construction and root-solving work	Same joint construction for doubling; strongest pure symmetry	297 constructions validated; global native failures and source-block/implicit comparisons retained separately
Partition sources by U^12	Bounded-degree elimination while keeping all phases	Same source partition for all arms; union of complete physical sets	All three regression unions match their independent signed-set/RREF oracle; local ranks pure 1/3, phi 2/3, doubling 1/3
Use all ordinary-factor permutations	Smaller pure baseline representation	Full four-factor elementary coordinates, not a distinguished fourth source	Pure finite and geometric regression solves are complete and independently audited; both rank 1/3
Concentrate at R=O	Reusable factor-log relations	Count zero folded rows and independent factor-log rank; then charge target descent	21 zero fibers and three full p37 population censuses registered; no target recovery from zero-only rows

Uniform total signed-tuple mass is conserved when the candidate domain has the same size. A higher probability of any useful relation, lower variance, better independent-rank yield or lower solving cost could still matter. The finite-count Lean module now passes its transitive-axiom audit. The domain's physical injectivity and disjointness are separate executable hypotheses; the theorem does not assume that the old conditioned traces were uniform.

What symmetry can and cannot add to a folded matrix

Suppose an endomorphism preserves the chosen cyclic prime-order subgroup and acts there by a known scalar lambda. Applying it jointly to a relation and to its residual multiplies the already folded augmented row by lambda. When lambda is nonzero, the projective row is unchanged. Such transported copies can reduce search or parameter work, but supply no extra independent row. This statement concerns joint transport of a relation; it does not equate the sets of newly found mixed relations.

The possible gains therefore need separate measurements: fewer independent factor-log columns, fewer different systems to solve, cheaper systems, or new physical relations with better rank yield. The existing fold already credits the known subgroup action. Awarding the same orbit multiplicity again as independent yield would double count it. The parent study's canonical augmented-row check is the executable control; the actual endomorphism/group/rank implication is not a new fully formalized Lean theorem here.

Frobenius-related disjoint bases: an existing method to test fairly

Galbraith, Granger, Merz and Petit construct Frobenius-related factor bases for subfield curves, and separately study Frobenius-invariant bases. Their symmetry-breaking construction expresses image logs through one base's logs. The comparison retains the actual polynomial-system solving cost; its factorial saving is conditional on the relevant solving-cost comparison. Invariant bases also reduce the number of unknowns. These are established mechanisms, not a new observation from the current study. Primary paper (https://eprint.iacr.org/2020/1315), accepted manuscript, sections 3.1–3.2 (https://pure.royalholloway.ac.uk/files/39395430/Accepted_Manuscript.pdf).

Proposed extension to this exact twist. The implemented transported Frobenius acts on abscissae as

tau_x(x) = t^(-(p-1)) * x^p.

The present L0 is invariant. A non-eigenvector line Fp*beta can instead have several distinct image lines. A candidate beta with several nonzero Kummer components needs explicit field-rank, disjointness, lift, subgroup, sign and eigenvalue checks on every factor. A four-line collector would need a fully specified S5 system and exact physical-set/rank controls.

There is a crucial baseline issue: an orbit of distinct lines can require more independent log columns than the already invariant L0 base, even if it adds no columns relative to its own non-invariant source base. Compare both its source-line control and the best invariant-line baseline, with their actual base sizes and matrix dimensions. An advantage against the first alone would not establish a gain against the second. This extension is not implemented or run in the present receipts.

Zero relations and several low-degree image maps

The predeclared doubled-triangle control (SUPPLEMENT_ZERO_DOUBLING_IDENTITY.md) predicts genuine physical zero relations whose folded rows vanish. The separately implemented post-run checker is registered. Its native version-2 gate passes 75 tests; the separate block-oracle correction in the external checker passes a fresh 76-test version-3 gate. The zero checker is designed to reconstruct them from group points and read the retained oracle sets without repeating the oracle. The resulting check would distinguish zero-fiber physical counts from useful precomputation rank.

The subsequent exact pure-zero component search (reports/run-20261024T0303Z-pure-zero/REPORT.md) finds a certificate expressing 2048 times the quartic discriminant in the ideal of the four H4 component coefficients. Integer replay and +1 mutation rejection pass. Both new Lean component/field theorems pass; independent IDC1h09d838b7dca9895f also passes, with 32 extra points and both constant and multiplier mutations rejected. The readable argument excludes a signed zero sum of four distinct Fp-abscissa points when B has degree four and characteristic is not 2 or 3. It does not cover mixed image coordinates, nonzero residuals or larger relation arities. In particular, precomputation using random known multiples of an anchor has a general residual, so this zero-only obstruction does not rule out ordinary index-calculus precomputation.

The stronger square-component check (reports/run-20261024T0445Z-square/REPORT.md) finds $64*S^3$ in the same ideal, $S=64*s4-(4*s2-s1^2)^2$. Its combined 10-theorem Lean gate passes and excludes three distinct roots, allowing the fourth abscissa to repeat. Independent IDC1h65c11f01d0b1e67a passes exact replay, 32 extra points and both mutation controls. The proposed finite-Fp residual filter retains infinity and must pass the frozen full-tape physical-presentation, unique-row, RREF and recovery audit before use. Both mixed image controls can use it; no twist-specific or complete-cost gain has been measured from it.

Five or more distinct ordinary factors remain an explicit open precomputation avenue. A useful test must count independent factor-log rank after folding, rather than assume that additional zero sums carry information. The current certificate concerns S4 and does not exclude that avenue. No higher-arity polynomial collector is implemented here. The frozen five-factor diagnostic (SUPPLEMENT_FIVE_FACTOR_ZERO.md) specifies all 21 cases, pure/phi/doubling domains, exact partition multiplicities and anchored factor-log rank. Its provenance amendment reconstructs factor logs from the saved verified matrix, because the historical recovered field stores only the target scalar. No five-factor run is claimed.

Another untested construction uses several distinct known-log images in one relation, rather than the present three-plus-one pattern. Low-degree CM maps could make that representation cheaper than scalar-image controls. Every proposed image needs an explicit coordinate map, nonzero subgroup scalar, injectivity/disjointness checks and complete costs. Enlarging the candidate domain is also available with generic scalar images; its contribution must be separated from a twist-specific algebraic saving. No such several-image collector has been measured here.

Stronger algorithmic baselines remain separate work

The pinned msolve 0.11.0 help also documents -S, a specialized saturation algorithm over the supported small prime fields. This is an untested representation control: components saturated by their discriminant can be supplied without the explicit inverse-discriminant variable. It would need a fresh frozen input, checked projection equivalence and the same physical-set oracle; it is not one of the currently running 21 literal GB inputs. The exact installed help is retained in results/msolve-0.11.0-help.txt. Likewise a complete GB and a complete Fp physical decomposition are different computations; the current external checker preserves that distinction.

Trace-zero index calculus already has a substantial literature. Gorla and Massierer analyze relation generation, sparse linear algebra and a double large-prime variation under stated geometric and solving heuristics; their prototype also illustrates the gap between asymptotic formulas and actual polynomial-system costs. Their trace-zero subgroup is a precisely defined group, not a property automatically supplied by placing points on a twist. Primary paper, sections 3–4 and 6 (https://arxiv.org/html/1405.1059).

The present collector has neither a new large-prime graph algorithm nor a measured sparse black-box linear algebra implementation. Those baselines, strong matched rho, scaling and complete prices remain required before a general competitiveness claim. The current rung can establish bounded construction, completeness or pipeline improvements within its declared scope; it does not establish a new asymptotic attack.

Graph coverage

This round adds the construction profiles and explicit pipeline diagram in the study. The old admitted cold-cost plots retain their frozen values. No newly admitted performance point, curve transfer or proved subgroup edge moves the canonical IC leaderboard, performance-gain graphs or curve registry. Those graphs are left unchanged for that reason. Failed and incomplete runs retain their own descriptive reports.