Kernel-checked polynomial and point-group lemmas

Run `lean-verification`; source freeze `0145df8ff32a104d186c31eca2f04c9ee256b21d`. Host `a81fcf6dc864`, Debian 13 x86_64, managed four-CPU virtual host, L0. Workloads use public synthetic fixtures or public-parameter checks. No wall-clock or full-cost improvement is admitted.

Raw outputs: run directory. Commands, binary/input hashes, seeds, resource limits and statuses are in execution receipts and the versioned protocols in the study root. No independent-host replay is claimed.

Recorded observations

Metric	Count / recorded value
audited theorems including generated definitions	13
compiler trusted proofs	0
explicit theorems	9
nonstandard axiom failures	0

Vector figures and editable data accompany this report on the following pages.

Lean 4.34.1 and the locked Mathlib commit build the five exact cleared polynomial identities and four trace/eigenspace statements on the actual Mathlib Weierstrass point group. The auditor checks nine explicit theorems plus four generated defining equations on standard foundations only. The concrete Frobenius/twist embedding, odd subgroup, field/chart/Jacobian maps and cost/complexity bridges remain open. See the exact proof map in lean/README.md; none of these missing bridges is an axiom or a completed theorem.

The chart has no statistical interval: census counts are exact on the stated finite sets; solver completion counts describe these bounded processes only. Missing or failed computations stay unresolved. Full original acceptance criteria and proof/measurement gaps remain in the requirement matrix.

Kernel-checked polynomial and point-group lemmas

Recorded counts; exact censuses or bounded run outcomes. No wall-time comparison.