Separate pairing-positive fixture preparation

Run `pairing-preparation`; source freeze `0145df8ff32a104d186c31eca2f04c9ee256b21d`. Host `a81fcf6dc864`, Debian 13 x86_64, managed four-CPU virtual host, L0. Workloads use public synthetic fixtures or public-parameter checks. No wall-clock or full-cost improvement is admitted.

Raw outputs: run directory. Commands, binary/input hashes, seeds, resource limits and statuses are in execution receipts and the versioned protocols in the study root. No independent-host replay is claimed.

Recorded observations

Metric	Count / recorded value
extension points	1936
known target controls	10
source points	44
source subgroup order	11

Vector figures and editable data accompany this report on the following pages.

The native preparation exhaustively counts the rational and quadratic-extension groups of the separately registered supersingular F43 model, chooses a nonidentity order-11 source generator, checks the distortion point lies outside that cyclic subgroup, and records ten known-scalar controls. This fixture is separate from the ordinary/NIST study. Independent PARI and source replay occur in the later V2 control.

The chart has no statistical interval: census counts are exact on the stated finite sets; solver completion counts describe these bounded processes only. Missing or failed computations stay unresolved. Full original acceptance criteria and proof/measurement gaps remain in the requirement matrix.

Separate pairing-positive fixture preparation

Recorded counts; exact censuses or bounded run outcomes. No wall-time comparison.