Semaev decomposition parameter sweeper: assessment and plan (2026-10-24)

Status: **proposed**. No code is written and no measurement is made by this note. Every statement below is labelled *measured* (from a committed record), *derived* (computed from recorded values) or *proposed*. Sources are named by path and branch; where a source is not on `origin/main` that is said.

0. Decisions fixed by the owner (2026-10-24, in chat)

1. The sweeper is written in **Rust** (no Python driver, no Optuna).
2. Curves are **generated**, and the sweep covers every family: prime j = 0, prime j = 1728, generic prime, Koblitz, and binary.
3. The primary target is the **a = 0, n = 83 Koblitz curve** (81-bit prime subgroup). The a = 1, n = 83 curve (52.9-bit subgroup) is the control that can run end to end.

1. Goal

Search the space of summation-polynomial (Semaev) point decompositions for m = 2…8 summands at group order about 2^83, over factor bases, large-prime variants, symmetry reductions and degree-of-regularity reductions, with an Optuna-style sequential optimiser: a typed search space, a trial store, pruning, and one scalar objective.

2. What exists (measured / read from source)

2.1 Harness

- `ic bench` runs `factor base × oracle × targets × solver × linalg` through `run_pipeline` (`src/cryptanalysis/ic_framework/mod.rs:311`) and reports `S = total GAE / √r`, `verified`, and the ratio to a matched rho (`docs/ic/FRAMEWORK.md` §2–§4). `ic bench --sweep FILE.json` expands a Cartesian matrix (`SweepFile`/`expand_matrix`, `src/bin/ic/bench.rs:715-746`); a configuration that errors is recorded in `configurations_skipped`. Shipped matrices: `docs/ic/sweeps/*.json`.
- The sweep is **serial, un-resumable, and writes its report once at the end**. There is no Optuna, TPE, Bayesian or pruning code anywhere in the repository (grep over `optuna|tpe|bayesian|hyperopt|hyperband` finds nothing relevant).
- Plug-ins: 12+ factor bases (`prime-abscissa`, `binary-subspace`, `koblitz-orbit`, `compact-orbit-scan` with `norm=/mult=`, `glv-orbit`, `cm-multiplier`, `binary-multiplier`, `prime-kummer`, `prime-isogeny`, …); oracles `subtract`, `mitm`, `mitm-frobenius` (with `large_primes={0,1,2}`), `descent-algebraic`, `symmetrised`, `rootfind-*`; solvers `f4-f2`, `matrix-f4`, `matrix-f5`, `inherited-f4`, `crossbred-f2`, `fes-f2`, `xl-f2`, `sat-cdcl`, `exhaustive`. ecbench adds `pdp3-koblitz`, `pdp-split` (chained S3, plans of the form [2,1,…,1]) and `sixsum-extract`.
- Prior sweeps: `examples/fb_hyperparam_sweep.rs` (n = 8…16, **m = 2 only**, wall-time cost model, 208 cells) and the two branch efforts in §2.4.
- Accounting an objective must obey (`AGENTS.md` §2, §3, §5a, §8a): S in group-addition equivalents with every phase inside it; a row without a verified answer is not a result; unpriced native work priced at 0, 0.1 and 1 GAE/op with arms ranked only where the order holds across the band; relabelling and accounting changes are not improvements; any claim meant to transfer to ECC2K-130 needs the n = 83 K_0 gate (`AGENTS.md` §8a).

2.2 Where the framework stops (read from source)

limit	where	consequence
binary field `Gf2`, n ≤ 63	`semaev_decomp.rs:231`; `koblitz_instance` does `group_order.to_u64()`?	`ic bench` cannot build n = 83
prime field `Fp64`, p < 2^62	`prime_fast.rs:60`	no 83-bit prime curve through the framework
m ≥ 4 oracle	`decompose_mitm` returns `None` for m ≥ 4 (`ic_boundary.rs:5350`)	m ≥ 4 exists only as standalone diagnostics
algebraic descent	`max_n_prime(m)` = ⌊64/m⌋ for m = 2, 3, else 0; `MAX_VARS = 64`	descent oracles are m = 2, 3 only
m = 7, 8	no implementation found	only the chained-S3 SAT circuit reaches them
wide pieces	`Gf2_128`, `koblitz_wide.rs`, `wide_groebner.rs` (≤ 128 unknowns), `wide_sixsum.rs`, `binary_semaev_chain_sat.rs` (MAX_VARS 512)	exist, are **not plugged into the framework**

2.3 Large primes, symmetries, regularity (technique inventory)

- **Large primes.** Five code paths: `large_prime.rs` (Koblitz m = 3 pair-table collector; oracle `mitm-frobenius:large_primes=…`), `ecbench_large_prime.rs` / `ic large-prime`, `gaudry_cubic.rs` (`LargePrimeEliminator`), `large_prime_filter.rs` (graph cycles / 2LP; **no callers outside its own tests**), `hyperelliptic_index_calculus.rs`. Measured at n = 41 (`research/ic_techniques_20261012/double_large_prime/`): best cell 2LP, |D| = 10|F|, $2.21 \cdot 10^6$ GAE, **17.7× counted signed-Frobenius rho**, but only **2.1×** better than an equal-envelope control; single LP is 1.07–1.98× *worse* than that control. At n = 23, 31 every LP cell is 2.2–750× worse than plain.
- **Symmetry reduction.** Negation (everywhere); Frobenius/Koblitz orbit fold (pair table 122× fewer entries at n = 61); FGHR 2-torsion translation (`fghr_full.rs`: degree 64 ⟶ 16, S ÷ 27); D_4-symmetrised S5 (`gaudry_quartic_d4.rs`); ψ and τ_T folds. Refuted: u-frame symmetrisation (worse at n = 31), Z/3 grading (12–70× worse), isogeny-transported bases.
- **Degree of regularity.** Weil descent (`pq_descent_symbolic.rs`), matrix F4/F5, inherited F4, crossbred (crosses fes-f2 at ~26 unknowns, fails at 30 with default parameters), FES, hybrid guess + Macaulay (optimum is exhaustive), degree falls (D^* 4 ⟶ 2 to N = 16, then dies), Shantz–Teske δ (δ = +1…+2 lowers D^* by ~1 at n = 8, 9). Not found in the repo: Fourier–Motzkin / sparse-basis code.
- **Falsified (do not spend sweep budget):** 4/5/6-sum extraction on compact-orbit (`S·T²` ≳ `r/2n` bound), first-fall-degree measurement, m = 2 factor-base shape search (trace-class artefact), cyclotomic bases (yield-neutral), isogeny/volcano/conductor routes for Koblitz,

hybrid slicing, single large prime with bounded D, Z/3 grading, Veronese PDP, merge-level caps on the F_{p³} 2LP.

2.4 Two prior efforts that are not on `origin/main` (verified this session)

Both are on remote branches only; a plan that assumes they are merged is wrong.

N83 summand sweep, m = 2…9 (`origin/claude/sweep-n83-varied-algorithms-rovr0x`, tip `45208c41f2`; `research/n83_msweep_20261024/`, preregistered at `b654e95b6`). *Measured*, on the **a = 1** curve (53-bit subgroup), 4-vCPU cloud container, wall time:

- Every Weil-descent engine (F4/F5/F6/crossbred/SAT/FES) **silently returned "proved UNSAT" on planted n = 83 relations** because `FieldStructure` truncated the field to one 64-bit word; the descent builders now refuse an inexact field. A sweeper must treat *refused* as invalid, never as a score.
- Chained-S3 full-width SAT is the only decomposer that runs at n = 83 for every m, and within a 180 s cap decides only **m = 2** (17.3 s per public query; derived projection 2^75.9 s = 2^75.3 × rho). All m = 3…9 cells and every orbit-domain cell hit the cap.
- The m = 4 root-table rootfinder (complete DLP, K = 1107): 188.5 s (root11), 175.2 s (root22) against strong-rho 1.509 s: **116–125×** from rho.
- Companion n = 61 (exact one-word field), m = 2: native-XOR SAT fastest at D ≥ 12 (0.79–2.41 ms/query); inherited F4 fastest Gröbner engine; matrix F5 0.78–1.05× of F4; **m ≥ 3 refused by the 64-variable descent mask.**

Algebraic IC ladder (`origin/claude/ic-m2-linear-ladder-20261024`, tip `96e016772e`; `research/ic_m2_linear_ladder_20261024/`). *Measured*: the linear Weil-descent of S3 over `V = span{1..z^{d-1}}` solved 52/52 one-target DLPs on seven rungs n = 13…41; work slope **0.647 [0.639, 0.655]** $\log_2$ trials per bit of n against **1.079** for the F4 arm; n = 41 takes ≈ 8 min and is **36,440×** strong rho in wall time, widening with n. Its report records an **owner criterion dated 2026-10-24: an index-calculus pipeline counts only when its relations come from solving summation-polynomial systems over an algebraically defined factor base, without table collisions** (table pipelines — PDP4root, `engine=rootfind`, "aimed m = 3", pair enumeration — are excluded). That sentence is not yet in `AGENTS.md` on `origin/main` (grep found nothing); §6 turns it into an explicit decision.




Figure 1: distance to rho

Graph data and source: `graph_data.json`, `plot.py`. Recorded values only. Panel B's six values were checked against `origin/main:docs/ic/LEADERBOARD.md`; those rows are marked "unvalidated (pre-gate)" there (validation gate, 2026-10-19), so they are context, not admitted results.

2.5 Same-day skeptical review (desk review, not a measurement)

`/Volumes/SSD990-2/ic-regime-review-20261024/REVIEW.md` (2026-10-24; outside the repository, written by another session; every number in it is quoted from a file it names, and I did not re-verify them). The points that bear on this plan:

- **No published-IC baseline exists in the repo.** No experiment runs a standard FGHR-style symmetric Gröbner decomposition with the standard base `{P : x(P) ∈ F_q}` as the reference arm, and WDSat appears only in cryptanalysis `pdp-scaling`. Every "× times" in the program is against rho or against the program's own previous producer. The stated goal (2026-10-22) is to beat published IC at matched (q, n, m). The review's F2 proposes the reference protocol: standard base, FGHR symmetrised S_{m+1}, msolve (and WDSat for binary) as solver, cold whole-solve S in GAE.
- **The repo's own F4 is not a published engine.** `E3.md` on branch `prime-semaev-20261019` finds it needs 10^3–10^7 more operations than a brute grid on the same PKM systems, so any cost comparison that used the in-house F4 (e.g. "383–46,911× faster than F4" root-finding) is not evidence about published Gröbner solvers. Degree measurements that used msolve are unaffected.
- **Multiplier-closure wins at toy sizes do not transfer** (cm-multiplier, binary-multiplier, Z[τ] norm bases): the gain is at most the multiplier-set size and per-relation cost is unchanged; the review also records unfair controls in the Z[τ] n = 71 row. Its stop list includes toy-size multiplier comparisons, further twist/GLS at p < 1000, and new Koblitz rungs n = 85, 89.
- **The "+10 bits" m = 4 row is a w = 1 lower bound**; at the measured exponent (w ≈ 2.2–2.3) and K = 4–16 it is about +45 bits (the review's arithmetic, its F1 is the check). cryptanalysis `pdp-scaling` finds MITM best over 35–51 bits with algebraic solvers scaling worse (WDSat 3.0, CryptoMiniSat 3.95–6.97, msolve 5.25 bits per unit of l against MITM's 2).
- Rho conventions differ across documents (three in use), adding 25–30% unit noise to any cross-document ratio. The review asks which canonicalisation the N83 panel's rho uses; the sweeper's rho reference must record it.

3. Curves

Koblitz curves are $y^2 + xy = x^3 + a\,x^2 + 1$. Frobenius has order n and acts as λ on the prime subgroup; the signed orbit has size 2n.

id	family	n	$\log_2 r$	cofactor	role
a = 0, `debefd74`	Koblitz	83	**81.0**	4	**primary**
a = 1, `9eba6cd5` / `cdcc5432`	Koblitz	83	52.9	1,128,547,018	**control**
a = 0, `f27192f3`	Koblitz	97	95.0	4	registered, no runs
a = 1, n = 79 / 85 / 89 / 97	Koblitz	—	69.7 / 64.5 / 64.7 / 87.4	634 / $1.4{\cdot}10^6$ / $2.1{\cdot}10^7$ / 778	unregistered, no runs
prime ≈ 83 bits	any	—	—	—	none exists

Slugs are abbreviated to their hash suffix; the full ICV1 slugs are `icv1-f2m83-tm6151469093347-debefd74`, `icv1-f2m83-t6151469093347-9eba6cd5`, `icv1-f2m83-t6151469093347-cdcc5432` and `icv1-f2m97-t378251973071909-f27192f3`, all in `docs/curves/registry.json`.

- **Primary (a = 0, n = 83).** Modulus `z^83+z^45+z^2+z+1` (`known_n83_k0()`). Registered with order 9671406556923184866742756 but **no generator recorded** (`ec1_unresolved`: `KoblitzCurve` covers n ≤ 63). Rho only (~2^37.5 steps).
- **Control (a = 1, n = 83).** Two registered representations of one group (same trace and order): `9eba6cd5` (modulus `z^83+z^7+z^4+z^2+1`) and `cdcc5432` (modulus `z^83+z^45+z^2+z+1`, fixture `known_n83_k1`). The summand sweep ran its decomposers on `cdcc5432` and its rho reference on the `9eba6cd5` basis (its PROTOCOL.md says so). Results are quoted per representation and never merged by degree. IC runs end to end on this curve.
- **a = 1, n = 79 / 85 / 89 / 97.** Computed in the audit, not registered. n = 85 and 89 are on the §2.5 review's stop list, so not a priority.
- **Prime ≈ 83 bits.** None exists in the repository. The nearest, `fp-j0-b80` (cryptanalysis catalog), has a 32-bit prime subgroup.

Two curve names for degree 83 must never be merged by degree (`research/n83_evaluation_20261012/verification/CURVE_ID_ERRATUM.md`); the repository's curve-name lint (`AGENTS.md` §11, `scripts/check_curve_names.py`) applies to everything the sweeper emits.

Generation constraints (derived; to be confirmed as each generator lands).

- *Binary j = 0 / 1728.* In characteristic 2, 1728 ≡ 0, so j = 0 = 1728 is a single class and is **supersingular** (embedding degree ≤ 4). It is not an ECDLP target. It is included only as a labelled MOV/Frobenius control, not as a sweep objective.
- *Prime j = 1728* ($y^2 = x^3 + ax$) always has the point (0,0) of order 2, so prime order is impossible: target cofactor 2 (or 4). *Prime j = 0* ($y^2 = x^3 + b$, $4p = t^2 + 3v^2$, six twists) can reach prime order.

- *Random binary* curves always have a 2-torsion point (b ≠ 0): the minimum cofactor is 2. Point counting over F_{2^83} needs Satoh/AGM/SEA-type code; whether the repository has it (candidates: `ai_schoof.rs`, `binary_velu.rs`) is **unverified**.
- *Prime ≈ 83-bit* needs a wide prime field: `Fp64` stops at 62 bits. The Montgomery code in `certicom131-native-*` is a candidate to reuse.
- Koblitz counts are cheap (trace recurrence) and already done for the table above.

4. Objective

At n = 83 no end-to-end `S` exists (a = 0: no relation, rank or DLP solve; a = 1: only the root-table pipeline completes). So the objective cannot be an `S` measured at n = 83.

- **Primary scalar: projected S at the target size.** Fit $\log_2 S$ against n on a ladder of at least four rungs (`AGENTS.md` §5 requires ≥ 4 sizes), and optimise the fitted value extrapolated to n = 83 — for the a = 0 curve, with its own rungs (a = 0, n = 13, 19, 23, 41, … primes with #E = 4·prime) — plus the n = 83 diagnostics measured directly (decided fraction, seconds per query, capacity). *Derived, not measured*; reported as such.
- **Baselines, named and frozen before the search starts.** (i) *Incumbent algebraic baseline* per family: ecbench `pdp3-koblitz` with inherited F4 on the S4 Weil descent over `span{1..z^{d-1}}`, m = 3 (named by the ladder report), with the linear m = 2 ladder as the current best algebraic arm. (ii) *Matched rho*, with the canonicalisation recorded. (iii) *Published-IC reference arm*: **missing** (§2.5). Until P4b builds it, every result is reported as "vs the repository's incumbent" and "distance to rho", and none is called an improvement over published index calculus.
- **Scale-relative knobs.** Optimising S at one toy size selects configurations that only work at that size, because the base size scales like r^{1/3}. Every size-like knob is expressed relative to scale: base size as a multiple of the family optimum `(#E·t/k)^{1/3}`, `lp_domain_factor` as a ratio, descent dimension d as d/n.
- **Band-robust scalar.** Score a trial by the worst case of `S_trial / S_baseline` over unpriced-work weights w ∈ {0, 0.1, 1} (§5a), so a winner holds across the band by construction. The baseline is named and frozen before the search starts.
- **Two tracks, both reported, one counted.** Track A (algebraic: relations from solving summation-polynomial systems, no table collisions) is the counted track if the owner criterion in §2.4 governs this work. Track B (table / rootfinder / pair table / `mitm-frobenius` large primes) is run as the reference and context track and is never ranked against Track A as an improvement. This split is decision D1 in §6.
- **Determinism.** Budgets are operation or trial counts, never `solver_budget_seconds > 0` (non-deterministic). Counts stay single-threaded; parallelism is across trials, one process each. Only 25 instances have pinned calibration (`docs/ic/calibration.json`); elsewhere a solver row is `measured`, comparable only on the same host, and a `S` is a lower bound.
- **Failure classes.** Every trial ends in `ok` (verified), `exhausted` (budget hit, count recorded), `refused` (the model cannot represent the instance, e.g. inexact field, 64-variable mask), or `invalid` (verification failed). Only `ok` is scored. `refused` and `invalid` are logged and never silently dropped or treated as "no solution" (the n = 83 UNSAT bug in §2.4).

5. Plan

P0 — Setup and hygiene. Branch from `origin/main` (`ec77beacc9`). The two efforts in §2.4 are on unmerged branches: build on a branch that can later rebase onto them, and re-read their

cells before running anything so nothing is repeated (m = 2…9 on a = 1 n = 83; the m = 2 linear ladder n = 13…41). New cargo target directory, not an existing `cargo-target-ic-*/-sixsum-s4`. Avoid files held by live worktrees: `ghs_generalized.rs`, `ghs_quadratic.rs`, `binary_ecc/operation_tally.rs`, `f2m.rs`, `binary_ecc/mod.rs`, `cryptanalysis/mod.rs`. Register a Conductor task first (the control plane was unreachable from this session, §7).

P1 — Trial interface (Rust). A subcommand `ic sweep-trial` taking one configuration as JSON and printing one JSON record: failure class, `s` over the band, `verified`, per-stage counts, native counters, solver `priced_by`. Built on `run_pipeline`, so the objective is defined in one place and `ic bench` stays unchanged. Includes the §4 failure classes and an operation-count budget.

P2 — Search space. One typed schema, conditional where a parameter exists only for some choices:

group	dimensions
instance	family ∈ {prime-j0, prime-j1728, prime-generic, koblitz-a0, koblitz-a1, binary}; n or $\log_2 r$
arity	m ∈ {2…8}; split plan ([2,1,…,1] chain, [2,2], [3], [2,1])
factor base	kind (§2.1); size relative to family optimum; `norm=`, `mult=`, `divisor=i;j`, subspace dimension d/n, basis (polynomial / orbit / coordinate / random)
symmetry	negation, Frobenius-orbit fold, FGHR torsion invariants, GLV/GLS/CM group, D_4 / ψ folds
large primes	none / single / double; domain ratio; partial-relation cap; merge depth
solver	engine; D, k (crossbred); max_degree, split, node budget (matrix/inherited F4); XOR encoding (SAT)
linear algebra	incremental, structured, sparse

Known-dead regions (§2.3 falsified list) are excluded and cited in the schema.

P3 — Optimiser (in-tree Rust, no new dependency). TPE over a conditional categorical/log-integer space is small enough to write directly. `rand` and `rayon` are already in `Cargo.lock`; the trial store is an append-only JSONL file (resumable, mergeable across hosts, no SQLite dependency). Pruning: successive halving on the rung ladder — evaluate at the two smallest rungs first, promote only trials whose early S/S_baseline is within a margin of the running median. Parallel workers are separate OS processes. Deterministic given a seed. The optimiser is a library module with tests; it does not touch the framework traits.

P4 — Calibration tier (n ≤ 41), where S is measured. Run m = 2 and 3 first, over every family that exists. Extend `fb_hyperparam_sweep` to m = 3 (its report names this as the next arm). Fit exponents over ≥ 4 rungs against a frozen baseline per family. Replay the ladder's seven rungs as a regression test of the trial interface. Expected outcome (*derived from prior fits*): the sweep finds constants, not a changed exponent; both measured IC exponents (0.59–0.62) sit above rho's (0.44), so a verified constant-factor gain with the gap to rho reported as distance remaining is the realistic success under the owner's criterion.

P4b — Published-IC reference arm and external solvers. Specify and build the arm the review's F2 describes (standard base, FGHR symmetrised S_{m+1}, msolve, WDSat for binary, cold whole-solve S in GAE) on the existing ladder sizes, and add adapters that run msolve, WDSat and CryptoMiniSat as sweepable engines beside the in-house ones. External-solver cost is priced by wall time (`measured`), so such rows are comparable only on the same host. This is the precondition for using the words "beats published".

P5 — Wide tier (n = 61…83). Lift the u64 caps so `S` is measured above n = 63: plug `Gf2_128`/`koblitz_wide`/wide mod-r arithmetic into the framework (the `InstanceCtx r: u64`, `CountedGroup::mul k: u64` and linalg u64 limits are the known blockers). Descent builders must keep refusing inexact fields. For prime curves, add a wide prime field. n = 83 on the a = 0 curve gets diagnostics only (decided fraction, seconds per query, capacity per query), labelled as stage diagnostics (§4).

P6 — m = 4…8. Cheapest route: wrap `pdp-split` chained-S3 plans ([2,1,…,1]) as a framework oracle; check the longest plan it accepts before promising m = 7, 8 (it needs b = 1 Koblitz and refuses unsplit S5). The n = 61 companion shows m ≥ 3 algebraic descent is blocked by the 64-variable mask, so a precondition is moving the descent builders to the wide (≤ 128-variable) monomial type from `wide_groebner.rs`. The summand-sweep result (all m ≥ 3 SAT cells capped at n = 83) is the prior to beat, not to repeat.

P7 — Curves. One generator per family behind a common trait, each emitting the curve, its group order, prime-subgroup order, cofactor and a primality certificate; registered in `docs/curves/registry.json` with full ICV1 ids. The a = 0 n = 83 curve is already registered but has no generator or subgroup record; completing that record (generator, prime-subgroup order, EC1 representation) is the first P7 item. A delegated audit reported it as unregistered; that was wrong and is corrected here.

- Prime j = 0: CM construction ($4p = t^2 + 3v^2$), choose the twist with prime or smallest-cofactor order; wide `Fp` required.
- Prime j = 1728: cofactor 2 or 4 (§3).
- Generic prime and random binary: needs a point counter first (§3).
- Binary j = 0/1728: supersingular, labelled control.
- Ladders per family at sizes spaced to give ≥ 4 rungs below 62 bits, then the 83-bit instance.

P8 — Reporting and landing. Every run leaves a report, a graph and a PDF (`research-visuals` skill). Performance gains also copy into `benchmarks/`. No leaderboard row without a replay certificate, validator report and matched rho with the §5a band (validation gate, 2026-10-19). Each landed trial batch is a preregistered protocol plus raw records plus fit, mirroring the ladder's layout (`PROTOCOL.md`, `raw/*.json`, `fit.json`).

6. Decisions still open

- **D1 (needs the owner).** Does the 2026-10-24 algebraic-only criterion govern the sweeper's counted track? It excludes the large-prime collector that exists today (`mitm-frobenius:large_primes`) and every pair-table arm. If it does, double-large-prime has to be rebuilt on the algebraic side (the `gaudry_cubic.rs` eliminator and the unwired `large_prime_filter.rs` are the starting points). The plan above defaults to two tracks, one counted.
- **D2.** Are n = 61 companion curves (unregistered by design, for registry size reasons) acceptable as calibration rungs for the a = 0 family?
- **D3.** Is a supersingular binary j = 0 control wanted at all, given that it cannot be an ECDLP target?

7. Risks, and what this note does not establish

- Both measured IC exponents exceed rho's, and the algebraic arm is 36,440× rho at n = 41 and widening. A sweeper cannot change that slope; it can shrink constants and find the regions where an engine is least bad.
- Everything at n = 83 on the a = 0 curve is a diagnostic until a decomposition oracle decides queries there (it does not today: every attempt ended UNKNOWN, `BOUNDED_*` or at the cap).
- Several ratios in the cited documents are weight-0 lower bounds recorded before the §5a rule.
- **Rung gap on the primary family.** The a = 0 curves with cofactor 4 and prime degree are n = 41, 83, 97 in the 24–130 range (cryptanalysis README); the intermediate a = 0 rungs (53, 61, 71, 73) have cofactors of 10^4–10^6. A fit projected to n = 83 therefore either extrapolates by 2× in n from n = 41, or mixes cofactors across rungs. The note does not resolve this; the fit must report which it did. The a = 1 control has the opposite problem (large cofactor at every rung).
- The Conductor control plane was unreachable from this session (404), and the sandbox blocked creating `.mcp.json` in the worktree. The lead atlas named in `CLAUDE.md` was not found in the sibling `crypto-autoresearcher` checkout (an old commit), so it was **not consulted**.
- The "Optimal-shift" session works in `crypto-autoresearcher` (`tools/smallroot_reach.py`); it reports its reach calculator has a sign error (S3 reach ≈ 0.28, not 0.8408). Nothing here relies on those figures.
- Sources read by delegated read-only audits and not re-verified line by line: the technique and curve inventories, and the leaderboard values in `graph_data.json` panel B.

8. Status: plan steps 1–3 built (2026-10-24, later the same day)

Implemented on branch `feat/ic-sweep-trial-20261024` (stacked on this note's branch), documented in `docs/ic/SWEEPER.md`:

- **P1, the trial interface** — `ic sweep-trial`. Scores from operation counts alone, `S(w) = (adds + doubles + w · native operations) / √r`. This follows from §5a: the pinned calibration ratios cancel between `G − C` and `n_C`, so no host timing or calibration enters. *Measured:* the n = 13 baseline scored `S = [19.1, 143911.0, 1438937.6]` in both a debug and a release build. Failure classes `exhausted / invalid / refused / invalid_config / crashed` are never scored. Time and memory limits are enforced from inside the process (`ps`

is unavailable in the sandbox; macOS ignores `RLIMIT_AS`); the time limit fired at 600.1 s in the three runs that reached it.

- **P2, the search space** — four typed, conditional, scale-relative spaces. The algebraic ones are the counted track; the table ones are tagged reference-only in code. `rootfind-*` is offered by no space, pending the owner's ruling (§6, D1 follow-up).
- **P3, the optimiser** — in-tree TPE, median pruning over the rung ladder, an append-only resumable store, one child process per trial. 42 unit tests, two of them end-to-end through the real pipeline.

Findings from building it (each measured):

1. A tagged-enum parse of the store failed on every `f64`, because the workspace enables `serde_json`'s `arbitrary_precision`. The store now reads through `Value`.
2. My first sampler defaults were wrong. On three synthetic problems (`tune_defaults`, 40 studies × 60 trials) a wider good-fraction (`gamma` 0.25) was worse everywhere; `gamma` 0.10 with a 15% exploration probability gave regret 0.211 against random's 0.407 (smooth), 0.004 against 0.050 (conditional), and 0.157 against 0.118 on a problem built to defeat independent models, the one case where it is worse than random.
3. **The ladder report's baseline does not run through this framework.** The framework's `descent-algebraic` with inherited F4 at `m = 3` finishes only at n = 13 (21 s in release); n = 15, 19 and 23 each hit a 600 s limit. The `m = 2` arm finishes on all four (about 1, 1, 1 and 27 s). The study baseline is therefore the `m = 2` arm, and §4′s reference to the `m = 3` `pdp3-koblitz` arm stands only for ecbench, not for the sweeper.
4. **K_0 degrees that exist** (`koblitz_instance(0, n)`, n ≤ 63): 9, 13, 15, 19, 23, 31, 37, 39, 41, 45, 51, 53, 57, 59, 61. n = 17 does not. K_1: 9, 11, 15, 17, 19, 23, 29, 43, 45, 47, 51, 57, 59, 61.

First study (a smoke run of the tool, not a result). `koblitz-algebraic`, K_0, rungs 13/15/19/23, 18 trials, 3 workers, 90 s per trial: finished in 4 min 16 s; 6 complete, 6 pruned, 6 failed. The n = 23 baseline hit the 90 s cap under load, so 3 rungs were usable, below `--min-fit 4`, and nothing was projected (reported as such). **No configuration beat the baseline**: the best trial is +2.41 in log2 (5.3× worse). All 6 failures were `exhausted` (Crossbred recovered no logarithm at these sizes; a SAT and an F4 run reached the cap). Eighteen trials on a small space says little; it shows the loop, the classes, the pruning and the store behave.

Not done: widening the framework past n = 63 and `m ≥ 4` (plan P5, P6); the published-IC reference arm (P4b); prime and random-binary curve generation (P7); the §5a band for rho itself (the record's rho gap is a `w = 0` lower bound); a larger study with four usable rungs and a projection.