1. Chained Jacobian transfers over F_{101}

2026-11-11 · crypto PR 3877 · cryptanalysis PR 1469 · queue 3904

Standing: unverified producer assertions. The initial Jacobian target is isomorphic to its source. A second fixture has nonisomorphic Jacobians over F101, distinguished by rational 2-torsion. Both complete elliptic endpoint functions match direct elliptic shortcuts. There is no measured DLP advantage. Full report, primary sources and raw receipts are retained beside this PDF. [pcc:unverified]

1.1. Initial explicit route and controls

E: $v^2=u^3+1$, $P=(4,41)$, $r=17$. The degree-two cover $f(x,y)=(x^2,y)$ from C: $y^2=x^6+1$ induces whole-fiber pullback into Jac(C). The ordered splitting $(x^2+1)(x^2+10x-1)(x^2-10x-1)$ has determinant40. Kunzweiler's normalized Richelot correspondence gives a degree-four map R to $\mathrm{Jac}(C_2)$, C_2: $w^2=41z^6+9z^4+9z^2+41$.

The first target quotient, $X=41z^2, V=41w$, reaches E_2: $V^2=X^3+9X^2+66X+39$ and sends P to (91,84), order17. The second target quotient annihilates this subgroup, as does the anti-invariant source norm on $f_*(E)$. These are explicit zero controls. [pcc:unverified]

Canonical classes use $t=1/(x-10), Y=yt^3$ with odd quintic $F(t)=1+60t+86t^2+2t^3+15t^4+60t^5$. Whole fibers include nonsplit support, multiplicities, Weierstrass points, both original infinities and degree drops. Unsupported input and elliptic identity are different outcomes. All10,404 source classes are admitted; kernel4 and image2601 have equal four-element fibers. Both sign-corrected dual compositions give[2] on the complete source and target. Source norm gives[4] on E, inverted by13 modulo17 to recover encoded points. This does not recover unknown DLP scalars. [pcc:unverified]

1.2. Two retained equivalences

C_2 is F101-isomorphic to C. Put $r=10, r^2=-1$: $x=(z-1)/(z+1), y=8r\,w/(z+1)^3$. Its inverse is $z=(1+x)/(1-x), w=-r\,y/(1-x)^3$. The aligned odd charts obey $t=56+10T, Y=79Z$. Every10,404 rational class round-trips. Cleared identities compile in Lean; projective/Picard geometry is not formalized. R becomes a nontrivial endomorphism after model identification, not a new destination. [pcc:unverified]

On all102 source elliptic points the full endpoint equals $\tau\,\varphi[2]$, where φ is the historical degree-two elliptic quotient and $\tau(U,V)=(82U+60, 98V)$. Future cost comparisons must include this direct shortcut. No cost ratio follows from finite functional equality. [pcc:unverified]

1.3. Nonisomorphic successor and its limitation

The model-tagged backend accepts ordered quadratic splittings and rational Weierstrass bases over **fixed F101**. It rejects mixed-curve/chart arithmetic; it does not yet generalize fields. The preselected successor is $G_1=x^2-1, G_2=x^2+x+4, G_3=x^2-x+4$, determinant$91=-10$:

- C_s: $y^2=x^6+6x^4+9x^2-16$, base$(1,0)$.
- C_t: $w^2=20z^6+81z^4+83z^2+21$, base$(2,0)$.

Each Jacobian has9,216 rational classes; all are admitted. Transfer fibers have size4 and both dual compositions are[2]. The source rational2-torsion has cardinality4 and target16. The unchanged BigUint reference independently recounts these as self-inverse classes, obtains order9,216 from Fp/Fp^2 point counts, and checks paired additions and dual norms on both complete sets. The first reference run used the development tree; immutable pin/replay is tracked separately. [pcc:unverified]

An F101 abelian-variety isomorphism induces a rational group isomorphism commuting with[2], hence equal rational2-torsion cardinalities. Uniqueness of reduced Mumford representatives gives a second derivation: self-inverse pairs have $v=0$ and monic u dividing the odd quintic, degree≤ 2. The source factor pattern is$1+2+2$ with both quadratics irreducible, so there are4 choices. The target has five rational quintic roots, giving$1+5+10=16$ choices. Closed quadratic support must be counted. Thus these Jacobians cannot be F101-isomorphic; no algebraic-closure nonisomorphism is asserted. [pcc:unverified]

The source elliptic quotient has96 points, largest odd prime factor3, $P=(48,20)$. Its transferred class is nonzero of order3, first target norm $(2,72)$, second norm zero. The normalized first target elliptic curve is $V^2=X^3+81X^2+44X+17$. This tiny subgroup is retained explicitly rather than substituted for the original $r=17$ fixture. [pcc:unverified]

The successor endpoint also equals a direct shortcut on all96 source points. Shift $U=u-1$, so $Y^2=U^3+9U^2+24U$. The standard quotient by$(0,0)$ is $V^2=X^3+83X^2+86X$; $\tau(X,V)=(100X+80,91V)$ identifies its target with the endpoint. The full function equals $\tau\ \varphi$[2]. All F101 affine coordinate isomorphisms satisfying the coefficient identities were checked; this sign uniquely matches. A nonisomorphic Jacobian hop still does not establish a new elliptic reduction or a computational advantage. [pcc:unverified]

Claims: PCC-20261111-a282a9(model equivalence), ae88cc(successor), 6e9e6b(successor shortcut); cryptanalysis21e28e(reference development). All remain unsigned and unverified.

1.4. Formal obligations and prime-field boundary

Core Lean4.35.0 is pinned. Nine structural lemmas cover norm composition, Bézout recovery/ injectivity, scalar relations, anti-invariant zero controls, torsion invariance and the characteristic obstruction. Eight polynomial lemmas cover cleared splitting, target numerator, chart and coordinate isomorphism identities. Gates audit21+8 declarations with standard foundations only(propext,Classical.choice,Quot.sound), no trusted native declarations. Actual Jacobians and their dual norm identities remain explicit hypotheses of the structural proofs. [pcc:unverified]

A unital additive map from characteristic p to q requires q dividing p. For distinct primes this forbids field maps, not arbitrary efficiently encoded cyclic subgroup transfers. A prime field has no proper subfield, so ordinary Weil restriction provides no smaller-base-field descent. Lifts and cross-prime reductions remain separate open mechanisms. [pcc:unverified]

The full projective/Picard/Richelot bridge remains open. Claims7a3fe0, a00fb9,a97961,ced5d7 are unverified until their actual signed standing changes. The two new proof records initially omitted theorem bindings; their initial incomplete bytes are retained and the correction appends ledger events, without altering any ledger history or published claim.

1.5. Reproduction, checks and gates

Run the standalone native Cargo tests and strict Clippy, then both Lean files through tools/lean/ proof-gate.sh. Root examples chained_jacobian_reference and chained_jacobian_identities now pass15 and1 tests, including the generic model extension. The native suite passes14 tests and strict Clippy. Two local replay-accepted identity certificates bind the polynomial Lean source digest. These are development checks, not signed independent validation. [pcc:unverified]

Cryptanalysis PR1469 freezes the original baseline at crypto18db046 with source/reference digests and a fail-closed check script. Original receipts remain immutable. The full crypto library run is still in progress and has reported failures in untouched historical modules. Keep failed elaboration, missing-dependency and lint attempts; never label them passed. [pcc:unverified]


No performance experiment has been launched. S3 checkpoint admission is unavailable, and live IsoLab budget/capacity is unknown. The research-KB and ecdb are unavailable; crypto-autoresearcher is vault locked without a key binding. The current-main PCC ledger fork is a merge blocker, not something to repair by rewriting history. Newly added workflows require default-branch registration before manual dispatch. GitHub CI and required reviews still apply. The queue names every blocker and next action.

Next: immutable successor replay, a second nonbacktracking Jacobian hop, field generalization, independent signed validation and an admitted total-cost comparison including both direct elliptic shortcuts. Canonical transfer and leaderboard graphs receive no promotion from this unsigned fixed-field work.

Primary sources: Galbraith, corrected Mathematics of Public Key Cryptography, ch.8 §8.3 and ch.10 §§10.3–10.4,10.6; Kunzweiler, DCC92(2024),1761–1802, DOI10.1007/s10623-024-01366-1, Proposition1 and §§3.1–3.2. Full PDFs were read; retrieval gaps and exact hashes are in SOURCES_20261111.md.

2. Explicit routes and controls

F101 chained Jacobian fixture · producer development evidence · PCC unverified



All objects and maps use F101. Solid edges are actual development maps; dashed edges are zero controls; dotted edges are complete finite endpoint shortcuts. The successor's different rational2-torsion counts obstruct a base-field Jacobian isomorphism. No edge denotes a measured DLP advantage. [pcc:unverified]