Independent graph-adapter review

Private component evidence, 31 October 2026 UTC. Producer packet: `pencil-kummer-graph-integration-20261031`.

Replay and custody. All 30 producer manifest entries match. Private offline native replay exited 0 and reproduced stdout byte for byte. A separately written Python matrix eliminator checked 70 geometric prefixes and nine synthetic prefixes. All 21 subgroup moduli per arm were checked prime.

Observation	Eager	Candidate
Original-G transitions	63	63
Inserted equations	35	35
Nonsplit quadratics	26	26
Recovery failures	2	0
Degree-one gate skips	0	2
Geometric graph cycles	0	0
Geometric terminal returns	0	0

The 35 equations are identical between arms. The two additional recovered degree-one divisors are rejected by the degree-two graph interface, so emitted-edge gain is zero in this fixed fixture. No trajectory was extended to seek a cycle.

Source correspondence. The adapter consumes the recovered signed divisor before constructing the reference $aG + bQ$. Quadratic roots and $v(x)$ supply signed point nodes. The equation is $s_u X_u + s_v X_v = a + bk$, represented by dense elimination as $[A, -b \mid a]$. The signed union-find implementation and the independently implemented dense matrix reference agree at every insertion. Reviewer Python elimination also agrees. Every geometric row increases row rank, with no target-only equation.

Separate stopping controls. Synthetic signed equations over $\mathbb{F}_{101}$ return the planted value 7 at prefixes 3, 2, and 4. They cover positive-cycle stopping, negative-cycle anchoring, and a target-free repeated-edge cycle followed by stopping. Each intentionally unconsumed trailing sentinel is inconsistent. These are equation controls, not geometric cycle observations.

Scope. No blocking discrepancy was found in these component claims. The historical collector filters before recovery; this wrapper recovers before filtering. Thus emitted-equation semantics are checked, not production scheduling or total costs. Individual graph nodes are not proved to lie in the prime-order subgroup. Geometric scalar-return, duplicate, and repeated-root branches were not exercised. No timing or cost ratio is assigned.

Artifacts. `review.json` contains exact source hashes and scoped findings; `PLAN.md` preceded source/raw inspection; `snapshot/receipt.json` retains the native command and exit; `independent-counts.json` and `overview.svg` provide structured counts and diagram. No producer repair, root build, cloud action, or scientific run occurred.