Union, polynomial division and runtime prerequisites

This packet advances the signed-graph union invariant and the monic quotient correspondence, and independently checks the proposed mount-diff parser. A separately built native checker and independent integer recomputation also verify the retained Kummer matrix bindings. These are formal, source and saved-certificate results; the original 1,260-target scientific scope is unchanged.

Signed graph union	Monic quotient	Retained Kummer	Runtime prerequisites
Global equations	Overwrite and return	105 matrix identities	43 parser controls
25 reviewed readbacks	32 reviewed readbacks	independent recomputation	adapter still separate

Union mutation. Five main declarations, eight producer controls and twelve independent reviewer controls passed twenty-five named axiom readbacks. The invariant covers every vertex equation and every stored anchor through either union direction, including signed descendants and a retained child anchor. Both-fixed roots yield the correct target when the constraint coefficient is nonzero, and consistency when it is zero. The model starts after find; forest/size preservation, allocation and concrete storage remain separate.

Monic division. Seventeen main declarations, nine producer controls and six independent reviewer controls passed thirty-two named axiom readbacks. The proof models coefficient overwrite, proves each selected quotient slot is fresh, preserves A=QB+R, and proves termination and the exact returned quotient. It uses the existing checked word-remainder loop under canonical monic inputs and prime p<2^31. Native quotient-vector storage/trim and general nonmonic inverse/extended-GCD behavior remain separate.

Retained Kummer matrices. All 105 ordered matrices across the 21 models satisfy M^2=cI with nonzero c and match the saved scalars. Twelve historical source pins match. Independent integer recomputation agrees on every matrix and normalized root; eight adverse controls preserve the distinction between native rejection, inventory rejection and external source-binding rejection. The checker alone accepts an altered walk file, so exact frozen hashes are a required acceptance component. Native row-fold and executed-binary provenance remain separate.

Runtime parser. Independent fixed controls accepted seven cases and rejected thirty-six malformed cases. Accepted records retain writer_attribution=null and no_writes_claim=false. Historical qualification v5 remains failed with Q0 alone passed. The actual supervisor still requires empty diff; the reviewed parser is not integrated. AMENDMENT_REQUIREMENTS.md lists the precise callsite, identity, transport, binding and qualification obligations.

Review sequence. The prospective joint plan was published before cross-review. Producer proof sources were published before independent review dispatch. All initial failures and source snapshots remain in the packet. Compiler success, named axiom inventories and source-fidelity review are separately recorded. No new scientific execution, timing measurement or cost ratio is supplied by this packet.