Isogeny-form guessing optimum (lead B)

Protocol: PROTOCOL.md (frozen before data, commit f9e1f3855a). Scope of every statement: **isogeny form, m = 2, mode full, lifts 0, k in {20, 24, 28}, only the (t, G) cells listed, 100 random subgroup targets per cell** (fewer where stated). No claim for other k, t, G, m or form, and no distance to Pollard rho (lead A, different unit).

Answer in one paragraph

Within the measured range the guessing cost does **not** turn up. At k = 20, for every t from 6 to 10, F4 multiply-adds per target fall at every step from G = 4 to G = t-1, and the argmin is the largest G allowed (G = t-1) in all five series, so no minimum is bracketed. The steps do not flatten as G approaches t: the final step is the largest ratio in the series for t = 9 and 10 (t = 10: 2.2, 4.1, 5.1, 3.7, 6.9 per step; t = 8 is the exception, 3.8, 4.8, 4.4). The same holds at k = 24 and 28 for t = 10 (G = 7..9) and at k = 24 for t = 12 (G = 9..11). The frozen U-shape prediction P1 is false and the falsifier P3 occurred. Where the optimum lies beyond G = t-1 cannot be asked: `pkm-semaev` refuses G >= t, and also G > 12 (found here). The k = 28, t = 14 coverage-matched series produced no data (OOM, wall-limit, and the G <= 12 refusal; see Failures).

Method

- Binary `/home/user/frozen-bin/curve25519_family_leadB`, sha256 `fc72092faa52e34f6fa1fb5eeea459b466b4b780416c6724724134374e057311`, built from the unmodified source of main 56c3e282ee (no code change in this lead). After the coordinator's warning about the shared target dir, the binary was rebuilt inside the cargo flock after `touch` of `src/bin/curve25519_family.rs` and `src/cryptanalysis/ic_framework/pkm_semaev.rs`: the sha256 was identical (`fc72092f...`), and `git diff 56c3e282ee..HEAD -- src` is empty. So the measured binary is from this worktree's source (done after stage 1 and 2 had started, before the report).
- Cell command: `( ulimit -v 3500000; timeout 1000 <bin> f4cost <k> isogeny <t> <G> 100 <seed> <cap_s> 2 full 0 )`, sequential, driver `analysis/run_cells.sh` (stage 1: `analysis/stage1.sh`, cap 600 s; stage 2: `analysis/stage2.sh`, cap 900 s). Raw: `analysis/cells.jsonl` (27 ok cells, 27 KB, sha256 `315ce49a8d9a18eb3422836f6ebee44b24a6acf0b6108579bbb7e9ee8400de98`), `analysis/cells.jsonl.status` (30 lines: 30 cells attempted, 27 ok, 3 failed; sha256 `93fac7f58171fc61347457b346c936b6a4e3be56740313eeeea08861347c9b11`), `analysis/stderr/` (empty for every ok cell; the two non-empty files are the failed cells), `analysis/support.jsonl` (lambda). Tables and figure: `analysis/make_tables.sh` (jq + awk). Run locally, not on EKS.
- Seeds: stage 1 `2026111600+t`; reproduction `2026111400+t` (lead 4's seeds); stage 2 `2026111700+t` (k = 24), `2026111800+t` (k = 28).
- Stage-2 rule applied mechanically: the lowest PR(cov) among uncapped stage-1 cells is t = 10, G = 9 (1.18e7), an edge cell, so the window is {7, 8, 9} (2a, fixed t = 10), and the coverage-matched t' = 12 (k = 24), 14 (k = 28) with G' = round(0.9 t') = 11 (k = 24), 13 (k = 28), edge, window {9,10,11} and {11,12,13} (2b).
- Load: `uptime` 1-minute load at each cell start is the last column and in the JSON (`load_at_start`); the box was shared (load 2 to 12). No cell hit the wall cap; wall times are not compared.

Full table


Columns: stage (s1, repro, s2a fixed t = 10, s2b coverage-matched t); k; t; G; targets done/requested; CAP = cap hit (none did); mul/tgt = F4 multiply-adds per target; calls/tgt = F4 calls per target (below 2^G because a target stops at its first hit); deg = max solving degree; und = undecided; h/v = hits/verified hits; lam = lambda from `support`; PR(lam) = mul/tgt / lam (modelled, cofactor-aware yield, lower figure); cov = `coverage_exact`; PR(cov) = mul/tgt / cov (modelled); obs = total muladds / hits

(observed, only where hits >= 1; at most 34 hits, not a ranking basis); unch = uncharged native field mults (system + grid reading) as share of charged muladds; load = 1-min load at start.

stage	k	t	G	targets	cap	mul/tgt	calls/tgt	deg	und	h/v	lam	PR(lam)	cov	PR(cov)	obs	unch	load
s1	20	6	4	100/100	-	7.1e5	16	5	0	0/0	0.00953	7.45e7	0.00131	5.42e8	-	0.041%	3.16
s1	20	6	5	100/100	-	1.46e5	32	4	0	0/0	0.00953	1.54e7	0.00131	1.12e8	-	0.306%	3.39
s1	20	7	4	100/100	-	9.43e6	15.55	5	0	4/4	0.06265	1.51e8	0.00905	1.04e9	2.36e8	0.01%	3.52
s1	20	7	5	100/100	-	1.83e6	31.47	5	0	4/4	0.06265	2.92e7	0.00905	2.02e8	4.57e7	0.069%	3.74
s1	20	7	6	100/100	-	4.13e5	61.99	4	0	4/4	0.06265	6.6e6	0.00905	4.57e7	1.03e7	0.377%	3.85
s1	20	8	4	100/100	-	8.77e7	15.79	5	0	2/2	0.24609	3.57e8	0.03512	2.5e9	4.39e9	0.002%	4.11
s1	20	8	5	100/100	-	2.32e7	31.61	5	0	2/2	0.24609	9.42e7	0.03512	6.6e8	1.16e9	0.008%	3.54
s1	20	8	6	100/100	-	4.84e6	63.1	5	0	2/2	0.24609	1.97e7	0.03512	1.38e8	2.42e8	0.051%	3.97
s1	20	8	7	100/100	-	1.1e6	127.24	4	0	2/2	0.24609	4.49e6	0.03512	3.14e7	5.52e7	0.283%	4.13
s1	20	9	4	100/100	-	7.75e8	14.24	5	0	17/17	0.62774	1.23e9	0.11834	6.55e9	4.56e9	0.006%	5.32
s1	20	9	5	100/100	-	2.23e8	28.58	5	0	17/17	0.62774	3.56e8	0.11834	1.89e9	1.31e9	0.02%	6.35
s1	20	9	6	100/100	-	5.3e7	56.68	5	0	17/17	0.62774	8.45e7	0.11834	4.48e8	3.12e8	0.087%	6.73
s1	20	9	7	100/100	-	1.26e7	111.87	5	0	17/17	0.62774	2e7	0.11834	1.06e8	7.39e7	0.376%	7.68
s1	20	9	8	100/100	-	2.23e6	226.36	4	0	17/17	0.62774	3.56e6	0.11834	1.89e7	1.31e7	2.166%	7.22
s1	20	10	4	100/100	-	5.24e9	12.93	5	0	29/29	0.97761	5.36e9	0.38229	1.37e10	1.81e10	0.006%	7.72
s1	20	10	5	100/100	-	2.39e9	25.57	5	0	29/29	0.97761	2.45e9	0.38229	6.26e9	8.25e9	0.013%	8.79
s1	20	10	6	100/100	-	5.89e8	51.36	5	0	29/29	0.97761	6.03e8	0.38229	1.54e9	2.03e9	0.052%	11.93
s1	20	10	7	100/100	-	1.15e8	103.23	5	0	29/29	0.97761	1.18e8	0.38229	3.01e8	3.97e8	0.267%	11.48
s1	20	10	8	100/100	-	3.1e7	204.58	5	0	29/29	0.97761	3.17e7	0.38229	8.1e7	1.07e8	1%	12.29
s1	20	10	9	100/100	-	4.52e6	405.69	4	0	29/29	0.97761	4.62e6	0.38229	1.18e7	1.56e7	6.902%	11.87
repro	20	6	4	100/100	-	7.1e5	16	5	0	0/0	0.00953	7.45e7	0.00131	5.42e8	-	0.041%	12.02
repro	20	7	4	100/100	-	9.7e6	16	5	0	0/0	0.06265	1.55e8	0.00905	1.07e9	-	0.003%	12.02
repro	20	8	4	100/100	-	8.64e7	15.54	5	0	4/4	0.24609	3.51e8	0.03512	2.46e9	2.16e9	0.003%	12.01
s2a	24	10	7	100/100	-	1.42e8	127.07	5	0	1/1	0.22957	6.17e8	0.03246	4.37e9	1.42e10	0.009%	4.29
s2a	24	10	8	100/100	-	3.85e7	254.11	5	0	1/1	0.22957	1.68e8	0.03246	1.19e9	3.85e9	0.039%	6.70
s2a	24	10	9	100/100	-	5.65e6	507.52	4	0	1/1	0.22957	2.46e7	0.03246	1.74e8	5.65e8	0.312%	7.41
s2a	28	10	7	100/100	-	1.43e8	128	5	0	0/0	0.01533	9.32e9	0.00193	7.4e10	-	0.002%	7.71
s2a	28	10	8	100/100	-	3.88e7	256	5	0	0/0	0.01533	2.53e9	0.00193	2.01e10	-	0.012%	6.97
s2a	28	10	9	100/100	-	5.7e6	512	4	0	0/0	0.01533	3.72e8	0.00193	2.96e9	-	0.126%	8.32
s2b	24	12	9	100/100	-	7.03e8	402.65	5	0	34/34	0.98012	7.17e8	0.38711	1.82e9	2.07e9	0.814%	8.43

stage	k	t	G	targets	cap	mul/tgt	calls/tgt	deg	und	h/v	lam	PR(lam)	cov	PR(cov)	obs	unch	load
s2b	24	12	10	100/100	-	1.81e8	793.74	5	0	34/34	0.98012	1.84e8	0.38711	4.66e8	5.31e8	3.173%	11.05
s2b	24	12	11	100/100	-	2.4e7	1576.71	4	0	34/34	0.98012	2.45e7	0.38711	6.21e7	7.07e7	23.871%	8.18

Not in the table (failed, no data): s2b k = 28, t = 14, G = 11, 12, 13 (see Failures).



F4 multiply-adds per target vs G

`analysis/guess_optimum.svg`: log-scale F4 multiply-adds per target against G, one line per (k, t) series; all points are uncapped.

Argmin per series, bracketing

Argmin = lowest multiply-adds per target (coverage is constant inside a (k, t), so the PR(cov) argmin is the same cell). “Bracketed” needs a measured smaller-G and a measured larger-G neighbour, both higher.

stage	k	t	G measured	argmin G	mul/tgt at argmin	bracketed?	cap
s1	20	6	4..5	5	1.465e+05	edge (largest G measured)	no cap
s1	20	7	4..6	6	4.134e+05	edge (largest G measured)	no cap
s1	20	8	4..7	7	1.104e+06	edge (largest G measured)	no cap
s1	20	9	4..8	8	2.232e+06	edge (largest G measured)	no cap
s1	20	10	4..9	9	4.519e+06	edge (largest G measured)	no cap
s2a	24	10	7..9	9	5.653e+06	edge (largest G measured)	no cap
s2a	28	10	7..9	9	5.703e+06	edge (largest G measured)	no cap
s2b	24	12	9..11	11	2.403e+07	edge (largest G measured)	no cap

No series is bracketed. Every argmin is the largest G measured, and for t = 6..10 (k = 20), t = 10 (k = 24, 28) and t = 12 (k = 24) that is G = t-1, the largest the code permits. The argmin ratio G/t is therefore (t-1)/t: 0.83, 0.86, 0.88, 0.89, 0.90 for t = 6..10 at k = 20; 0.90 at k = 24 and 28 (t = 10); 0.92 at k = 24 (t = 12). That is the boundary of the allowed range, not a measured optimum, and it says nothing about stability of an interior optimum.

Step ratios (cost at G divided by cost at G+1)

All ratios are above 1.25 (resolved by the frozen criterion; every cell uncapped); the smallest is 2.19.

series	step	ratio	cap
s1 k=20 t=6	G=4 to 5	4.85	-
s1 k=20 t=7	G=4 to 5	5.16	-
s1 k=20 t=7	G=5 to 6	4.42	-

series	step	ratio	cap
s1 k=20 t=8	G=4 to 5	3.78	-
s1 k=20 t=8	G=5 to 6	4.79	-
s1 k=20 t=8	G=6 to 7	4.39	-
s1 k=20 t=9	G=4 to 5	3.47	-
s1 k=20 t=9	G=5 to 6	4.21	-
s1 k=20 t=9	G=6 to 7	4.22	-
s1 k=20 t=9	G=7 to 8	5.63	-
s1 k=20 t=10	G=4 to 5	2.19	-
s1 k=20 t=10	G=5 to 6	4.06	-
s1 k=20 t=10	G=6 to 7	5.12	-
s1 k=20 t=10	G=7 to 8	3.72	-
s1 k=20 t=10	G=8 to 9	6.86	-
s2a k=24 t=10	G=7 to 8	3.68	-
s2a k=24 t=10	G=8 to 9	6.81	-
s2a k=28 t=10	G=7 to 8	3.68	-
s2a k=28 t=10	G=8 to 9	6.80	-
s2b k=24 t=12	G=9 to 10	3.89	-
s2b k=24 t=12	G=10 to 11	7.51	-

Pairing: within a (k, t) all G share the same 100 targets, so the ratios compare like with like, but the tool emits no per-target costs and no interval is given. The last step is the largest in the series at t = 9, 10 (k = 20), at k = 24, 28 (t = 10) and at k = 24 (t = 12); not at t = 6, 7, 8: the max solving degree drops 5 to 4 at G = t-1 in every series (the `deg` column), which is where the extra gain over the nominal 2x-per-level comes from; that attribution is a reading of the `deg` column, not tested.

Predictions (frozen in PROTOCOL.md)

- **P1 (U-shape, argmin at t-3 or t-2 for t = 8, 9, 10, with G = t-1 resolved worse): false.** Argmin is t-1 for all of t = 8, 9, 10 (G = 7, 8, 9), and cost at t-1 is lower than at t-2 by 4.4, 5.6, 6.9.
- **P3 (falsifier, strictly resolved fall from G = 4 to t-1 for t = 8, 9, 10): occurred.** All 3 + 4 + 5 = 12 steps of those series are resolved falls (ratio 2.19 to 6.86).
- **P2 (argmin G/t stable across k): not judgeable.** The frozen condition applies to bracketed uncapped series; there are none. Reported ratios are in the argmin section.
- **P4 (reproduction, G = 4 at t = 6, 7, 8 with seeds 2026111400+t equal to lead 4): true, exact.** F4 multiply-adds, F4 calls and hits are identical to lead 4's `f4cost_guess.jsonl` cells: t = 6: 71009645 / 1600 / 0; t = 7: 970300397 / 1600 / 0; t = 8: 8635143755 / 1554 / 4. The fresh-seed G = 4 cells (seed 2026111600+t) are 7.10e5, 9.43e6, 8.77e7 per target (t = 7 differs by 3% from the lead-4 target set, t = 8 by 2%): the target-set spread.

k-scaling

Compare equal (t, G) across k = 20, 24, 28 at t = 10, G = 7..9 (k = 20 rows come from stage 1, seed differs by k, so the target sets differ):

G	mul/tgt k=20	k=24	k=28	cov k=20	k=24	k=28
7	1.15e8	1.42e8	1.43e8	0.3823	0.03246	0.00193
8	3.10e7	3.85e7	3.88e7	0.3823	0.03246	0.00193
9	4.52e6	5.65e6	5.70e6	0.3823	0.03246	0.00193

F4 cost per target at fixed (t, G) is nearly independent of k (k = 20 is lower by about 20%, plausibly because at k = 20 coverage is 0.38 and 29 of 100 targets stop at a hit, saving the remaining branches; this attribution is not tested). Per-relation cost therefore rises with k at fixed t through the yield alone: PR(cov) at t = 10, G = 9 is 1.18e7 (k = 20), 1.74e8 (k = 24), 2.96e9 (k = 28), and PR(lam) 4.62e6, 2.46e7, 3.72e8. The coverage-matched series (t = 12 at k = 24, coverage 0.387, similar to k = 20, t = 10's 0.382): G = 11 gives 2.40e7 per target and PR(cov) 6.21e7, i.e. 5.3x the k = 20, t = 10, G = 9 value (1.18e7) at +2 in t, +2 in k. One matched point gives no scaling exponent; the k = 28 coverage-matched point was not obtained.

Uncharged native work

The uncharged field multiplications (system specialisation and grid reading) are a small fraction of charged work at low G but grow toward G = t-1: for example 0.041% to 6.9% over G = 4..9 at k = 20, t = 10, and 0.81% to 23.9% over G = 9..11 at k = 24, t = 12 (the `unch` column; the units differ, field multiplications against F4 multiply-adds, and grid reading is a fixed cost per cell). Pricing these at weight 1 against the charged unit (the harsh end of the section 5a band) leaves every step ratio above 2.19 and the argmins unchanged (checked on all steps; smallest 2.19 at k = 20, t = 10, G = 4 to 5). The 0 and 0.1 weights lie between. No cross-method comparison is made.

Failures and caps (all of them)

- **No cell hit the wall cap** (largest elapsed 588 s for a cell with cap 900; stage 1 largest 435 s with cap 600). Nothing is a truncated sample.
- **s2b k = 28, t = 14, G = 11: failed, rc 134** after 968 s: `memory allocation of 1207959568 bytes failed` in `pkm_semaev::decomposable` (hash set of u64) under `ulimit -v 3500000`.
- **s2b k = 28, t = 14, G = 12: failed, rc 124**: killed by `timeout 1000` (elapsed 1001 s) before the first target finished; no JSON.
- **s2b k = 28, t = 14, G = 13: failed, rc 101** after 1 s: `pkm-semaev: guess = 13 must be below the tower height 14 and at most 12`. The code caps G at 12. The smoke test before freezing used only t <= 10, so this limit was not seen; PROTOCOL says G up to t-1 is accepted, which is true only for t <= 13.
- No code change, no rerun, no cell removed or added after seeing data. The stage-2 rule produced these three cells and they stay failed. Fixing the OOM or the cap would need more memory or time than the box rule allows (3.5 GB, shared machine) and was not attempted.

Deviations and caveats

- Stage 2b was specified with an expected-cap note for t' > 12; k = 28, t = 14 failed instead of capping (above). Stage-2b k = 24, t = 12 succeeded.

- The per-relation figures PR(lam), PR(cov) are modelled (cost / frozen yield). The observed hit counts (0 to 34 in 100 targets) agree with coverage in magnitude but do not rank cells. At high coverage (k = 20, t = 9, 10; k = 24, t = 12) the target stops at its first hit, so mul/tgt is below the full-refutation cost and PR(cov) is slightly optimistic there; `obs` is the corresponding observed figure and differs from PR(cov) by 0.2x to 3.3x in rows with 1 to 4 hits, and by 0.7x to 1.4x in the rows with 17 to 34 hits (k = 20, t = 9, 10; k = 24, t = 12).
- Within a (k, t), cells use the same target set (same seed); across t or k they do not.
- Lowest per-relation cost among the measured cells, on both modelled bases: k = 20, t = 10, G = 9, with PR(cov) 1.18e7 and PR(lam) 4.62e6 (the stage-2 selection); for comparison the best cell of lead 4 (k = 20, t = 6, G = 4) is 5.42e8 and 7.45e7 on the same bases, and the best cell here at t = 6 (G = 5) is 1.12e8 and 1.54e7. These are different (t, G) points of one oracle at k = 20 with the yield differing across t; this is a measured improvement of the modelled F4 cost per relation at that cell, not a result at larger k, where the same cell costs 1.74e8 (k = 24) and 2.96e9 (k = 28) on PR(cov), and it is an edge cell. No distance to rho is claimed.
- No replay certificate, validator report or matched rho reference: under the validation gate nothing here is a leaderboard or `benchmarks/` row.
- Statements hold for the measured cells on these curves only; “no turn-up” is a statement about G <= t-1 <= 12, the range the code allows.

Files

`PROTOCOL.md`, `README.md`, `REPORT.pdf`, `analysis/` (scripts, `cells.jsonl`, status, `support.jsonl`, `binary.sha256`, `table_rows.md`, `argmin_rows.md`, `ratio_rows.md`, `guess_optimum.svg`).