Branch helper replay: one failed helper call

The first planned compiler call, BranchRootMultiplicity, exited1 with a type mismatch at line153: the ENat identity uses the numeral2 where the goal retains the natural-number cast of2. The previous four error locations no longer appear in this replay, but the module did not compile successfully.

Seven local axiom printouts were retained. support_base_multiplicity_sum includes sorryAx; the other six print only propext, Classical.choice and Quot.sound. These local prints do not replace the planned final audit. BranchCoefficientMultiplicity, IndependentControls, Readback and ExpectedFailure were not reached; the final13-name readback remains absent.

Pre/post shared dependency inventories match across16736files and3111892318bytes. The26 copied predecessor source/artifact entries match pre/post and their retained bytes. Source hashes and runtime pins match; the failed compiler process was reaped, and all three native phase owners were confirmed terminal.

Precheck47.846993seconds; compiler phase35.763581seconds; postcheck27.499790seconds; total111.225177seconds. Full2400-second reservation charged, bringing campaign charges to20640seconds. Native limits were1CPU,8GiB,zero swap,128tasks. Recorded durations are wall time, not CPU time.

All native and outer evidence was archived after terminal confirmation, with hashes checked before and after packing. No compiler rerun or independent kernel checker was invoked. The completed custody checks and six clean local printouts are preserved at their scopes; no completed target theorem is asserted.

Helper replay: recorded five-call sequence

1 failed helper 4 calls not reached

Local support print contains sorryAx; final13-name audit absent

Recorded native outcomes; no compiler rerun by archivist.