Index-calculus leads after the closure-slope study (2026-10-18)

Companion to `RESEARCH_IC_LEADS_20261018.md` in this directory. **Class:** analysis and one exploratory pilot; no `S`, no rho ratio, no claim about a deployed curve. Prior-art verdicts cite the repository files named in the note.

The filter

Five closure arguments are settled enough that a lead failing one is not a lead: (1) the generic-group bound on table oracles, with the preprocessing-rho control measured positive on 2026-10-14 and 2026-10-16; (2) no Frobenius-stable subspace at $n = 131, 163$ (2 is a primitive root); (3) shape closure at $m \geq 3$ (every shape equals random, G1 killed); (4) the admissible-degree inequality (degree 3–5 at $w = 1$, 2 at $w = 2.2$ for $n = 131$); (5) the measured degree wall (closure 4 at $m \cdot \ell \leq 18$, above 4 at 21, degree 5 at 40 unknowns beyond a 15 GB host).

Lead map: each lead against the five closure arguments it must survive (from RESEARCH_IC_LEADS_20261018.md)

	generic-group bound (table oracles)	no stable subspace at n = 131, 163	shape closure at m ≥ 3	admissible-degree inequality	measured degree wall (this host)
L1 target-free algebraic relations	pass	pass	escapes (no x_R)	must still pass	untested
L2 dense-bit-row XL at degree 5	n/a	n/a	n/a	n/a	aimed at it
L3 raised-cap sparse closure	n/a	n/a	n/a	n/a	in flight
L4 4E-class stratification	pass	pass	accounting	n/a	n/a
L5 coset-indicator degree (pilot)	pass	pass	closed: ≈ ℓ−1 on every V	n/a	n/a
L6 theorem: shape closure m ≥ 3	n/a	n/a	formalises it	n/a	n/a
L7 lemma: admissible degree	n/a	n/a	n/a	formalises it	n/a
L8 K-233 derived row	pass	stable 29-blocks exist	pass	D ≈ 3–4 (cols^2.2) / 7–8 (w = 1)	n/a
L9 G4 stable non-subspace base	pass	escapes (not a subspace)	untested	3n unknowns: fails	n/a
L10 ladder: retire online rows (Lead A)	is the bound	n/a	n/a	n/a	n/a

Figure 1: Each lead against the five arguments. Green: the lead escapes or formalises the argument; yellow: untested or in flight; red: closed by this round.

The leads, ranked

- **L1 target-free algebraic relations** (not tried before): solve $S_4(x_1, \ldots, x_4) = 0$ with every variable in V and no target; the leading forms then live in V^4, which can be dependent. Falsifier: closure degree at $(16, 4), (20, 5), (24, 6)$ against the chained target system at equal $m \cdot \ell$; kill if no cell is a degree lower. Yield is the price ($\ell \gtrsim \frac{n}{3} - 7$ needed, no-wrap window $\ell < \frac{n}{4}$).
- **L2 dense-bit-row XL at degree 5** for the $m \cdot \ell = 21$ cells: 34,482 rows over 760 k columns (3.3 GB); a refutation resolves the cells at exactly 5. Not built; about one chance in four of a positive.
- **L3 raised-cap sparse closure**: the rewritten engine's cap used 1.4 GB of 15 GB; a degree-5 run at 2.5 G entries is in flight (§3 of the note).
- **L4 4E-class stratification** (accounting): $a = 0$ Koblitz curves carry a 2-bit class in $E/4E$; EXP-H conditioned on one bit. Re-score the committed draws by class.
- **L5 coset-indicator degree** — piloted, negative as a predictor (below).
- **L6, L7 theorem and lemma**: write the $m \geq 3$ shape-closure argument and the admissible-degree inequality as statements the FFD programme can cite; neither exists in writing.
- **L8 K-233 derived row**: $\mathrm{ord}_{233}(2) = 29$, eight stable 29-blocks, admissible degree 3–4 under the $C(N, \leq D)^{2.2}$ cost and 7–8 under the $w = 1$ lower bound; a distance row for the one standard Koblitz curve where Frobenius structure helps the algebra. Not analysed anywhere.
- **L9 G4 stable non-subspace bases**: closed by counting (87 conditions, 22 cubic, $3n$ unknowns).
- **L10 ladder accounting**: Lead A ran positive twice; two documents still list it as scheduled.

Pilot: the coset-indicator degree (negative)




Figure 2: ANF degree of $x \to \mathrm{Tr}(1/x)$ on V, from `coset_indicator_pilot.jsonl` (80 records; committed anchor and fresh bases at $n = 12$–30, progression and random bases at $n = 43$), against the measured closure degrees of the chained system. Layout only; the degrees are exact Möbius transforms.

The indicator degree is $\ell - 1$ or ℓ on every base, progression no better than random, far above the closure degree 4 at $\ell \leq 6$: the closure does not refute through the parity, the indicator does not predict it, and no subspace shape at prime n lowers the parity degree (Mattarei: inverse-closed subspaces are subfields). Exploratory, not preregistered.

What would change the picture

The closure degree at $m \cdot \ell = 21$ and beyond (64 GB host, or L2/L3); a target-free system a degree below the target system (L1); or a proof that the closure degree is $\Omega(\ell)$, for which L6 is the first lemma. Everything else is a constant, a row or bookkeeping, listed because the success criterion counts verified constants.