Cheon ecbench sessions on one tier: the Cheon arms ranked by frontier procedure 2

Protocol: PROTOCOL.md, frozen in `b83ccff8ce` before any session ran. Run report: reports/run-20261106T0300Z/RUN_REPORT.md.

Outcome

Re-running the medium-tier curves of research/cheon_ecbench_20261022/ as sessions of their own makes every Cheon bound rankable.

- **Fits.** The 18 whole-session fit-version-2 bounds are all accepted, with no admissibility reason.
- **Frontier.** Procedure 2 ranks all 18 in the six oracle domains: n−1 and n+1, each at w = 0, 0.1 and 1 GAE per unpriced operation.
- **Comb.** In every one of those domains the Cheon comb arm is the ops leader, and it shares the frontier with `rho.negation`. Comb has fewer operations; rho makes no oracle queries.

Predictions (PROTOCOL.md §4)

	prediction	result
P1	counts of every run equal the original session's run (same arm, curve, target)	**met**: 272 of 272 runs identical in outcome, recovered scalar, `total_gae`, S, oracle queries, oracle server work and every per-phase count (results-p1.jsonl, compare.sh)
P2	all 18 fits accepted and ranked by procedure 2	**met**: 18 of 18 ranked, 0 admissibility reasons
P3	`rho.negation` and the comb arm both on the frontier at every weight	**met** in all six n−1 and n+1 domains
P4	`cheon.pminus1_naive` dominated by `rho.negation` at every weight	**met at w = 0, not met at w = 0.1 and w = 1** (below)

P4 at w = 0.1 and w = 1. On the charged cost, rho is clearly better than naive on ops and memory. At w = 0.1 the ops are 1.23 [0.93, 1.55] and 1.31 [0.99, 1.65] against 13.9 [10.7, 17.0]. Procedure 2 still does not call that dominance in a band-priced domain: unpriced work is uncounted on one side, so the order cannot be shown to hold across the pricing band of 0 to 1 GAE (AGENTS.md §5a). The frontier page says exactly this. Naive therefore stays on the frontier by that rule, not on cost. At w = 0 rho dominates naive outright.


Ranked bounds (measured, from `docs/bounds/frontier.json`)

`ops` is `S / S_floor` with its 95 % interval, as the bound records it. `oracle queries` is static-DH queries per `√r`.

domain	method	ops (× floor)	95 %	oracle queries (/√r)	on frontier
n−1, w = 0	`cheon.pminus1_comb`	0.648	[0.514, 0.818]	0.00003	yes, ops leader
n−1, w = 0	`rho.negation` (minus)	1.114	[0.846, 1.408]	0	yes
n−1, w = 0	`rho.negation` (minus-naive)	1.190	[0.904, 1.496]	0	yes
n−1, w = 0	`cheon.pminus1_naive`	13.814	[10.619, 16.929]	0.00003	no, dominated by both rho bounds
n−1, w = 0.1	`cheon.pminus1_comb`	0.690	[0.543, 0.873]	0.00003	yes, ops leader
n−1, w = 0.1	`rho.negation` (minus)	1.225	[0.931, 1.549]	0	yes
n−1, w = 0.1	`rho.negation` (minus-naive)	1.309	[0.995, 1.646]	0	yes
n−1, w = 0.1	`cheon.pminus1_naive`	13.861	[10.651, 16.987]	0.00003	yes (see P4)

domain	method	ops (× floor)	95 %	oracle queries (/√r)	on frontier
n−1, w = 1	`cheon.pminus1_comb`	1.074	[0.809, 1.376]	0.00003	yes, ops leader
n−1, w = 1	`rho.negation` (minus)	2.227	[1.693, 2.816]	0	yes
n−1, w = 1	`rho.negation` (minus-naive)	2.380	[1.808, 2.992]	0	yes
n−1, w = 1	`cheon.pminus1_naive`	14.278	[10.953, 17.522]	0.00003	yes (see P4)
n+1, w = 0	`cheon.pplus1_comb`	0.657	[0.483, 0.845]	0.00058	yes, ops leader
n+1, w = 0	`rho.negation`	1.143	[0.840, 1.457]	0	yes
n+1, w = 0.1	`cheon.pplus1_comb`	0.670	[0.493, 0.864]	0.00058	yes, ops leader
n+1, w = 0.1	`rho.negation`	1.257	[0.924, 1.602]	0	yes
n+1, w = 1	`cheon.pplus1_comb`	0.795	[0.580, 1.031]	0.00058	yes, ops leader
n+1, w = 1	`rho.negation`	2.285	[1.679, 2.913]	0	yes

The n−1 domains hold two rho bounds because the minus and minus-naive sessions each carry their own matched rho arm. The minus-naive arm stops at 52 bits.



Graph: ranks.svg, drawn by ranks_svg.jq from ranks.json, the entries of the rebuilt `docs/bounds/frontier.json`. Sessions `ECBS1he3401ce241ca` (minus), `ECBS1hb3aa04e7a9c6` (minus-naive) and `ECBS1h64874297871c` (plus); 8 targets per size. A filled marker is on the frontier; an open one is dominated.

Scope

- These are costs under a stated oracle: the DLP with auxiliary inputs, which queries a static-DH oracle. Nothing here changes a plain-ECDLP or index-calculus cost.
- The measurement repeats the original study's workloads. P1 shows the counts are identical run by run, so these sessions change no number of the original report. What they change is which tier each bound is fitted on, and with it the procedure-2 ranking.
- No new `benchmarks/` row: the counts are identical to the original runs (P1), and those are already in the validated `benchmarks/20261022-cheon-ecbench` row. This study changes the fits and the ranking, not a measured value.
- Counts only, at L0 on a shared 4-core host; no wall time is admitted.
- 8 targets per size, as in the original.

Files

- **Specs:** `spec-minus.json`, `spec-minus-naive.json`, `spec-plus.json`.
- **Sessions:** `sessions/{minus,minus-naive,plus}-20261106/` and their audit receipts, `sessions/*.audit.json`. Each audit reproduced every run.
- **Bounds:** `docs/bounds/records/cheon-ecbench-medium-*.json` (18), fitted by `fit.sh`. The rebuilt pages are `docs/bounds/frontier.json` and `docs/bounds/FRONTIER.md`.
- **Binary:** `sessions/BINARY.txt`.