Known small-degree pairing positive control

Run `pairing-20261022T0024Z-v2`; source freeze `e517e80b1e77778d529f51ce5a900e00cb010761`. Host `a81fcf6dc864`, Debian 13 x86_64, managed four-CPU virtual host, L0. Workloads use public synthetic fixtures or public-parameter checks. No wall-clock or full-cost improvement is admitted.

Raw outputs: run directory. Commands, binary/input hashes, seeds, resource limits and statuses are in execution receipts and the versioned protocols in the study root. No independent-host replay is claimed.

Recorded observations

Metric	Count / recorded value
embedding degree	2
independent PARI logs	10
known scalar positive control only	true
native bilinearity controls	10
source group replay	true
subgroup order	11

Vector figures and editable data accompany this report on the following pages.

This separate supersingular control uses the registered F43 model and $F43^2$ with w^2+1, r=11 and a distortion point outside the source cyclic subgroup. Native Miller arithmetic and independent PARI Tate pairing/finite-field logarithms recover all ten deliberately known scalar controls, checked again on the public source points. The GP script receives only target coordinates. This validates a known positive conditional branch; it is no ordinary/NIST transfer, novelty claim or speed result.

The chart has no statistical interval: census counts are exact on the stated finite sets; solver completion counts describe these bounded processes only. Missing or failed computations stay unresolved. Full original acceptance criteria and proof/measurement gaps remain in the requirement matrix.

Known small-degree pairing positive control

Recorded counts; exact censuses or bounded run outcomes. No wall-time comparison.