Multi-curve re-baseline of the ledger incumbents

Claim `PCC-20261105-37a78d`, standing `unverified`. Every earlier comparison in this loop used one curve per size (all 37 holdout specs have exactly one). This run measures the ledger incumbents and rho-neg on five Curve25519-family curves per size.

Curves

The family rule (`curve25519_family`) takes the largest prime p = 5 mod 8 below 2^k and the smallest valid A. The new `siblings` subcommand applies the same rule to the next primes down, with A at most 4000. Each size uses the ledger curve and four siblings. Specs were frozen before data (`spec-k*.json`, siblings in `siblings-k*.json`).

Result

12 fresh public targets x 2 rounds per curve. The audit checked 720 of 720 records at each size and reproduced 8 of 8 replays. S is at w = 0, averaged over the five curves.

k	incumbent	incumbent S	rho-neg S	mean per-curve ratio	per- range	SD
20	`wsum2g-b15-n2`	2.601	1.660	1.57	1.44 to 1.69	0.09
24	`wwalkGg-x09-sr-n2`	2.111	1.193	1.78	1.52 to 2.10	0.21
28	`wwalkGg-x09-sr-n2`	1.869	1.040	1.80	1.62 to 1.94	0.12
32	`wwalkG-x06-sr-n2`	1.930	1.013	1.91	1.69 to 2.13	0.16

Reading [pcc:unverified]

- The single-curve ledger ratios (1.76x, 1.94x, 1.81x, 1.82x) are within the curve-to-curve spread. The plateau near 1.8x to 1.9x holds across curves at k = 24 to 32.
- At k = 20 the box incumbent is 1.57x on average, better than the 1.76x of the ledger curve.
- The ratio of one size varies by about plus or minus 0.2 between curves, which is larger than most differences the loop resolved between arms. A paired comparison within a curve stays valid; a ratio to rho quoted from one curve does not carry to others.
- No incumbent S falls below the two-unknown-seed floor of 1.662, so none trips the audit trigger in OBSTRUCTION.md.
- The incumbents' parameters (B or x) were tuned on the ledger curve; their ratios on the sibling curves are held-out.