Native signed collision bridge

Status: source candidate, unexecuted. This packet derives and proposes the missing connection from the native collector's signed duplicate suppression to a target equation. It preserves the existing default entry point and introduces an opt-in source candidate. Production source is unchanged.

The first normalized label pair is retained for each canonical divisor. A later pair yields Delta_a + Delta_b k = 0. A nonzero denominator gives a candidate; zero denominators retain redundant or inconsistent outcomes without inversion. Every proposed successful return in the opt-in path checks kG = Q on the source curve.

The derivation assumes the transfer map is a group homomorphism, P is nonzero of the same prime order, and the target has the stated group relation. Source subgroup checks and a final source equation are explicit. The candidate does not establish the transfer-map premise or independently prove native arithmetic.

The source-ordered event table and symbolic cost table are separate CSV files. Shared field counters would include added source-curve arithmetic; map work, allocation, observer output, error-prefix costs and full wall-time accounting remain unmeasured. The 24-byte label-value calculation excludes keys and allocation. No measured ratio is reported.

Historical fixed-stream evidence is context only. This packet adds zero cohort targets, invokes no compiler or solver, and does not claim runtime validation or proof-carrying code verification. Independent review is pending publication of the exact committed source.

The collision identity follows the standard prime-order Pollard collision equation in Handbook of Applied Cryptography, section 3.6.3, equations 3.3–3.4 and Algorithm 3.60 (https://cacr.uwaterloo.ca/hac/about/chap3.pdf). The contribution here is the explicit connection to the native signed canonicalization branch and its source-verification and accounting obligations.

See DERIVATION.md for assumptions and branch invariants, source-bindings.json for exact source and patch identities, events.csv for source order, costs.csv for cost boundaries, and result.json for machine-readable status.

Native signed collision bridge — source proposal

No execution • costs unmeasured • independent review pending publication

1 Candidate divisor D = aP + bT

Canonicalize D; apply the same sign to both labels.

2 First normalized label retained

Map canonical divisor to (A, B, first attempt).

3 Duplicate normalized label

Subtract labels: $\Delta a + \Delta b\, k = 0$.

4 Branch on Δb

Zero: redundant or invariant conflict. Nonzero: $k = -\Delta a / \Delta b$.

5 Source verification and finalization

Require $kG = Q$; retain counter snapshots and terminal evidence.