Frozen retained-duplicate source review

Two reporting corrections are required before execution: nested adapter failures must set the standardized failure flag, and setup accounting must be unambiguously once per target. The target/source contract is otherwise supported. No native compilation or execution was performed.

Custody and selection. All24 manifest hashes/sizes and six control-reference hashes match. The archive has180 records,60 per prime. The exact p739 selection gives60 records and420 cases. Index order, original labels, target/workload identifiers and seeds match. Duplicate/graph/native source and fixture are unchanged from the reviewed helper.

Target and label contract. Every target gets a fresh table/graph. The model derives from pinned p739 theta constants; original witnesses supply G,Q. Native checks enforce validity, nonidentity G, prime-order Ring, rG=rQ=0, Q=planted*G and each D=aG+bQ. First graph insertion retains original signs and labels. The synthetic alternate-label function is unreachable from main; no walk or relabeling occurs.

Completion and limits. All cases remain in the loop. Verified terminal stops graph forwarding only; later comparisons are diagnostic. Partition failures and poisoned cases receive dispositions. A global failure may truncate output, but the wrapper preserves it and marks incomplete. Exact420 unique index identities and exit0 establish coverage completion. Frozen hashes and refusal to overwrite protect outputs;120seconds plus5seconds grace covers the whole offline cargo invocation, including compilation.

Reporting cautions. Coverage completion does not mean universal case acceptance. The convenience failed-dispositions flag omits nested invariant-error/candidate-rejection statuses; inspect adapter counts and rows. Setup counts repeat with count-once markers. Designed fixture categories require fixed case indices and labels, since the provenance string is coarse. Native counters do not establish complete calibrated costs. Natural traces remain unadmitted.

No native results or informative-duplicate count are claimed. Root retains execution admission. Exact checks and source hashes are in static-checks.json and review.json.