

ISO Geodetic Registry

<i>Item class</i>	OperationMethod
<i>Name</i>	Time-Dependent Position Vector Transformation (geocentric Cartesian domain)
<i>Item status</i>	VALID
<i>Identifier</i>	82
<i>Alias</i>	Time-Dependent 7-Parameter Transformation
<i>Alias</i>	14-Parameter Transformation
<i>Alias</i>	Time-Dependent Position Vector Transformation
<i>Data source</i>	ISO Geodetic Registry
<i>Remarks</i>	Note the analogy with the rotation for the Time-dependent Coordinate Frame Transformation but beware of the differences! The Position Vector Transformation convention is used by IAG.
<i>Formula</i>	Geomatics Guidance Note No 7, part 2: Coordinate Conversions and Transformations including Formulas

Operation parameters

<i>X-axis translation</i>
<i>Y-axis translation</i>
<i>Z-axis translation</i>
<i>X-axis rotation</i>
<i>Y-axis rotation</i>
<i>Z-axis rotation</i>
<i>Scale difference</i>
<i>Rate of change of X-axis translation</i>
<i>Rate of change of Y-axis translation</i>
<i>Rate of change of Z-axis translation</i>
<i>Rate of change of X-axis rotation</i>
<i>Rate of change of Y-axis rotation</i>
<i>Rate of change of Z-axis rotation</i>
<i>Rate of change of scale difference</i>
<i>Time reference</i>