ISO Geodetic Registry

Item class Transformation

Name IGS00 to IGb00 [IGS v1]

Item status VALID Identifier 475

Information source Title IGS00 (v2)
Author R. Ferland

Publisher International GNSS Service (IGS)

Publication date 2003-10-09

Edition date

Series/Journal name IGSMAIL Issue identification 4642.0

Information source Title Chronology of IGS Reference Frame Usage

Author International GNSS Service Analysis Centre

Coordinator

Publisher National Oceanic and Atmospheric Administration

(NOAA), National Geodetic Survey (NGS)

Publication date 2012-10-04 Other citation details Website

Data source ISO Geodetic Registry

Remarks Null transformation. IGS00 and IGb00 are both aligned to ITRF2000

and are treated as the same reference frame. Although the actual IGS00-IGb00 transformation parameters are not null, they are

statistically insignificant and treated as null by the IGS.

Operation version IGS v1

Scope Spatial referencing

Operation accuracy 0.0 m

Source CRS IGS00 - XYZ
Target CRS IGb00 - XYZ

Operation method Time-Dependent Position Vector Transformation (geocentric Cartesian

domain)

Extent

| Description | World. | |
|-------------------------|----------------------|--------|
| Geographic Bounding Box | West-bound longitude | -180.0 |
| | North-bound latitude | 90.0 |
| | East-bound longitude | 180.0 |
| | South-bound latitude | -90.0 |

Operation parameter values

| Time reference | 1998.0 year |
|--------------------------------------|--------------------------------|
| Rate of change of scale difference | 0.0 parts per billion per year |
| Rate of change of Z-axis rotation | 0.0 milliarc-second per year |
| Rate of change of Y-axis rotation | 0.0 milliarc-second per year |
| Rate of change of X-axis rotation | 0.0 milliarc-second per year |
| Rate of change of Z-axis translation | 0.0 millimetre per year |
| Rate of change of Y-axis translation | 0.0 millimetre per year |
| Rate of change of X-axis translation | 0.0 millimetre per year |
| Scale difference | 0.0 parts per billion |
| Z-axis rotation | 0.0 milliarc-second |

| Y-axis rotation | 0.0 milliarc-second | |
|--------------------|---------------------|--|
| X-axis rotation | 0.0 milliarc-second | |
| Z-axis translation | 0.0 millimetre | |
| Y-axis translation | 0.0 millimetre | |
| X-axis translation | 0.0 millimetre | |

ISO Geodetic Registry

Item class OperationMethod

Name Time-Dependent Position Vector

Transformation (geocentric Cartesian domain)

Item status VALID Identifier 82

Alias Time-Dependent 7-Parameter Transformation

Alias 14-Parameter Transformation

Alias Time-Dependent Position Vector Transformation

Data source ISO Geodetic Registry

Remarks Note the analogy with the rotation for the Time-dependent Coordinate

Frame Transformation but beware of the differences! The Position

Vector Transformation convention is used by IAG.

Formula Geomatics Guidance Note No 7, part 2: Coordinate Conversions and

Transformations including Formulas

Operation parameters

X-axis translation

Y-axis translation

Z-axis translation

X-axis rotation

Y-axis rotation

Z-axis rotation

Scale difference

Rate of change of X-axis translation

Rate of change of Y-axis translation

Rate of change of Z-axis translation

Rate of change of X-axis rotation

Rate of change of Y-axis rotation

Rate of change of Z-axis rotation

Rate of change of scale difference

Time reference