ISO Geodetic Registry

Item class Transformation

NAD83(CSRS) v4 to NAD 83 (CORS96) Epoch

2002.0 [v1]

Item statusVALIDIdentifier517

Information source Title The Canadian Spatial Reference System (CSRS)

Author Canadian Geodetic Survey

Publisher Canadian Geodetic Survey, Surveyor General

Branch, Earth Sciences Sector, Natural Resources Canada, Government of Canada

Publication date 2016-08-30

Information source Title The Evolution of NAD83 in Canada: Addendum

Author M. Craymer

Publisher Canadian Institute of Geomatics

Publication date 2006
Series/Journal name Geomatica
Issue identification Volume 60, No. 4

Page 433.0

Information source Title Continuously Operating Reference Station

(CORS): History, Applications, and Future

Enhancements

Author R.A. Snay, T. Soler

Publisher ASCE
Publication date 2008-04-01
Edition date 2008-04-01

Series/Journal name Journal of Surveying Engineering

Issue identification Volume 134, No. 4

Page 95-104

Other citation details NAD83 (CORS96) Epoch 1996.0, NAD83

(CORS96) Epoch 1997.0, NAD83 (CORS96)

Epoch 2002.0

Information source Title NGS No Longer Updates Published CORS

Coordinates in the Following Reference Frames

Author National Geodetic Survey

Publisher National Oceanic and Atmospheric Administration

(NOAA) National Geodetic Survey (NGS)

Revision date 2017-03-16 Edition date 2017-03-16

Series/Journal name NGS Online listing of transformation parameters

Other citation details webpage

Information source Title The Evolution of NAD83 in Canada

Author M. Craymer

Publisher Canadian Institute of Geomatics

Publication date 2006
Series/Journal name Geomatica
Issue identification Volume 60, No. 2

Page 151-164

Data source ISO Geodetic Registry

Remarks Null transformation. NAD83(CSRS)v4 and NAD83(CORS96) epoch

2002 are equivalent by definition.

Operation version v1

Scope Spatial referencing

Operation accuracy 0.0 m

Source CRS NAD83(CSRS) v4 - XYZ

Target CRS NAD 83 (CORS96) Epoch 2002.0 - XYZ

Extent

Description	North America - onshore and offshore: Canada - Alberta, British Columbia, Manitoba, New Brunswick, Newfoundland and Labrador, Northwest Territories, Nova Scotia, Nunavut, Ontario, Prince Edward Island, Quebec, Saskatchewan, Yukon. Puerto Rico. United States (USA) - Alaska, CONUS (Alabama, Arizona, Arkansas, California, Colorado, Connecticut, Delaware, Florida, Georgia, Idaho, Illinois, Indiana, Iowa, Kansas, Kentucky, Louisiana, Maine, Maryland, Massachusetts, Michigan, Minnesota, Mississippi, Missouri, Montana, Nebraska, Nevada, New Hampshire, New Jersey, New Mexico, New York, North Carolina, North Dakota, Ohio, Oklahoma, Oregon, Pennsylvania, Rhode Island, South Carolina, South Dakota, Tennessee, Texas	
	Carolina, South Dakota, Tennessee, Texas, Utah, Vermont, Virginia, Washington, West	
	Virginia, Wisconsin, W (US).	yoming). Virgin Islands
Geographic Bounding Box	West-bound longitude North-bound latitude East-bound longitude South-bound latitude	167.65 86.46 -47.74 14.92

Operation parameter values

Time reference	2002.0 year
Rate of change of scale difference	0.0 parts per billion per year
Rate of change of Z-axis rotation	0.0 milliarc-second per year
Rate of change of Y-axis rotation	0.0 milliarc-second per year
Rate of change of X-axis rotation	0.0 milliarc-second per year
Rate of change of Z-axis translation	0.0 metre per year
Rate of change of Y-axis translation	0.0 metre per year
Rate of change of X-axis translation	0.0 metre per year
Scale difference	0.0 parts per billion
Z-axis rotation	0.0 milliarc-second
Y-axis rotation	0.0 milliarc-second
X-axis rotation	0.0 milliarc-second
Z-axis translation	0.0 metre
Y-axis translation	0.0 metre
X-axis translation	0.0 metre

ISO Geodetic Registry

Item class OperationMethod

Name Time-Dependent Position Vector

Transformation (geocentric Cartesian domain)

Item status VALID Identifier 82

Alias Time-Dependent 7-Parameter Transformation

Alias 14-Parameter Transformation

Alias Time-Dependent Position Vector Transformation

Data source ISO Geodetic Registry

Remarks Note the analogy with the rotation for the Time-dependent Coordinate

Frame Transformation but beware of the differences! The Position

Vector Transformation convention is used by IAG.

Formula Geomatics Guidance Note No 7, part 2: Coordinate Conversions and

Transformations including Formulas

Operation parameters

X-axis translation

Y-axis translation

Z-axis translation

X-axis rotation

Y-axis rotation

Z-axis rotation

Scale difference

Rate of change of X-axis translation

Rate of change of Y-axis translation

Rate of change of Z-axis translation

Rate of change of X-axis rotation

Rate of change of Y-axis rotation

Rate of change of Z-axis rotation

Rate of change of scale difference

Time reference