ISO Geodetic Registry

| Name | GDA2020 to WGS 84 (G1762) [GA v1] | Item status | VALID

Transformation

Identifier 563

Information source Title Geocentric Datum of Australia 2020 Technical

Manual Version 1.2

Author Permanent Committee on Geodesy of the

Intergovernmental Committee on Surveying and

Mapping

Publisher Intergovernmental Committee on Surveying and

Mapping

Publication date 2018-08-24

Edition date

Data source ISO Geodetic Registry

Operation version GA v1

Scope Spatial referencing

Operation accuracy 0.2 m

Source CRS GDA2020 - XYZ

Target CRS WGS 84 (G1762) - XYZ

Operation method Time-Dependent Coordinate Frame Transformation (geocentric

Cartesian domain)

Extent

Item class

Description	Australia - onshore and offshore - mainland, Tasmania, Lord Howe Island, Norfolk Island, Macquarie Island. Christmas Island - onshore and offshore. Cocos (Keeling) Islands -	
	onshore and offshore.	.
Geographic Bounding Box	West-bound longitude	93.41
	North-bound latitude	-8.47
	East-bound longitude	173.4
	South-bound latitude	-60.56

Operation parameter values

X-axis translation	0.0 metre
Y-axis translation	0.0 metre
Z-axis translation	0.0 metre
X-axis rotation	0.0 arc-second
Y-axis rotation	0.0 arc-second
Z-axis rotation	0.0 arc-second
Scale difference	0.0 parts per million
Rate of change of X-axis translation	0.0 metre per year
Rate of change of Y-axis translation	0.0 metre per year
Rate of change of Z-axis translation	0.0 metre per year
Rate of change of X-axis rotation	-1.50379 milliarc-second per year
Rate of change of Y-axis rotation	-1.18346 milliarc-second per year
Rate of change of Z-axis rotation	-1.20716 milliarc-second per year

Rate of change of scale difference Time reference 0.0 parts per million per year 2020.0 year

ISO Geodetic Registry

Item class OperationMethod

Name Time-Dependent Coordinate Frame

Transformation (geocentric Cartesian domain)

Item status VALID
Identifier 94

Alias Time-Dependent 7-Parameter Transformation

Alias 14-Parameter Transformation

Alias Time-Dependent Coordinate Frame Transformation

Data source ISO Geodetic Registry

Remarks Note the analogy with the Time-dependent Position Vector

Transformation but beware of the differences! The Position Vector

Transformation convention is used by IAG.

Formula Geomatics Guidance Note No 7, part 2: Coordinate Conversions and

Transformations including Formulas

Operation parameters

X-axis translation

Y-axis translation

Z-axis translation

X-axis rotation

Y-axis rotation

Z-axis rotation

Scale difference

Rate of change of X-axis translation

Rate of change of Y-axis translation

Rate of change of Z-axis translation

Rate of change of X-axis rotation

Rate of change of Y-axis rotation

Rate of change of Z-axis rotation

Rate of change of scale difference

Time reference