

# ISO Geodetic Registry

<i>Item class</i>	GeodeticDatum	
<i>Name</i>	<b>North American Datum of 1927</b>	
<i>Item status</i>	VALID	
<i>Identifier</i>	104	
<i>Alias</i>	NAD27(74)	
<i>Alias</i>	NAD27	
<i>Information source</i>	<i>Title</i>	NADCON 5.0: Geometric Transformation Tool for points in the National Spatial Reference System
	<i>Author</i>	D. Smith, A. Bilich
	<i>Publisher</i>	NOAA's National Geodetic Survey
	<i>Publication date</i>	2017-03-27
	<i>Edition date</i>	2017-03-27
	<i>Series/Journal name</i>	NGS Technical Report
	<i>Other citation details</i>	Replaces version 4.2 and all earlier. Provides gridding algorithm, datum transformations, and extents of covnversion grids.
<i>Information source</i>	<i>Title</i>	Annual Report of the Superintendent of the Coast and Geodetic Survey for fiscal year ended June 30, 1927
	<i>Author</i>	Coast and Geodetic Survey
	<i>Publisher</i>	Coast and Geodetic Survey
	<i>Publication date</i>	1927
<i>Information source</i>	<i>Title</i>	Notice to Adopt Standard Method for Horizontal Datum Transformation
	<i>Author</i>	US Government
	<i>Publisher</i>	Office of Federal Register, NARA
	<i>Publication date</i>	1990-08-10
	<i>Edition date</i>	1990-08-10
	<i>Series/Journal name</i>	Federal Register Notice
	<i>Issue identification</i>	Volume 55, No. 155, Document: 00-18809
	<i>Page</i>	32681.0
	<i>Other citation details</i>	Mandates use of NADCON for official transformations between datums
<i>Information source</i>	<i>Title</i>	Annual Report of the Director, United States Coast and Geodetic Survey to the Secretary of Commerce for the Fiscal Year Ended June 30, 1930
	<i>Author</i>	US Government
	<i>Publisher</i>	Government Printing Office
	<i>Publication date</i>	1930-06-30
	<i>Edition date</i>	1930-06-30
	<i>Page</i>	33.0
	<i>Other citation details</i>	NGVD29
<i>Data source</i>	ISO Geodetic Registry	
<i>Remarks</i>	Replaced by NAD27(76) in Ontario, CGQ77 in Quebec, Mexican Datum of 1993 in Mexico, NAD83(1986) in Canada (excl. Ontario & Quebec) & USA.	
<i>Anchor definition</i>	Fundamental point: Meade's Ranch. Latitude: 39°13'26.686"N, longitude: 98°32'30.506"W (of Greenwich). Note: this CRS includes longitudes which are POSITIVE EAST.	
<i>Release date</i>	1927-01-01	
<i>Scope</i>	Spatial referencing	
<i>Ellipsoid</i>	Clarke 1866	
<i>Prime Meridian</i>	Greenwich	

## Extent

<i>Description</i>	<p><b>North and Central America: Antigua and Barbuda - onshore. Bahamas onshore plus offshore internal continental shelf only. Belize - onshore. Canada - onshore and offshore - Alberta, British Columbia, Manitoba, New Brunswick, Newfoundland and Labrador, Northwest Territories, Nova Scotia, Nunavut, Ontario, Prince Edward Island, Quebec, Saskatchewan, Yukon. Cuba - onshore and offshore. El Salvador - onshore. Guatemala - onshore. Honduras - onshore. Puerto Rico - onshore. Mexico - onshore plus offshore Gulf of Mexico. Nicaragua - onshore. United States (USA) – onshore and offshore - Alaska, CONUS (Alabama, Arizona, Arkansas, California, Colorado, Connecticut, Delaware, Florida, Georgia, Idaho, Illinois, Indiana, Iowa, Kansas, Kentucky, Louisiana, Maine, Maryland, Massachusetts, Michigan, Minnesota, Mississippi, Missouri, Montana, Nebraska, Nevada, New Hampshire, New Jersey, New Mexico, New York, North Carolina, North Dakota, Ohio, Oklahoma, Oregon, Pennsylvania, Rhode Island, South Carolina, South Dakota, Tennessee, Texas, Utah, Vermont, Virginia, Washington, West Virginia, Wisconsin, Wyoming). Virgin Islands (British) - onshore. Virgin Islands (US) - onshore and offshore.</b></p>								
<i>Geographic Bounding Box</i>	<table> <tr> <td><i>West-bound longitude</i></td><td>167.65</td></tr> <tr> <td><i>North-bound latitude</i></td><td>83.17</td></tr> <tr> <td><i>East-bound longitude</i></td><td>-47.74</td></tr> <tr> <td><i>South-bound latitude</i></td><td>7.98</td></tr> </table>	<i>West-bound longitude</i>	167.65	<i>North-bound latitude</i>	83.17	<i>East-bound longitude</i>	-47.74	<i>South-bound latitude</i>	7.98
<i>West-bound longitude</i>	167.65								
<i>North-bound latitude</i>	83.17								
<i>East-bound longitude</i>	-47.74								
<i>South-bound latitude</i>	7.98								

# ISO Geodetic Registry

<i>Item class</i>	Ellipsoid
<i>Name</i>	<b>Clarke 1866</b>
<i>Item status</i>	VALID
<i>Identifier</i>	28
<i>Information source</i>	<p><i>Title</i> Annual Report of the Superintendent of the Coast and Geodetic Survey for fiscal year ended June 30, 1927</p> <p><i>Author</i> Coast and Geodetic Survey</p> <p><i>Publisher</i> Coast and Geodetic Survey</p> <p><i>Publication date</i> 1927</p>
<i>Information source</i>	<p><i>Title</i> Universal Transverse Mercator Grid Tables For Latitudes 0°-80° Clarke 1866 Spheroid (Meters) Volume II</p> <p><i>Author</i> U.S. Army Map Service</p> <p><i>Publisher</i> U.S. Army Map Service</p> <p><i>Publication date</i> 1958-07</p> <p><i>Series/Journal name</i> Technical Manual</p> <p><i>Issue identification</i> TM 5-241-4/2</p>
<i>Information source</i>	<p><i>Title</i> Transformation of grid coordinates</p> <p><i>Author</i> U.S. Army Map Service</p> <p><i>Publisher</i> U.S. Army Map Service</p> <p><i>Publication date</i> 1944</p> <p><i>Series/Journal name</i> Army Map Services Bulletin</p> <p><i>Issue identification</i> 7.0</p>
<i>Information source</i>	<p><i>Title</i> Annual Report of the Director, United States Coast and Geodetic Survey to the Secretary of Commerce for the Fiscal Year Ended June 30, 1930</p> <p><i>Author</i> US Government</p> <p><i>Publisher</i> Government Printing Office</p> <p><i>Publication date</i> 1930-06-30</p> <p><i>Edition date</i> 1930-06-30</p> <p><i>Page</i> 33.0</p> <p><i>Other citation details</i> NGVD29</p>
<i>Information source</i>	<p><i>Title</i> Grids and Grid References</p> <p><i>Author</i> Department of the Army</p> <p><i>Publisher</i> Headquarters, Department of the Army, Washington, DC</p> <p><i>Publication date</i> 1967-06-07</p> <p><i>Series/Journal name</i> Department of the Army Technical Manual</p> <p><i>Issue identification</i> TM 5-241-1</p>
<i>Information source</i>	<p><i>Title</i> Universal transverse mercator grid tables. Clarke 1866 (Technical Manual nos. 7, 21, 37), Clarke 1880 (nos. 9, 48), Everest (nos. 11, 49), Bessel (nos. 8, 39), International (no. 6) spheroids</p> <p><i>Author</i> U.S. Army Map Service</p> <p><i>Publisher</i> U.S. Army Map Service</p> <p><i>Publication date</i> 1951</p>
<i>Data source</i>	ISO Geodetic Registry
<i>Remarks</i>	Original definition a=20926062 and b=20855121 (British) feet. Uses Clarke's 1865 inch-metre ratio of 39.370432 to obtain metres. Metric value then converted to US survey feet for use in the US and international feet for use in Cayman Islands.
<i>Semi-major axis</i>	6378206.4 m
<i>Semi-minor axis</i>	6356583.8 m

# ISO Geodetic Registry

<i>Item class</i>	PrimeMeridian	
<i>Name</i>	<b>Greenwich</b>	
<i>Item status</i>	VALID	
<i>Identifier</i>	25	
<i>Alias</i>	Zero meridian	
<i>Information source</i>	<i>Title</i>	Why the Greenwich meridian moved
	<i>Author</i>	S. Malys, J.H. Seago, N.K. Pavlis, P.K. Seidelmann, G.H. Kaplan
	<i>Publisher</i>	Springer International Publishing
	<i>Publication date</i>	2015-12
	<i>Series/Journal name</i>	Journal of Geodesy
	<i>Issue identification</i>	Volume 89, No. 12
	<i>Page</i>	1263–1272
	<i>Title</i>	IERS Conventions (2010)
	<i>Author</i>	G. Petit, B.J. Luzum (eds)
	<i>Publisher</i>	Verlag des Bundesamts für Kartographie und Geodäsie
<i>Information source</i>	<i>Publication date</i>	2010
	<i>Edition date</i>	
	<i>Series/Journal name</i>	IERS Technical Notes
	<i>Issue identification</i>	36.0
	<i>Other citation details</i>	ISSN: 1019-4568
<i>Data source</i>	ISO Geodetic Registry	
<i>Greenwich longitude</i>	0.0 °	