### ISO Geodetic Registry

Item class Transformation

Name ITRF2008 to SIRGAS-CON SIR11P01 [SIRv1]

Item status **VALID** Identifier 513

Information source Title Use of velocities in the processing of GNSS data

> Sistema de Referencia Geocéntrico para las Author

> > Américas (SIRGAS)

Publisher Sistema de Referencia Geocéntrico para las

Américas (SIRGAS)

Publication date 2017 Other citation details Website

Information source Title The 2009 Horizontal Velocity Field for South

> America and the Caribbean H. Drewes, O. Heidbach

Author Publisher Springer Berlin Heidelberg

Publication date 2012

Series/Journal name International Association of Geodesy Symposia

Issue identification 136.0 Page 657-664

Other citation details In Kenyon S., Pacino M., Marti U. (eds) Geodesy

for Planet Earth. International Association of Geodesy Symposia, Vol 136. Springer, Berlin,

Heidelberg

Information source Title Sistema de Referencia Geocentrico para las

Americas (SIRGAS)

Author Sistema de Referencia Geocéntrico para las

Américas (SIRGAS)

Sistema de Referencia Geocéntrico para las Publisher

Américas (SIRGAS)

Publication date 2018 Other citation details Website

Information source Title Recent activities of the IGS Regional Network

Associate Analysis Centre for SIRGAS (IGS

RNAAC SIR)

Author L. Sanchez, M. Seitz

Publisher Deutsches Geodaetisches Forschungsinstitut,

Munich, Germany, PANGAEA

Publication date Series/Journal name DGFI Report Issue identification No. 87

Other citation details Data for paper included in supplement SIRGAS

reference frame realization SIR11P01.

Data source ISO Geodetic Registry

Null reference frame transformation between ITRF2008 and SIRGAS-Remarks

CON SIR11P01.

Operation version SIR<sub>v</sub>1

Scope Spatial referencing

Operation accuracy 0.01 m

Source CRS ITRF2008 - XYZ

Target CRS SIRGAS-CON SIR11P01 - LatLon

Time-Dependent Position Vector Transformation (geocentric Cartesian Operation method

domain)

#### Extent

Description	South America - onshore and offshore. Central America - onshore and offshore. Mexico - onshore and offshore.	
Geographic Bounding Box	West-bound longitude	-122.19
	North-bound latitude	32.72
	East-bound longitude	-25.28
	South-bound latitude	-59.87

# Operation parameter values

Time reference	2005.0 year
Rate of change of scale difference	0.0 parts per billion per year
Rate of change of Z-axis rotation	0.0 milliarc-second per year
Rate of change of Y-axis rotation	0.0 milliarc-second per year
Rate of change of X-axis rotation	0.0 milliarc-second per year
Rate of change of Z-axis translation	0.0 millimetre per year
Rate of change of Y-axis translation	0.0 millimetre per year
Rate of change of X-axis translation	0.0 millimetre per year
Scale difference	0.0 parts per billion
Z-axis rotation	0.0 milliarc-second
Y-axis rotation	0.0 milliarc-second
X-axis rotation	0.0 milliarc-second
Z-axis translation	0.0 millimetre
Y-axis translation	0.0 millimetre
X-axis translation	0.0 millimetre

## **ISO Geodetic Registry**

Item class OperationMethod

Name Time-Dependent Position Vector

**Transformation (geocentric Cartesian domain)** 

Item status VALID Identifier 82

Alias Time-Dependent 7-Parameter Transformation

Alias 14-Parameter Transformation

Alias Time-Dependent Position Vector Transformation

Data source ISO Geodetic Registry

Remarks Note the analogy with the rotation for the Time-dependent Coordinate

Frame Transformation but beware of the differences! The Position

Vector Transformation convention is used by IAG.

Formula Geomatics Guidance Note No 7, part 2: Coordinate Conversions and

Transformations including Formulas

#### Operation parameters

X-axis translation

Y-axis translation

Z-axis translation

X-axis rotation

Y-axis rotation

Z-axis rotation

Scale difference

Rate of change of X-axis translation

Rate of change of Y-axis translation

Rate of change of Z-axis translation

Rate of change of X-axis rotation

Rate of change of Y-axis rotation

Rate of change of Z-axis rotation

Rate of change of scale difference

Time reference