## ISO Geodetic Registry

Item class Transformation

Name ITRF94 to ETRF2000 [EUREF v1]

Item statusVALIDIdentifier697

Information source Title EUREF Technical Note 1: Relationship and

Transformation between the International and the

European Terrestrial Reference Systems

Author Z. Altamimi

Publisher Institut National de l'Information Géographique et

Forestière (IGN), France

Publication date 2018-06-28

Series/Journal name IERS Technical Note

Issue identification 1.0

Information source Title Memo: Specifications for reference frame fixing

in the analysis of a EUREF GPS campaign

(version 8)

Author C. Boucher, Z. Altamimi

Publisher Institute National de l'Information Geographique

et Forestiere (IGN), Laboratoire de Recherche en

Geodesie (LAREG)

Publication date 2011-05-18

Edition date

Data source ISO Geodetic Registry

Remarks Accuracy of transformation is given at the reference epoch for the

transformation parameters (2000.0); actual accuracy then depends on the epoch at which the transformation parameters are applied (refer to

Citation for accuracies of velocities of the parameters).

Operation version EUREF v1

Scope Spatial referencing

Operation accuracy 0.001 m

Source CRS ITRF94 - XYZ

Target CRS ETRF2000 - XYZ

Operation method Time-Dependent Position Vector Transformation (geocentric Cartesian

domain)

#### Extent

Europe - onshore and offshore: Albania,
Andorra, Austria, Belgium, Bosnia and
Herzegovina, Bulgaria, Croatia, Cyprus,
Czech Republic, Denmark, Estonia, Faroe
Islands, Finland, France, Germany, Gibraltar,
Greece, Hungary, Ireland, Italy, Latvia,
Liechtenstein, Lithuania, Luxembourg,
Macedonia, Malta, Monaco, Montenegro,
Netherlands, Norway including Svalbard and
Jan Mayen, Poland, Portugal, Romania, San
Marino, Serbia, Slovakia, Slovenia, Spain,
Sweden, Switzerland, United Kingdom (UK)

# including Channel Islands and Isle of Man, Vatican City State.

Geographic Bounding Box West-bound longitude -16.1

North-bound latitude 84.17
East-bound longitude 39.65
South-bound latitude 32.88

## Operation parameter values

2000.0 year
-0.01 parts per billion per year
-0.812 milliarc-second per year
0.49 milliarc-second per year
0.081 milliarc-second per year
1.4 millimetre per year
0.6 millimetre per year
0.0 millimetre per year
-1.58 parts per billion
-8.772 milliarc-second
5.39 milliarc-second
0.891 milliarc-second
-25.3 millimetre
46.7 millimetre
47.3 millimetre

# **ISO Geodetic Registry**

Item class OperationMethod

Name Time-Dependent Position Vector

**Transformation (geocentric Cartesian domain)** 

Item status VALID Identifier 82

Alias Time-Dependent 7-Parameter Transformation

Alias 14-Parameter Transformation

Alias Time-Dependent Position Vector Transformation

Data source ISO Geodetic Registry

Remarks Note the analogy with the rotation for the Time-dependent Coordinate

Frame Transformation but beware of the differences! The Position

Vector Transformation convention is used by IAG.

Formula Geomatics Guidance Note No 7, part 2: Coordinate Conversions and

Transformations including Formulas

### Operation parameters

X-axis translation

Y-axis translation

Z-axis translation

X-axis rotation

Y-axis rotation

Z-axis rotation

Scale difference

Rate of change of X-axis translation

Rate of change of Y-axis translation

Rate of change of Z-axis translation

Rate of change of X-axis rotation

Rate of change of Y-axis rotation

Rate of change of Z-axis rotation

Rate of change of scale difference

Time reference