

ISO Geodetic Registry

<i>Item class</i>	GeodeticDatum	
<i>Name</i>	IGS14	
<i>Item status</i>	VALID	
<i>Identifier</i>	153	
<i>Alias</i>	International GNSS Service 2014	
<i>Information source</i>	<i>Title</i>	Upcoming switch to IGS14/igs14.atx
	<i>Author</i>	P. Rebischung
	<i>Publisher</i>	International GNSS Service (IGS)
	<i>Publication date</i>	2016-12-21
	<i>Series/Journal name</i>	IGSMail
	<i>Issue identification</i>	7399.0
<i>Data source</i>	ISO Geodetic Registry	
<i>Remarks</i>	Replaces IGB08. Replaced by IGB14. Used by IGS products from 2017-01-29 to 2020-05-17.	
<i>Anchor definition</i>	Derived from and aligned to a subset of stable, well-performing IGS station coordinates and velocities in ITRF2014 at epoch 2010.0 with position corrections applied to account for updated ground receiver antenna calibrations. Use of IGS14 requires the use of the updated ground and satellite antenna calibrations (igs14.atx) and post-seismic deformation models (psd_IGS14.snx).	
<i>Release date</i>	2017-01-29	
<i>Coordinate Reference Epoch</i>	2010.0	
<i>Scope</i>	Spatial referencing	
<i>Ellipsoid</i>	GRS 1980	
<i>Prime Meridian</i>	Greenwich	

Extent

<i>Description</i>	World.	
<i>Geographic Bounding Box</i>	<i>West-bound longitude</i>	-180.0
	<i>North-bound latitude</i>	90.0
	<i>East-bound longitude</i>	180.0
	<i>South-bound latitude</i>	-90.0

ISO Geodetic Registry

<i>Item class</i>	Ellipsoid														
<i>Name</i>	GRS 1980														
<i>Item status</i>	VALID														
<i>Identifier</i>	27														
<i>Alias</i>	Geodetic Reference System 1980														
<i>Alias</i>	GRS1980														
<i>Alias</i>	IAG GRS80														
<i>Alias</i>	International 1979														
<i>Alias</i>	GRS80														
<i>Information source</i>	<table> <tr> <td><i>Title</i></td><td>Geodetic Reference System 1980</td></tr> <tr> <td><i>Author</i></td><td>H. Moritz</td></tr> <tr> <td><i>Publisher</i></td><td>Springer International Publishing</td></tr> <tr> <td><i>Publication date</i></td><td>2003-03</td></tr> <tr> <td><i>Series/Journal name</i></td><td>Journal of Geodesy</td></tr> <tr> <td><i>Issue identification</i></td><td>Volume 74, No. 1</td></tr> <tr> <td><i>Page</i></td><td>128–162</td></tr> </table>	<i>Title</i>	Geodetic Reference System 1980	<i>Author</i>	H. Moritz	<i>Publisher</i>	Springer International Publishing	<i>Publication date</i>	2003-03	<i>Series/Journal name</i>	Journal of Geodesy	<i>Issue identification</i>	Volume 74, No. 1	<i>Page</i>	128–162
<i>Title</i>	Geodetic Reference System 1980														
<i>Author</i>	H. Moritz														
<i>Publisher</i>	Springer International Publishing														
<i>Publication date</i>	2003-03														
<i>Series/Journal name</i>	Journal of Geodesy														
<i>Issue identification</i>	Volume 74, No. 1														
<i>Page</i>	128–162														
<i>Information source</i>	<table> <tr> <td><i>Title</i></td><td>Geodetic Reference System 1980</td></tr> <tr> <td><i>Author</i></td><td>H. Moritz</td></tr> <tr> <td><i>Publisher</i></td><td>International Association of Geodesy</td></tr> <tr> <td><i>Publication date</i></td><td>1984</td></tr> <tr> <td><i>Series/Journal name</i></td><td>Bulletin Geodesique</td></tr> <tr> <td><i>Issue identification</i></td><td>Volume 58, No. 3</td></tr> <tr> <td><i>Page</i></td><td>395-405</td></tr> </table>	<i>Title</i>	Geodetic Reference System 1980	<i>Author</i>	H. Moritz	<i>Publisher</i>	International Association of Geodesy	<i>Publication date</i>	1984	<i>Series/Journal name</i>	Bulletin Geodesique	<i>Issue identification</i>	Volume 58, No. 3	<i>Page</i>	395-405
<i>Title</i>	Geodetic Reference System 1980														
<i>Author</i>	H. Moritz														
<i>Publisher</i>	International Association of Geodesy														
<i>Publication date</i>	1984														
<i>Series/Journal name</i>	Bulletin Geodesique														
<i>Issue identification</i>	Volume 58, No. 3														
<i>Page</i>	395-405														
<i>Data source</i>	ISO Geodetic Registry														
<i>Remarks</i>	Adopted by IUGG 1979 Canberra. Inverse flattening is derived from geocentric gravitational constant $GM = 3986005e8 \text{ m}^3/\text{s}^2$, dynamic form factor $J_2 = 108263e-8$ and Earth's angular velocity = $7292115e-11 \text{ rad/s}$.														
<i>Semi-major axis</i>	6378137.0 m														
<i>Inverse flattening</i>	298.257222101 m														

ISO Geodetic Registry

<i>Item class</i>	PrimeMeridian	
<i>Name</i>	Greenwich	
<i>Item status</i>	VALID	
<i>Identifier</i>	25	
<i>Alias</i>	Zero meridian	
<i>Information source</i>	<i>Title</i>	Why the Greenwich meridian moved
	<i>Author</i>	S. Malys, J.H. Seago, N.K. Pavlis, P.K. Seidelmann, G.H. Kaplan
	<i>Publisher</i>	Springer International Publishing
	<i>Publication date</i>	2015-12
	<i>Series/Journal name</i>	Journal of Geodesy
	<i>Issue identification</i>	Volume 89, No. 12
	<i>Page</i>	1263–1272
<i>Information source</i>	<i>Title</i>	IERS Conventions (2010)
	<i>Author</i>	G. Petit, B.J. Luzum (eds)
	<i>Publisher</i>	Verlag des Bundesamts für Kartographie und Geodäsie
	<i>Publication date</i>	2010
	<i>Edition date</i>	
	<i>Series/Journal name</i>	IERS Technical Notes
	<i>Issue identification</i>	36.0
<i>Data source</i>	<i>Other citation details</i>	ISSN: 1019-4568
	ISO Geodetic Registry	
<i>Greenwich longitude</i>	0.0 °	