

ISO Geodetic Registry

<i>Item class</i>	Transformation	
<i>Name</i>	ITRF2008 to NAD83(CSRS) v6 [v1]	
<i>Item status</i>	VALID	
<i>Identifier</i>	489	
<i>Information source</i>	<i>Title</i>	The Canadian Spatial Reference System (CSRS)
	<i>Author</i>	Canadian Geodetic Survey
	<i>Publisher</i>	Canadian Geodetic Survey, Surveyor General Branch, Earth Sciences Sector, Natural Resources Canada, Government of Canada
	<i>Publication date</i>	2016-08-30
<i>Information source</i>	<i>Title</i>	Reference Frames: National
	<i>Author</i>	M. Craymer, J. Henton, D. Hutchinson, E. Lapelle, M. Piraszewski
	<i>Publisher</i>	Canadian Geodetic Survey, Surveyor General Branch, Earth Sciences Sector, Natural Resources Canada
	<i>Publication date</i>	2010-04-19
	<i>Series/Journal name</i>	Presentation to Canadian Geodetic Reference Systems Committee Meeting, Ottawa, April 19-21, 2010
<i>Data source</i>	ISO Geodetic Registry	
<i>Remarks</i>	Transformation defines NAD83(CSRS)v6 and is treated as errorless.	
<i>Operation version</i>	v1	
<i>Scope</i>	Spatial referencing	
<i>Operation accuracy</i>	0.0 m	
<i>Source CRS</i>	ITRF2008 - XYZ	
<i>Target CRS</i>	NAD83(CSRS) v6 - XYZ	
<i>Operation method</i>	Time-Dependent Position Vector Transformation (geocentric Cartesian domain)	

Extent

<i>Description</i>	Canada - onshore and offshore - Alberta, British Columbia, Manitoba, New Brunswick, Newfoundland and Labrador, Northwest Territories, Nova Scotia, Nunavut, Ontario, Prince Edward Island, Quebec, Saskatchewan, Yukon.	
<i>Geographic Bounding Box</i>	<i>West-bound longitude</i>	-141.01
	<i>North-bound latitude</i>	90.0
	<i>East-bound longitude</i>	-47.74
	<i>South-bound latitude</i>	40.04

Operation parameter values

<i>Time reference</i>	1997.0 year
<i>Rate of change of scale difference</i>	-0.102 parts per billion per year
<i>Rate of change of Z-axis rotation</i>	0.05133 milliarc-second per year
<i>Rate of change of Y-axis rotation</i>	0.75744 milliarc-second per year
<i>Rate of change of X-axis rotation</i>	-0.06667 milliarc-second per year

<i>Rate of change of Z-axis translation</i>	-0.00134 metre per year
<i>Rate of change of Y-axis translation</i>	-6.0E-4 metre per year
<i>Rate of change of X-axis translation</i>	7.9E-4 metre per year
<i>Scale difference</i>	1.71504 parts per billion
<i>Z-axis rotation</i>	-11.59935 milliarc-second
<i>Y-axis rotation</i>	-9.42645 milliarc-second
<i>X-axis rotation</i>	-25.91467 milliarc-second
<i>Z-axis translation</i>	-0.52655 metre
<i>Y-axis translation</i>	-1.90331 metre
<i>X-axis translation</i>	0.99343 metre

ISO Geodetic Registry

<i>Item class</i>	OperationMethod
<i>Name</i>	Time-Dependent Position Vector Transformation (geocentric Cartesian domain)
<i>Item status</i>	VALID
<i>Identifier</i>	82
<i>Alias</i>	Time-Dependent 7-Parameter Transformation
<i>Alias</i>	14-Parameter Transformation
<i>Alias</i>	Time-Dependent Position Vector Transformation
<i>Data source</i>	ISO Geodetic Registry
<i>Remarks</i>	Note the analogy with the rotation for the Time-dependent Coordinate Frame Transformation but beware of the differences! The Position Vector Transformation convention is used by IAG.
<i>Formula</i>	Geomatics Guidance Note No 7, part 2: Coordinate Conversions and Transformations including Formulas

Operation parameters

<i>X-axis translation</i>
<i>Y-axis translation</i>
<i>Z-axis translation</i>
<i>X-axis rotation</i>
<i>Y-axis rotation</i>
<i>Z-axis rotation</i>
<i>Scale difference</i>
<i>Rate of change of X-axis translation</i>
<i>Rate of change of Y-axis translation</i>
<i>Rate of change of Z-axis translation</i>
<i>Rate of change of X-axis rotation</i>
<i>Rate of change of Y-axis rotation</i>
<i>Rate of change of Z-axis rotation</i>
<i>Rate of change of scale difference</i>
<i>Time reference</i>