ISO Geodetic Registry

Item class Transformation

NAD27 to NAD83(CSRS) v2 [NBv1]

Item status VALID
Identifier 674

Information source Title FAQ: What are some of the transformation

methods for Canada?

AuthorEsri CanadaPublisherEsri, Redlands, CAPublication date2016-05-05

Issue identification Article ID: 000011846

Information source Title Desktop Applications: NTv2

Author Canadian Geodetic Survey

Publisher Canadian Geodetic Survey, Surveyor General

Branch, Earth Sciences Sector, Natural Resources Canada, Government of Canada

Publication date 2017-02-28

Information source Title Data Catalogue: NTv2 Grid Shift Files

Author GeoNB

Publisher Service New Brunswick, Government of New

Brunswick

Publication date 2011-06-01

Data source ISO Geodetic Registry

Remarks Grid tranformation in NTv2 format adopted for use in New Brunswick.

Operation version NBv1

Scope Spatial referencing

Operation accuracy 0.8 m

Source CRS NAD27 - LatLon

Target CRS NAD83(CSRS) v2 - LatLon

Operation method NTv2

Extent

Description	Canada - onshore and offshore - New	
	Brunswick.	
Geographic Bounding Box	West-bound longitude	-69.05
	North-bound latitude	48.07
	East-bound longitude	-63.7
	South-hound latitude	44 56

Operation parameter values

Latitude and Longitude difference file	NB2783v2.GSB	
--	--------------	--

ISO Geodetic Registry

Item class OperationMethod

Name NTv2
Item status VALID
Identifier 95

Alias National Transformation version 2 grid shift

Data source ISO Geodetic Registry

Remarks National Transformation version 2 grid shift file interpolation. Geodetic

transformation operating on a grid of 2D geographic coordinate

differences by bi-linear interpolation. Assumes longitudes to be positive

west.

Operation parameters

Latitude and Longitude difference file