ISO Geodetic Registry

Item class Transformation

Name ITRF94 to ITRF2000 [IERS v1]

Item status **VALID** Identifier 646

Information source Title IERS Conventions (2003)

Author D.D. McCarthy, G. Petit Verlag des Bundesamts fur Kartographie und Publisher

Geodasie, Frankfurt am Main, Germany

2004-01-01 Publication date

Edition date

Series/Journal name IERS Technical Notes

Issue identification 32.0

Information source Title IERS Conventions (2010)

Author G. Petit, B.J. Luzum (eds)

Verlag des Bundesamts fur Kartographie und Publisher

Geodasie

Publication date 2010

Edition date

Series/Journal name IERS Technical Notes

Issue identification 36.0

Other citation details ISSN: 1019-4568

Data source ISO Geodetic Registry

The IERS citation describes the ITRF2000 to ITRF94 transformation. Remarks

> Accuracy of transformation is given at the reference epoch for the transformation parameters. Accuracy at other epochs depends on the accuracies of the parameters at the reference epoch and their rates of change. Refer to citations for accuracies of the parameters and their

rates of change.

Operation version IERS v1

Scope Spatial referencing

Operation accuracy 0.001 m Source CRS ITRF94 - XYZ Target CRS ITRF2000 - XYZ

Operation method Time-Dependent Position Vector Transformation (geocentric Cartesian

domain)

Extent

Description	World.		
Geographic Bounding Box	West-bound longitude	-180.0	İ
	North-bound latitude	90.0	
	East-bound longitude	180.0	
	South-bound latitude	-90.0	

Operation parameter values

Time reference 1997.0 year Rate of change of scale difference -0.01 parts per billion per year Rate of change of Z-axis rotation -0.02 milliarc-second per year Rate of change of Y-axis rotation 0.0 milliarc-second per year Rate of change of X-axis rotation 0.0 milliarc-second per year Rate of change of Z-axis translation 0.14 centimetre per year

Rate of change of Y-axis translation	0.06 centimetre per year
Rate of change of X-axis translation	0.0 centimetre per year
Scale difference	-1.55 parts per billion
Z-axis rotation	0.0 milliarc-second
Y-axis rotation	0.0 milliarc-second
X-axis rotation	0.0 milliarc-second
Z-axis translation	1.85 centimetre
Y-axis translation	-0.61 centimetre
X-axis translation	-0.67 centimetre

ISO Geodetic Registry

Item class OperationMethod

Name Time-Dependent Position Vector

Transformation (geocentric Cartesian domain)

Item status VALID
Identifier 82

Alias Time-Dependent 7-Parameter Transformation

Alias 14-Parameter Transformation

Alias Time-Dependent Position Vector Transformation

Data source ISO Geodetic Registry

Remarks Note the analogy with the rotation for the Time-dependent Coordinate

Frame Transformation but beware of the differences! The Position

Vector Transformation convention is used by IAG.

Formula Geomatics Guidance Note No 7, part 2: Coordinate Conversions and

Transformations including Formulas

Operation parameters

X-axis translation

Y-axis translation

Z-axis translation

X-axis rotation

Y-axis rotation

Z-axis rotation

Scale difference

Rate of change of X-axis translation

Rate of change of Y-axis translation

Rate of change of Z-axis translation

Rate of change of X-axis rotation

Rate of change of Y-axis rotation

Rate of change of Z-axis rotation

Rate of change of scale difference

Time reference