Item class	Transformation
Name	**ITRF94 to SIRGAS95 [SIRv1]**
Item status	VALID
Identifier	525
Information source	Title	Use of velocities in the processing of GNSS data
	Author	Sistema de Referencia Geocéntrico para las Américas (SIRGAS)
	Publisher	Sistema de Referencia Geocéntrico para las Américas (SIRGAS)
	Publication date	2017
	Other citation details	Website
Information source	Title	Deformation of the South American crust estimated from finite element and collocation methods
	Author	H. Drewes, O. Heidbach
	Publisher	Springer Berlin Heidelberg
	Publication date	2005
	Series/Journal name	International Association of Geodesy Symposia
	Issue identification	128.0
	Page	544-549
	Other citation details	In Sanso F. (eds) A Window on the Future of Geodesy. International Association of Geodesy Symposia, Vol 128. Springer, Berlin, Heidelberg
Information source	Title	South American Geocentric Reference System: Final Report, Working Groups I and II
	Author	SIRGAS Working Groups I and II
	Publisher	Instituto Brasileiro de Geografia e Estatistica (IBGE), Rio de Janeiro, Brasil
	Publication date	1997
	Other citation details	Report in both English and Spanish.
Information source	Title	Sistema de Referencia Geocentrico para las Americas (SIRGAS)
	Author	Sistema de Referencia Geocéntrico para las Américas (SIRGAS)
	Publisher	Sistema de Referencia Geocéntrico para las Américas (SIRGAS)
	Publication date	2018
	Other citation details	Website
Data source	ISO Geodetic Registry
Remarks	Null reference frame transformation between ITRF94 and SIRGAS95.
Operation version	SIRv1
Scope	Spatial referencing
Operation accuracy	0.01 m
Source CRS	ITRF94 - LatLon
Target CRS	SIRGAS95 - LatLon
Operation method	Time-Dependent Position Vector Transformation (geocentric Cartesian domain)

Extent

Description	**South America - onshore and offshore**	
Geographic Bounding Box	West-bound longitude	-113.21
	North-bound latitude	16.75
	East-bound longitude	-26.0

South-bound latitude	-59.87

Operation parameter values

Time reference	1995.4 year
Rate of change of scale difference	0.0 parts per billion per year
Rate of change of Z-axis rotation	0.0 milliarc-second per year
Rate of change of Y-axis rotation	0.0 milliarc-second per year
Rate of change of X-axis rotation	0.0 milliarc-second per year
Rate of change of Z-axis translation	0.0 millimetre per year
Rate of change of Y-axis translation	0.0 millimetre per year
Rate of change of X-axis translation	0.0 millimetre per year
Scale difference	0.0 parts per billion
Z-axis rotation	0.0 milliarc-second
Y-axis rotation	0.0 milliarc-second
X-axis rotation	0.0 milliarc-second
Z-axis translation	0.0 millimetre
Y-axis translation	0.0 millimetre
X-axis translation	0.0 millimetre

ISO Geodetic Registry

Item class	OperationMethod
Name	**Time-Dependent Position Vector Transformation (geocentric Cartesian domain)**
Item status	VALID
Identifier	82
Alias	Time-Dependent 7-Parameter Transformation
Alias	14-Parameter Transformation
Alias	Time-Dependent Position Vector Transformation
Data source	ISO Geodetic Registry
Remarks	Note the analogy with the rotation for the Time-dependent Coordinate Frame Transformation but beware of the differences! The Position Vector Transformation convention is used by IAG.
Formula	Geomatics Guidance Note No 7, part 2: Coordinate Conversions and Transformations including Formulas

Operation parameters

X-axis translation
Y-axis translation
Z-axis translation
X-axis rotation
Y-axis rotation
Z-axis rotation
Scale difference
Rate of change of X-axis translation
Rate of change of Y-axis translation
Rate of change of Z-axis translation
Rate of change of X-axis rotation
Rate of change of Y-axis rotation
Rate of change of Z-axis rotation
Rate of change of scale difference
Time reference