ISO Geodetic Registry

Item class Transformation

Name IGS05 to SIRGAS-CON DGF07P01 [SIRv1]

Item status VALID
Identifier 694

Information source Title The new position and velocity solution DGF07P01

of the IGS Regional Network Associate Analysis

Center for SIRGAS (IGS RNAAC SIR)

Author W. Seemueller, M. Kruegel, H. Drewes, A.

Abolghasem

Publisher American Geophysical Union

Publication date 2007

Series/Journal name Eos Transactions, Fall Meeting Supplement Issue identification Volume 88, No. 52, Abstract G43C-1471 Other citation details AGU Fall Meeting. San Francisco, USA,

December 10 - 14, 2007, Abstract G43C-1471

Information source Title Use of velocities in the processing of GNSS data

Author Sistema de Referencia Geocéntrico para las

Américas (SIRGAS)

Publisher Sistema de Referencia Geocéntrico para las

Américas (SIRGAS)

Publication date 2017 Other citation details Website

Information source Title Sistema de Referencia Geocentrico para las

Americas (SIRGAS)

Author Sistema de Referencia Geocéntrico para las

Américas (SIRGAS)

Publisher Sistema de Referencia Geocéntrico para las

Américas (SIRGAS)

Publication date 2018
Other citation details Website

Information source Title Deformation of the South American crust

estimated from finite element and collocation

methods

Author H. Drewes, O. Heidbach
Publisher Springer Berlin Heidelberg

Publication date 2005

Series/Journal name International Association of Geodesy Symposia

Issue identification 128.0 Page 544-549

Other citation details In Sanso F. (eds) A Window on the Future of

Geodesy. International Association of Geodesy Symposia, Vol 128. Springer, Berlin, Heidelberg

Data source ISO Geodetic Registry

Remarks Null reference frame transformation between IGS05 and SIRGAS-CON

DGF07P01.

Operation version SIRv1

Scope Spatial referencing

Operation accuracy 0.01 m

Source CRS IGS05 - LatLon

Target CRS SIRGAS-CON DGF07P01 - LatLon

Operation method Time-Dependent Position Vector Transformation (geocentric Cartesian

domain)

Extent

Description	South America - onshore and offshore. Central America - onshore and offshore. Mexico - onshore and offshore.	
Geographic Bounding Box	West-bound longitude North-bound latitude East-bound longitude South-bound latitude	-122.19 32.72 -25.28 -59.87

Operation parameter values

Time reference	2004.5 year
Rate of change of scale difference	0.0 parts per billion per year
Rate of change of Z-axis rotation	0.0 milliarc-second per year
Rate of change of Y-axis rotation	0.0 milliarc-second per year
Rate of change of X-axis rotation	0.0 milliarc-second per year
Rate of change of Z-axis translation	0.0 millimetre per year
Rate of change of Y-axis translation	0.0 millimetre per year
Rate of change of X-axis translation	0.0 millimetre per year
Scale difference	0.0 parts per billion
Z-axis rotation	0.0 milliarc-second
Y-axis rotation	0.0 milliarc-second
X-axis rotation	0.0 milliarc-second
Z-axis translation	0.0 millimetre
Y-axis translation	0.0 millimetre
X-axis translation	0.0 millimetre

ISO Geodetic Registry

Item class OperationMethod

Name Time-Dependent Position Vector

Transformation (geocentric Cartesian domain)

Item status VALID Identifier 82

Alias Time-Dependent 7-Parameter Transformation

Alias 14-Parameter Transformation

Alias Time-Dependent Position Vector Transformation

Data source ISO Geodetic Registry

Remarks Note the analogy with the rotation for the Time-dependent Coordinate

Frame Transformation but beware of the differences! The Position

Vector Transformation convention is used by IAG.

Formula Geomatics Guidance Note No 7, part 2: Coordinate Conversions and

Transformations including Formulas

Operation parameters

X-axis translation

Y-axis translation

Z-axis translation

X-axis rotation

Y-axis rotation

Z-axis rotation

Scale difference

Rate of change of X-axis translation

Rate of change of Y-axis translation

Rate of change of Z-axis translation

Rate of change of X-axis rotation

Rate of change of Y-axis rotation

Rate of change of Z-axis rotation

Rate of change of scale difference

Time reference