

# ISO Geodetic Registry

<i>Item class</i>	Transformation	
<i>Name</i>	<b>ITRF97 to GDA94 [GA v1]</b>	
<i>Item status</i>	VALID	
<i>Identifier</i>	718	
<i>Information source</i>	<i>Title</i>	International Terrestrial Reference Frame (ITRF) to GDA94 Coordinate Transformations
	<i>Author</i>	J. Dawson, J. Steed
	<i>Publisher</i>	Geoscience Australia
	<i>Publication date</i>	2004-03-01
	<i>Edition date</i>	
<i>Data source</i>	ISO Geodetic Registry	
<i>Remarks</i>	Implemented 2001. Replaced by Dawson and Woods transformation of 2010, ITRF97 to GDA94 [GA-Aus 2010 v2].	
<i>Operation version</i>	GA v1	
<i>Scope</i>	Spatial referencing	
<i>Operation accuracy</i>	0.1 m	
<i>Source CRS</i>	ITRF97 - XYZ	
<i>Target CRS</i>	GDA94 - XYZ	
<i>Operation method</i>	Time-Dependent Coordinate Frame Transformation (geocentric Cartesian domain)	

## Extent

<i>Description</i>	<b>Australia - onshore and offshore - mainland, Tasmania, Lord Howe Island, Norfolk Island, Macquarie Island. Christmas Island - onshore and offshore. Cocos (Keeling) Islands - onshore and offshore.</b>	
<i>Geographic Bounding Box</i>	<i>West-bound longitude</i>	93.41
	<i>North-bound latitude</i>	-8.47
	<i>East-bound longitude</i>	173.4
	<i>South-bound latitude</i>	-60.56

## Operation parameter values

<i>Time reference</i>	2000.0 year
<i>Rate of change of scale difference</i>	-0.00109 parts per million per year
<i>Rate of change of Z-axis rotation</i>	0.001697 arc-second per year
<i>Rate of change of Y-axis rotation</i>	0.001782 arc-second per year
<i>Rate of change of X-axis rotation</i>	0.00204 arc-second per year
<i>Rate of change of Z-axis translation</i>	0.0169 metre per year
<i>Rate of change of Y-axis translation</i>	0.0049 metre per year
<i>Rate of change of X-axis translation</i>	-0.022 metre per year
<i>Scale difference</i>	0.004559 parts per million
<i>Z-axis rotation</i>	0.011825 arc-second
<i>Y-axis rotation</i>	0.013639 arc-second
<i>X-axis rotation</i>	0.012059 arc-second
<i>Z-axis translation</i>	0.1855 metre
<i>Y-axis translation</i>	0.0119 metre

*X-axis translation*

-0.2088 metre

# ISO Geodetic Registry

<i>Item class</i>	OperationMethod
<i>Name</i>	<b>Time-Dependent Coordinate Frame Transformation (geocentric Cartesian domain)</b>
<i>Item status</i>	VALID
<i>Identifier</i>	94
<i>Alias</i>	Time-Dependent 7-Parameter Transformation
<i>Alias</i>	14-Parameter Transformation
<i>Alias</i>	Time-Dependent Coordinate Frame Transformation
<i>Data source</i>	ISO Geodetic Registry
<i>Remarks</i>	Note the analogy with the Time-dependent Position Vector Transformation but beware of the differences! The Position Vector Transformation convention is used by IAG.
<i>Formula</i>	Geomatics Guidance Note No 7, part 2: Coordinate Conversions and Transformations including Formulas

## Operation parameters

<i>X-axis translation</i>
<i>Y-axis translation</i>
<i>Z-axis translation</i>
<i>X-axis rotation</i>
<i>Y-axis rotation</i>
<i>Z-axis rotation</i>
<i>Scale difference</i>
<i>Rate of change of X-axis translation</i>
<i>Rate of change of Y-axis translation</i>
<i>Rate of change of Z-axis translation</i>
<i>Rate of change of X-axis rotation</i>
<i>Rate of change of Y-axis rotation</i>
<i>Rate of change of Z-axis rotation</i>
<i>Rate of change of scale difference</i>
<i>Time reference</i>