

ISO Geodetic Registry

<i>Item class</i>	GeodeticCRS	
<i>Name</i>	NAD83(CSR96) v1 - LatLon	
<i>Item status</i>	VALID	
<i>Identifier</i>	230	
<i>Alias</i>	NAD83(CSR96)v1	
<i>Alias</i>	CSR96	
<i>Alias</i>	NAD83	
<i>Alias</i>	NAD83(CSR96)	
<i>Alias</i>	Canadian Spatial Reference System 1996	
<i>Alias</i>	North American Datum 1983 v1	
<i>Alias</i>	NAD83(CSR96)	
<i>Alias</i>	Canadian Spatial Reference System	
<i>Alias</i>	CSR96	
<i>Alias</i>	NAD83v1	
<i>Information source</i>	<i>Title</i>	The Canadian Spatial Reference System (CSR96)
	<i>Author</i>	Canadian Geodetic Survey
	<i>Publisher</i>	Canadian Geodetic Survey, Surveyor General Branch, Earth Sciences Sector, Natural Resources Canada, Government of Canada
	<i>Publication date</i>	2016-08-30
<i>Information source</i>	<i>Title</i>	Modern Geodetic Reference Frames for Precise Satellite Positioning and Navigation
	<i>Author</i>	J. Kouba, J. Popelar
	<i>Publication date</i>	1994-09-02
	<i>Series/Journal name</i>	Proceedings on the International Symposium on Kinematic Systems in Geodesy, Geomatics and Navigation, Banff, Canada, August 30 - September 2, 1994
<i>Data source</i>	<i>Page</i>	79-86
	<i>ISO Geodetic Registry</i>	
<i>Scope</i>	Spatial referencing	
<i>Datum</i>	North American Datum of 1983 (CSR96) version 1	
<i>Coordinate System</i>	Ellipsoidal 2D CS. Axes: latitude, longitude. Orientations: north, east. UoM: degree	

Extent

<i>Description</i>	Canada - onshore and offshore - Alberta, British Columbia, Manitoba, New Brunswick, Newfoundland and Labrador, Northwest Territories, Nova Scotia, Nunavut, Ontario, Prince Edward Island, Quebec, Saskatchewan, Yukon.	
<i>Geographic Bounding Box</i>	<i>West-bound longitude</i>	-141.01
	<i>North-bound latitude</i>	90.0
	<i>East-bound longitude</i>	-47.74
	<i>South-bound latitude</i>	40.04

ISO Geodetic Registry

<i>Item class</i>	GeodeticDatum	
<i>Name</i>	North American Datum of 1983 (CSRS96) version 1	
<i>Item status</i>	VALID	
<i>Identifier</i>	148	
<i>Alias</i>	NAD83(CSRS)v1	
<i>Alias</i>	CSRS96	
<i>Alias</i>	NAD83	
<i>Alias</i>	Canadian Spatial Reference System 1996	
<i>Alias</i>	North American Datum 1983 v1	
<i>Alias</i>	NAD83(CSRS96)	
<i>Alias</i>	Canadian Spatial Reference System	
<i>Alias</i>	CSRS	
<i>Alias</i>	NAD83v1	
<i>Information source</i>	<i>Title</i>	The Evolution of NAD83 in Canada
	<i>Author</i>	M. Craymer
	<i>Publisher</i>	Canadian Institute of Geomatics
	<i>Publication date</i>	2006
	<i>Series/Journal name</i>	Geomatica
	<i>Issue identification</i>	Volume 60, No. 2
	<i>Page</i>	151-164
	<i>Title</i>	Modern Geodetic Reference Frames for Precise Satellite Positioning and Navigation
<i>Information source</i>	<i>Author</i>	J. Kouba, J. Popelar
	<i>Publication date</i>	1994-09-02
	<i>Series/Journal name</i>	Proceedings on the International Symposium on Kinematic Systems in Geodesy, Geomatics and Navigation, Banff, Canada, August 30 - September 2, 1994
	<i>Page</i>	79-86
<i>Information source</i>	<i>Title</i>	The Canadian Spatial Reference System (CSRS)
	<i>Author</i>	Canadian Geodetic Survey
	<i>Publisher</i>	Canadian Geodetic Survey, Surveyor General Branch, Earth Sciences Sector, Natural Resources Canada, Government of Canada
	<i>Publication date</i>	2016-08-30
<i>Information source</i>	<i>Title</i>	The Evolution of NAD83 in Canada: Addendum
	<i>Author</i>	M. Craymer
	<i>Publisher</i>	Canadian Institute of Geomatics
	<i>Publication date</i>	2006
	<i>Series/Journal name</i>	Geomatica
	<i>Issue identification</i>	Volume 60, No. 4
	<i>Page</i>	433.0
<i>Data source</i>	ISO Geodetic Registry	
<i>Remarks</i>	Adopted by the Canadian federal government for use in Canada. Replaces NAD83(Original). Replaced by NAD83(CSRS) v2.	
<i>Anchor definition</i>	Realization of the North American Datum of 1983 and the first version of the Canadian Spatial Reference System, referred to as CSRS96. The frame is defined by a seven parameter transformation of ITRF92 3D geocentric Cartesian coordinates for Canadian stations at reference epoch 1988.0. This solution is associated with only a diagonal covariance matrix for the defining coordinates. The origin, scale and orientation of the frame are nominally defined to be that for the BIH Terrestrial System 1984 (BTS84).	

<i>Release date</i>	1996-01-01
<i>Scope</i>	Spatial referencing
<i>Ellipsoid</i>	GRS 1980
<i>Prime Meridian</i>	Greenwich

Extent

<i>Description</i>	Canada - onshore and offshore - Alberta, British Columbia, Manitoba, New Brunswick, Newfoundland and Labrador, Northwest Territories, Nova Scotia, Nunavut, Ontario, Prince Edward Island, Quebec, Saskatchewan, Yukon.		
<i>Geographic Bounding Box</i>	<i>West-bound longitude</i>	-141.01	
	<i>North-bound latitude</i>	90.0	
	<i>East-bound longitude</i>	-47.74	
	<i>South-bound latitude</i>	40.04	

ISO Geodetic Registry

<i>Item class</i>	Ellipsoid														
<i>Name</i>	GRS 1980														
<i>Item status</i>	VALID														
<i>Identifier</i>	27														
<i>Alias</i>	Geodetic Reference System 1980														
<i>Alias</i>	GRS1980														
<i>Alias</i>	IAG GRS80														
<i>Alias</i>	International 1979														
<i>Alias</i>	GRS80														
<i>Information source</i>	<table> <tr> <td><i>Title</i></td><td>Geodetic Reference System 1980</td></tr> <tr> <td><i>Author</i></td><td>H. Moritz</td></tr> <tr> <td><i>Publisher</i></td><td>Springer International Publishing</td></tr> <tr> <td><i>Publication date</i></td><td>2003-03</td></tr> <tr> <td><i>Series/Journal name</i></td><td>Journal of Geodesy</td></tr> <tr> <td><i>Issue identification</i></td><td>Volume 74, No. 1</td></tr> <tr> <td><i>Page</i></td><td>128–162</td></tr> </table>	<i>Title</i>	Geodetic Reference System 1980	<i>Author</i>	H. Moritz	<i>Publisher</i>	Springer International Publishing	<i>Publication date</i>	2003-03	<i>Series/Journal name</i>	Journal of Geodesy	<i>Issue identification</i>	Volume 74, No. 1	<i>Page</i>	128–162
<i>Title</i>	Geodetic Reference System 1980														
<i>Author</i>	H. Moritz														
<i>Publisher</i>	Springer International Publishing														
<i>Publication date</i>	2003-03														
<i>Series/Journal name</i>	Journal of Geodesy														
<i>Issue identification</i>	Volume 74, No. 1														
<i>Page</i>	128–162														
<i>Information source</i>	<table> <tr> <td><i>Title</i></td><td>Geodetic Reference System 1980</td></tr> <tr> <td><i>Author</i></td><td>H. Moritz</td></tr> <tr> <td><i>Publisher</i></td><td>International Association of Geodesy</td></tr> <tr> <td><i>Publication date</i></td><td>1984</td></tr> <tr> <td><i>Series/Journal name</i></td><td>Bulletin Geodesique</td></tr> <tr> <td><i>Issue identification</i></td><td>Volume 58, No. 3</td></tr> <tr> <td><i>Page</i></td><td>395-405</td></tr> </table>	<i>Title</i>	Geodetic Reference System 1980	<i>Author</i>	H. Moritz	<i>Publisher</i>	International Association of Geodesy	<i>Publication date</i>	1984	<i>Series/Journal name</i>	Bulletin Geodesique	<i>Issue identification</i>	Volume 58, No. 3	<i>Page</i>	395-405
<i>Title</i>	Geodetic Reference System 1980														
<i>Author</i>	H. Moritz														
<i>Publisher</i>	International Association of Geodesy														
<i>Publication date</i>	1984														
<i>Series/Journal name</i>	Bulletin Geodesique														
<i>Issue identification</i>	Volume 58, No. 3														
<i>Page</i>	395-405														
<i>Data source</i>	ISO Geodetic Registry														
<i>Remarks</i>	Adopted by IUGG 1979 Canberra. Inverse flattening is derived from geocentric gravitational constant $GM = 3986005e8 \text{ m}^3/\text{s}^2$, dynamic form factor $J_2 = 108263e-8$ and Earth's angular velocity = $7292115e-11 \text{ rad/s}$.														
<i>Semi-major axis</i>	6378137.0 m														
<i>Inverse flattening</i>	298.257222101 m														

ISO Geodetic Registry

<i>Item class</i>	PrimeMeridian	
<i>Name</i>	Greenwich	
<i>Item status</i>	VALID	
<i>Identifier</i>	25	
<i>Alias</i>	Zero meridian	
<i>Information source</i>	<i>Title</i>	Why the Greenwich meridian moved
	<i>Author</i>	S. Malys, J.H. Seago, N.K. Pavlis, P.K. Seidelmann, G.H. Kaplan
	<i>Publisher</i>	Springer International Publishing
	<i>Publication date</i>	2015-12
	<i>Series/Journal name</i>	Journal of Geodesy
	<i>Issue identification</i>	Volume 89, No. 12
	<i>Page</i>	1263–1272
<i>Information source</i>	<i>Title</i>	IERS Conventions (2010)
	<i>Author</i>	G. Petit, B.J. Luzum (eds)
	<i>Publisher</i>	Verlag des Bundesamts für Kartographie und Geodäsie
	<i>Publication date</i>	2010
	<i>Edition date</i>	
	<i>Series/Journal name</i>	IERS Technical Notes
	<i>Issue identification</i>	36.0
<i>Data source</i>	<i>Other citation details</i>	ISSN: 1019-4568
	ISO Geodetic Registry	
<i>Greenwich longitude</i>	0.0 °	

ISO Geodetic Registry

<i>Item class</i>	EllipsoidalCS	
<i>Name</i>	Ellipsoidal 2D CS. Axes: latitude, longitude. Orientations: north, east. UoM: degree	
<i>Item status</i>	VALID	
<i>Identifier</i>	43	
<i>Information source</i>	<i>Title</i>	ISO 19111 Geographical information - Spatial referencing by coordinates
	<i>Author</i>	International Organization for Standardization (ISO)
	<i>Publisher</i>	International Organization for Standardization (ISO)
	<i>Publication date</i>	2007-07-01
	<i>Edition</i>	Second Edition
	<i>Series/Journal name</i>	International Standard
	<i>Issue identification</i>	ISO 19111:2007
<i>Data source</i>	ISO Geodetic Registry	
<i>Remarks</i>	Used in geographic 2D coordinate reference systems. Coordinates referenced to this CS are in degrees. Any degree representation (e.g. DMSH, decimal, etc.) may be used but that used must be declared for the user by the supplier of data.	

Axes

<i>Item class</i>	CoordinateSystemAxis	
<i>Name</i>	Geodetic latitude	
<i>Item status</i>	VALID	
<i>Identifier</i>	38	
<i>Information source</i>	<i>Title</i>	ISO 19111 Geographical information - Spatial referencing by coordinates
	<i>Author</i>	International Organization for Standardization (ISO)
	<i>Publisher</i>	International Organization for Standardization (ISO)
	<i>Publication date</i>	2007-07-01
	<i>Edition</i>	Second Edition
	<i>Series/Journal name</i>	International Standard
	<i>Issue identification</i>	ISO 19111:2007
<i>Data source</i>	ISO Geodetic Registry	
<i>Remarks</i>	Used in geographic 2D and geographic 3D coordinate reference systems.	
<i>Abbreviation</i>	Lat	
<i>Direction</i>	north	
<i>Unit</i>	degree (supplier to define representation)	

<i>Item class</i>	CoordinateSystemAxis	
<i>Name</i>	Geodetic longitude	
<i>Item status</i>	VALID	
<i>Identifier</i>	34	
<i>Information source</i>	<i>Title</i>	ISO 19111 Geographical information - Spatial referencing by coordinates
	<i>Author</i>	International Organization for Standardization (ISO)

	<i>Publisher</i>	International Organization for Standardization (ISO)
	<i>Publication date</i>	2007-07-01
	<i>Edition</i>	Second Edition
	<i>Series/Journal name</i>	International Standard
	<i>Issue identification</i>	ISO 19111:2007
<i>Data source</i>		ISO Geodetic Registry
<i>Remarks</i>		Used in geographic 2D and geographic 3D coordinate reference systems.
<i>Abbreviation</i>		Lon
<i>Direction</i>		east
<i>Unit</i>		degree (supplier to define representation)