ISO Geodetic Registry

Item class Transformation

Name ITRF2005 to GDA94 [GA v1]

Item status VALID
Identifier 486

Information source Title ITRF to GDA94 coordinate transformations

Author John Dawson and Alex Woods

Publisherde GruyterPublication date2010-10-25Edition date2010-10-01

Series/Journal name Journal of Applied Geodesy

Issue identification 4.0
Page 189.0
ISO Geodetic Registry

Remarks Implemented 2010. RMS of transformation residuals: 4mm north, 8mm

east and 30mm vertical. Maximum residuals: 10mm north, 17 mm east

and 61mm vertical.

Operation version GA v1

Scope Spatial referencing

Operation accuracy 0.03 m

Source CRS ITRF2005 - XYZ
Target CRS GDA94 - XYZ

Operation method Time-Dependent Coordinate Frame Transformation (geocentric

Cartesian domain)

Extent

Data source

Description	Australia - onshore and offshore - mainland, Tasmania, Lord Howe Island, Norfolk Island, Macquarie Island. Christmas Island - onshore and offshore. Cocos (Keeling) Islands -	
	onshore and offshore.	
Geographic Bounding Box	West-bound longitude	93.41
	North-bound latitude	-8.47
	East-bound longitude	173.4
	South-bound latitude	-60.56

Operation parameter values

X-axis translation	-79.73 millimetre	
Y-axis translation	-6.86 millimetre	
Z-axis translation	38.03 millimetre	
X-axis rotation	-0.0351 milliarc-second	
Y-axis rotation	2.1211 milliarc-second	
Z-axis rotation	2.1411 milliarc-second	
Scale difference	6.636 parts per billion	
Rate of change of X-axis translation	2.25 millimetre per year	
Rate of change of Y-axis translation	-0.62 millimetre per year	
Rate of change of Z-axis translation	-0.56 millimetre per year	
Rate of change of X-axis rotation	1.4707 milliarc-second per year	

Rate of change of Y-axis rotation1.1443 milliarc-second per yearRate of change of Z-axis rotation1.1701 milliarc-second per yearRate of change of scale difference0.294 parts per billion per yearTime reference1994.0 year

ISO Geodetic Registry

Item class OperationMethod

Name Time-Dependent Coordinate Frame

Transformation (geocentric Cartesian domain)

Item status VALID
Identifier 94

Alias Time-Dependent 7-Parameter Transformation

Alias 14-Parameter Transformation

Alias Time-Dependent Coordinate Frame Transformation

Data source ISO Geodetic Registry

Remarks Note the analogy with the Time-dependent Position Vector

Transformation but beware of the differences! The Position Vector

Transformation convention is used by IAG.

Formula Geomatics Guidance Note No 7, part 2: Coordinate Conversions and

Transformations including Formulas

Operation parameters

X-axis translation

Y-axis translation

Z-axis translation

X-axis rotation

Y-axis rotation

Z-axis rotation

Scale difference

Rate of change of X-axis translation

Rate of change of Y-axis translation

Rate of change of Z-axis translation

Rate of change of X-axis rotation

Rate of change of Y-axis rotation

Rate of change of Z-axis rotation

Rate of change of scale difference

Time reference