Item class GeodeticCRS

NAD 83 (2007) - LatLonEHt

Item statusVALIDIdentifier397

Alias North American Datum of 1983 (2007)

Information source Title NADCON 5.0: Geometric Transformation Tool for

points in the National Spatial Reference System

Author D. Smith, A. Bilich

Publisher NOAA's National Geodetic Survey

Publication date 2017-03-27 Edition date 2017-03-27

Series/Journal name NGS Technical Report

Other citation details Replaces version 4.2 and all earlier. Provides

gridding algorithm, datum transformations, and

extents of covnversion grids.

Information source Title Notice to Adopt Standard Method for Horizontal

Datum Transformation

Author US Government

Publisher Office of Federal Register, NARA

Publication date 1990-08-10 Edition date 1990-08-10

Series/Journal name Federal Register Notice

Issue identification Volume 55, No. 155, Document: 00-18809

Page 32681.0

Other citation details Mandates use of NADCON for official

transformations between datums

Data source ISO Geodetic Registry
Scope Spatial referencing

Datum North American Datum of 1983 (2007)

Coordinate System Ellipsoidal 3D CS. Axes: latitude, longitude, ellipsoidal height. Orientations: north, east, up. UoM: degree, degree, metre.

Extent

United States and Territories - onshore

and offshore: Puerto Rico. United States (USA) - Alaska, CONUS (Alabama, Arizona, Arkansas, California, Colorado, Connecticut, Delaware, Florida, Georgia, Idaho, Illinois, Indiana, Iowa, Kansas, Kentucky, Louisiana, Maine, Maryland, Massachusetts, Michigan, Minnesota, Mississippi, Missouri, Montana, Nebraska, Nevada, New Hampshire, New Jersey, New Mexico, New York, North Carolina, North Dakota, Ohio, Oklahoma, Oregon, Pennsylvania, Rhode Island, South Carolina, South Dakota, Tennessee, Texas, Utah, Vermont, Virginia, Washington, West Virginia, Wisconsin, Wyoming). Virgin Islands (US).

Geographic Bounding Box	West-bound longitude	167.65	
	North-bound latitude	74.71	
	East-bound longitude	-63.88	
	South-bound latitude	14.92	l

Item class GeodeticDatum

North American Datum of 1983 (2007)

Item status VALID
Identifier 134

Alias NAD83(NSRS)
Alias NAD83(NSRS 2007)

Alias NAD83(2007)

Information source Title NADCON 5.0: Geometric Transformation Tool for

points in the National Spatial Reference System

Author D. Smith, A. Bilich

Publisher NOAA's National Geodetic Survey

Publication date 2017-03-27 Edition date 2017-03-27

Series/Journal name NGS Technical Report

Other citation details Replaces version 4.2 and all earlier. Provides

gridding algorithm, datum transformations, and

extents of covnversion grids.

Information source Title Notice to Adopt Standard Method for Horizontal

Datum Transformation

Author US Government

Publisher Office of Federal Register, NARA

Publication date 1990-08-10 Edition date 1990-08-10

Series/Journal name Federal Register Notice

Issue identification Volume 55, No. 155, Document: 00-18809

Page 32681.0

Other citation details Mandates use of NADCON for official

transformations between datums

Data source ISO Geodetic Registry

Remarks Reaplaces NAD83(HARN) or NAD83(FBN). Replaced by

NAD83(2011), NAD83(PA11) or NAD83(MA11).

Anchor definition This is a realization of NAD83. A nationwide adjustment of the passive

control network constrained to the NAD83 (CORS96) Epoch 2002 coordinates. The CORS coordinates remained in NAD83 (CORS96) Epoch 2002, while passive control were identified as being on NAD83 (2007). Hence, this datum is only for the passive control network. In Alaska, a different epoch was used (which epoch?). Southern California

epoch?

Scope Spatial referencing

Ellipsoid GRS 1980
Prime Meridian Greenwich

Extent

Description United States and Territories - onshore

and offshore: Puerto Rico. United States (USA) - Alaska, CONUS (Alabama, Arizona, Arkansas, California, Colorado, Connecticut, Delaware, Florida, Georgia, Idaho, Illinois, Indiana, Iowa, Kansas, Kentucky, Louisiana, Maine, Maryland, Massachusetts, Michigan,

Minnesota, Mississippi, Missouri, Montana, Nebraska, Nevada, New Hampshire, New Jersey, New Mexico, New York, North Carolina, North Dakota, Ohio, Oklahoma, Oregon, Pennsylvania, Rhode Island, South Carolina, South Dakota, Tennessee, Texas, Utah, Vermont, Virginia, Washington, West Virginia, Wisconsin, Wyoming). Virgin Islands (US).

Geographic Bounding Box

West-bound longitude167.65North-bound latitude74.71East-bound longitude-63.88South-bound latitude14.92

Item class Ellipsoid

Name GRS 1980

Item statusVALIDIdentifier27

Alias Geodetic Reference System 1980

Alias GRS1980
Alias IAG GRS80

Alias International 1979

Alias GRS80

Information source Title Geodetic Reference System 1980

Author H. Moritz

Publisher Springer International Publishing

Publication date 2003-03

Series/Journal name Journal of Geodesy Issue identification Volume 74, No. 1

Page 128–162

Information source Title Geodetic Reference System 1980

Author H. Moritz

Publisher International Association of Geodesy

Publication date 1984

Series/Journal name Bulletin Geodesique Issue identification Volume 58, No. 3

Page 395-405

Data source ISO Geodetic Registry

Remarks Adopted by IUGG 1979 Canberra. Inverse flattening is derived from

geocentric gravitational constant GM = 3986005e8 m*m*m/s/s, dynamic form factor J2 = 108263e-8 and Earth's angular velocity =

7292115e-11 rad/s.

 Semi-major axis
 6378137.0 m

 Inverse flattening
 298.257222101 m

Item class PrimeMeridian

Name Greenwich

Item status VALID
Identifier 25

Alias Zero meridian

Information source Title Why the Greenwich meridian moved

Author S. Malys, J.H. Seago, N.K. Pavlis, P.K.

Seidelmann, G.H. Kaplan

Publisher Springer International Publishing

Publication date 2015-12

Series/Journal name Journal of Geodesy Issue identification Volume 89, No. 12

Page 1263–1272

Information source Title IERS Conventions (2010)

Author G. Petit, B.J. Luzum (eds)

Publisher Verlag des Bundesamts fur Kartographie und

Geodasie

Publication date 2010

Edition date

Series/Journal name IERS Technical Notes

Issue identification 36.0

Other citation details ISSN: 1019-4568

Data source ISO Geodetic Registry

Greenwich longitude 0.0 °

Item class EllipsoidalCS

Name Ellipsoidal 3D CS. Axes: latitude, longitude,

ellipsoidal height. Orientations: north, east, up.

UoM: degree, degree, metre.

Item status VALID
Identifier 46

Information source Title ISO 19111 Geographical information - Spatial

referencing by coordinates

Author International Organization for Standardization

(ISO)

Publisher International Organization for Standardization

(ISO)

Publication date 2007-07-01

Edition Second Edition

Series/Journal name International Standard

Issue identification ISO 19111:2007

Data source ISO Geodetic Registry

Remarks Used in geographic 3D coordinate reference systems. Horizontal

coordinates referenced to this CS are in degrees. Any degree representation (e.g. DMSH, decimal, etc.) may be used but that used

epresentation (e.g. Divish, decimal, etc.) may be used but

must be declared for the user.

Axes

Item class CoordinateSystemAxis

Name Geodetic latitude

Item statusVALIDIdentifier38

Information source Title ISO 19111 Geographical information - Spatial

referencing by coordinates

Author International Organization for Standardization

(ISO)

Publisher International Organization for Standardization

(ISO)

Publication date 2007-07-01

Edition Second Edition

Series/Journal name International Standard

Issue identification ISO 19111:2007

Data source ISO Geodetic Registry

Remarks Used in geographic 2D and geographic 3D coordinate reference

systems.

Abbreviation Lat
Direction north

Unit degree (supplier to define representation)

Item class CoordinateSystemAxis

Name Geodetic longitude

Item status VALID
Identifier 34

Information source Title ISO 19111 Geographical information - Spatial

referencing by coordinates

Author International Organization for Standardization

(ISO)

Publisher International Organization for Standardization

(ISO)

Publication date 2007-07-01

Edition Second Edition

Series/Journal name International Standard

Issue identification ISO 19111:2007

Data source ISO Geodetic Registry

Remarks Used in geographic 2D and geographic 3D coordinate reference

systems.

Abbreviation Lon
Direction east

Unit degree (supplier to define representation)

Item class CoordinateSystemAxis

Name Ellipsoidal height

Item statusVALIDIdentifier36

Information source Title ISO 19111 Geographical information - Spatial

referencing by coordinates

Author International Organization for Standardization

(ISO)

Publisher International Organization for Standardization

(ISO)

Publication date 2007-07-01

Edition Second Edition

Series/Journal name International Standard

Issue identification ISO 19111:2007

Data source ISO Geodetic Registry

Remarks Used only as part of an ellipsoidal 3D coordinate system in a

geographic 3D coordinate reference system, never on its own.

Abbreviation h

Direction up
Unit metre