

ISO Geodetic Registry

| | | |
|---------------------------|---|--|
| <i>Item class</i> | Transformation | |
| <i>Name</i> | ITRF2008 to SIRGAS-CON SIR11P01 [SIRv1] | |
| <i>Item status</i> | VALID | |
| <i>Identifier</i> | 513 | |
| <i>Information source</i> | <i>Title</i> | Use of velocities in the processing of GNSS data |
| | <i>Author</i> | Sistema de Referencia Geocéntrico para las Américas (SIRGAS) |
| | <i>Publisher</i> | Sistema de Referencia Geocéntrico para las Américas (SIRGAS) |
| | <i>Publication date</i> | 2017 |
| | <i>Other citation details</i> | Website |
| <i>Information source</i> | <i>Title</i> | The 2009 Horizontal Velocity Field for South America and the Caribbean |
| | <i>Author</i> | H. Drewes, O. Heidbach |
| | <i>Publisher</i> | Springer Berlin Heidelberg |
| | <i>Publication date</i> | 2012 |
| | <i>Series/Journal name</i> | International Association of Geodesy Symposia |
| | <i>Issue identification</i> | 136.0 |
| | <i>Page</i> | 657-664 |
| | <i>Other citation details</i> | In Kenyon S., Pacino M., Marti U. (eds) Geodesy for Planet Earth. International Association of Geodesy Symposia, Vol 136. Springer, Berlin, Heidelberg |
| <i>Information source</i> | <i>Title</i> | Sistema de Referencia Geocentrico para las Americas (SIRGAS) |
| | <i>Author</i> | Sistema de Referencia Geocéntrico para las Américas (SIRGAS) |
| | <i>Publisher</i> | Sistema de Referencia Geocéntrico para las Américas (SIRGAS) |
| | <i>Publication date</i> | 2018 |
| | <i>Other citation details</i> | Website |
| <i>Information source</i> | <i>Title</i> | Recent activities of the IGS Regional Network Associate Analysis Centre for SIRGAS (IGS RNAAC SIR) |
| | <i>Author</i> | L. Sanchez, M. Seitz |
| | <i>Publisher</i> | Deutsches Geodaetisches Forschungsinstitut, Munich, Germany, PANGAEA |
| | <i>Publication date</i> | 2011 |
| | <i>Series/Journal name</i> | DGFI Report |
| | <i>Issue identification</i> | No. 87 |
| | <i>Other citation details</i> | Data for paper included in supplement SIRGAS reference frame realization SIR11P01. |
| <i>Data source</i> | ISO Geodetic Registry | |
| <i>Remarks</i> | Null reference frame transformation between ITRF2008 and SIRGAS-CON SIR11P01. | |
| <i>Operation version</i> | SIRv1 | |
| <i>Scope</i> | Spatial referencing | |
| <i>Operation accuracy</i> | 0.01 m | |
| <i>Source CRS</i> | ITRF2008 - XYZ | |
| <i>Target CRS</i> | SIRGAS-CON SIR11P01 - LatLon | |
| <i>Operation method</i> | Time-Dependent Position Vector Transformation (geocentric Cartesian domain) | |

Extent

| | | |
|--------------------------------|---|---------|
| <i>Description</i> | South America - onshore and offshore. Central America - onshore and offshore. Mexico - onshore and offshore. | |
| <i>Geographic Bounding Box</i> | <i>West-bound longitude</i> | -122.19 |
| | <i>North-bound latitude</i> | 32.72 |
| | <i>East-bound longitude</i> | -25.28 |
| | <i>South-bound latitude</i> | -59.87 |

Operation parameter values

| | |
|---|--------------------------------|
| <i>Time reference</i> | 2005.0 year |
| <i>Rate of change of scale difference</i> | 0.0 parts per billion per year |
| <i>Rate of change of Z-axis rotation</i> | 0.0 milliarc-second per year |
| <i>Rate of change of Y-axis rotation</i> | 0.0 milliarc-second per year |
| <i>Rate of change of X-axis rotation</i> | 0.0 milliarc-second per year |
| <i>Rate of change of Z-axis translation</i> | 0.0 millimetre per year |
| <i>Rate of change of Y-axis translation</i> | 0.0 millimetre per year |
| <i>Rate of change of X-axis translation</i> | 0.0 millimetre per year |
| <i>Scale difference</i> | 0.0 parts per billion |
| <i>Z-axis rotation</i> | 0.0 milliarc-second |
| <i>Y-axis rotation</i> | 0.0 milliarc-second |
| <i>X-axis rotation</i> | 0.0 milliarc-second |
| <i>Z-axis translation</i> | 0.0 millimetre |
| <i>Y-axis translation</i> | 0.0 millimetre |
| <i>X-axis translation</i> | 0.0 millimetre |

ISO Geodetic Registry

| | |
|--------------------|--|
| <i>Item class</i> | OperationMethod |
| <i>Name</i> | Time-Dependent Position Vector Transformation (geocentric Cartesian domain) |
| <i>Item status</i> | VALID |
| <i>Identifier</i> | 82 |
| <i>Alias</i> | Time-Dependent 7-Parameter Transformation |
| <i>Alias</i> | 14-Parameter Transformation |
| <i>Alias</i> | Time-Dependent Position Vector Transformation |
| <i>Data source</i> | ISO Geodetic Registry |
| <i>Remarks</i> | Note the analogy with the rotation for the Time-dependent Coordinate Frame Transformation but beware of the differences! The Position Vector Transformation convention is used by IAG. |
| <i>Formula</i> | Geomatics Guidance Note No 7, part 2: Coordinate Conversions and Transformations including Formulas |

Operation parameters

| |
|---|
| <i>X-axis translation</i> |
| <i>Y-axis translation</i> |
| <i>Z-axis translation</i> |
| <i>X-axis rotation</i> |
| <i>Y-axis rotation</i> |
| <i>Z-axis rotation</i> |
| <i>Scale difference</i> |
| <i>Rate of change of X-axis translation</i> |
| <i>Rate of change of Y-axis translation</i> |
| <i>Rate of change of Z-axis translation</i> |
| <i>Rate of change of X-axis rotation</i> |
| <i>Rate of change of Y-axis rotation</i> |
| <i>Rate of change of Z-axis rotation</i> |
| <i>Rate of change of scale difference</i> |
| <i>Time reference</i> |