

ISO Geodetic Registry

<i>Item class</i>	Transformation	
<i>Name</i>	ITRF96 to GDA94 [GA v1]	
<i>Item status</i>	VALID	
<i>Identifier</i>	546	
<i>Information source</i>	<i>Title</i>	International Terrestrial Reference Frame (ITRF) to GDA94 Coordinate Transformations
	<i>Author</i>	J. Dawson, J. Steed
	<i>Publisher</i>	Geoscience Australia
	<i>Publication date</i>	2004-03-01
	<i>Edition date</i>	
<i>Data source</i>	ISO Geodetic Registry	
<i>Remarks</i>	Implemented 2001. Replaced by Dawson and Woods transformation of 2010, ITRF96 to GDA94 [GA-Aus 2010 v2].	
<i>Operation version</i>	GA v1	
<i>Scope</i>	Spatial referencing	
<i>Operation accuracy</i>	0.1 m	
<i>Source CRS</i>	ITRF96 - XYZ	
<i>Target CRS</i>	GDA94 - XYZ	
<i>Operation method</i>	Time-Dependent Coordinate Frame Transformation (geocentric Cartesian domain)	

Extent

<i>Description</i>	Australia - onshore and offshore - mainland, Tasmania, Lord Howe Island, Norfolk Island, Macquarie Island. Christmas Island - onshore and offshore. Cocos (Keeling) Islands - onshore and offshore.	
<i>Geographic Bounding Box</i>	<i>West-bound longitude</i>	93.41
	<i>North-bound latitude</i>	-8.47
	<i>East-bound longitude</i>	173.4
	<i>South-bound latitude</i>	-60.56

Operation parameter values

<i>X-axis translation</i>	-0.014 metre
<i>Y-axis translation</i>	0.0431 metre
<i>Z-axis translation</i>	0.201 metre
<i>X-axis rotation</i>	0.012464 arc-second
<i>Y-axis rotation</i>	0.012013 arc-second
<i>Z-axis rotation</i>	0.006434 arc-second
<i>Scale difference</i>	0.024607 parts per million
<i>Rate of change of X-axis translation</i>	0.0411 metre per year
<i>Rate of change of Y-axis translation</i>	0.0218 metre per year
<i>Rate of change of Z-axis translation</i>	0.0383 metre per year
<i>Rate of change of X-axis rotation</i>	0.002542 arc-second per year
<i>Rate of change of Y-axis rotation</i>	0.001431 arc-second per year
<i>Rate of change of Z-axis rotation</i>	-2.34E-4 arc-second per year
<i>Rate of change of scale difference</i>	0.005897 parts per million per year

Time reference

2000.0 year

ISO Geodetic Registry

<i>Item class</i>	OperationMethod
<i>Name</i>	Time-Dependent Coordinate Frame Transformation (geocentric Cartesian domain)
<i>Item status</i>	VALID
<i>Identifier</i>	94
<i>Alias</i>	Time-Dependent 7-Parameter Transformation
<i>Alias</i>	14-Parameter Transformation
<i>Alias</i>	Time-Dependent Coordinate Frame Transformation
<i>Data source</i>	ISO Geodetic Registry
<i>Remarks</i>	Note the analogy with the Time-dependent Position Vector Transformation but beware of the differences! The Position Vector Transformation convention is used by IAG.
<i>Formula</i>	Geomatics Guidance Note No 7, part 2: Coordinate Conversions and Transformations including Formulas

Operation parameters

<i>X-axis translation</i>
<i>Y-axis translation</i>
<i>Z-axis translation</i>
<i>X-axis rotation</i>
<i>Y-axis rotation</i>
<i>Z-axis rotation</i>
<i>Scale difference</i>
<i>Rate of change of X-axis translation</i>
<i>Rate of change of Y-axis translation</i>
<i>Rate of change of Z-axis translation</i>
<i>Rate of change of X-axis rotation</i>
<i>Rate of change of Y-axis rotation</i>
<i>Rate of change of Z-axis rotation</i>
<i>Rate of change of scale difference</i>
<i>Time reference</i>