ISO Geodetic Registry

Item class Transformation

Name ATS77 to NAD83(CSRS) v2 [NBv1]

Item status VALID Identifier 647

Information source Title FAQ: What are some of the transformation

methods for Canada?

Author Esri Canada
Publisher Esri, Redlands, CA
Publication date 2016-05-05

Issue identification Article ID: 000011846

Information source Title Data Catalogue: NTv2 Grid Shift Files

Author GeoNB

Publisher Service New Brunswick, Government of New

Brunswick

Publication date 2011-06-01

Data source ISO Geodetic Registry

Remarks Grid tranformation in NTv2 format adopted for use in New Brunswick.

Operation version NBv1

Scope Spatial referencing

Operation accuracy 1.5 m

Source CRS ATS77 - LatLon

Target CRS NAD83(CSRS) v2 - LatLon

Operation method NTv2

Extent

Description	Canada - onshore and offshore - New	
	Brunswick.	
Geographic Bounding Box	West-bound longitude	-69.05
	North-bound latitude	48.07
	East-bound longitude	-63.7
	South-bound latitude	44.56

Operation parameter values

ND7700-0 CCD	Latitude and Langitude difference of file
NB7783v2.GSB	Latitude and Longitude difference file
110110012:000	Latitado dila Lorigitado dilitororios ino
ND1100V2.00D	Latitude and Longitude americance me

ISO Geodetic Registry

Item class OperationMethod

Name NTv2
Item status VALID
Identifier 95

Alias National Transformation version 2 grid shift

Data source ISO Geodetic Registry

Remarks National Transformation version 2 grid shift file interpolation. Geodetic

transformation operating on a grid of 2D geographic coordinate

differences by bi-linear interpolation. Assumes longitudes to be positive

west.

Operation parameters

Latitude and Longitude difference file