ISO Geodetic Registry

Item class Transformation

NAD27 to NAD83(CSRS) v3 [BCv2]

Item statusVALIDIdentifier659

Information source Title FAQ: What are some of the transformation

methods for Canada?

Author Esri Canada
Publisher Esri, Redlands, CA
Publication date 2016-05-05

Issue identification Article ID: 000011846
Title Desktop Applications: NTv2

Information source Title Desktop Applications: NTv2
Author Canadian Geodetic Survey

Publisher Canadian Geodetic Survey, Surveyor General

Branch, Earth Sciences Sector, Natural Resources Canada, Government of Canada

Publication date 2017-02-28

Information source Title MASCOT Survey Utilities: National

Transformation Coordinate Conversions

Author GeoBC

Publisher GeoBC, Government of British Columbia

Publication date 2017-03-28

Data source ISO Geodetic Registry

Remarks Grid tranformation in NTv2 format adopted for use on Vancouver

Island, outside the Capital Regional District, British Columbia, Canada.

Operation version BCv2

Scope Spatial referencing

Operation accuracy 1.5 m

Source CRS NAD27 - LatLon

Target CRS NAD83(CSRS) v3 - LatLon

Operation method NTv2

Extent

Canada - onshore and offshore - British
Columbia - Vancouver Island excluding Capital
Regional District.

Geographic Bounding Box
West-bound longitude
North-bound latitude
East-bound longitude
South-bound latitude
South-bound latitude
South-bound latitude
48.5

Operation parameter values

Latitude and Longitude difference file NVI27_05.GSB

ISO Geodetic Registry

Item class OperationMethod

Name NTv2
Item status VALID
Identifier 95

Alias National Transformation version 2 grid shift

Data source ISO Geodetic Registry

Remarks National Transformation version 2 grid shift file interpolation. Geodetic

transformation operating on a grid of 2D geographic coordinate

differences by bi-linear interpolation. Assumes longitudes to be positive

west.

Operation parameters

Latitude and Longitude difference file