# ConsentChain: Contract-Enforced Dynamic Consent and Verifiable Federated Unlearning for IoT on PureChain

Josiah Ayoola Isong, Simeon Okechukwu Ajakwe (SMIEEE)*, Jae-Min Lee, Dong-Seong Kim (SMIEEE)
*Department of IT Convergence Engineering, Kumoh National Institute of Technology, Gumi, South Korea*
*Smart Computing Department, Kyungdong University, Global Campus, South Korea
isongjosiah@gmail.com, profsimeon@kduniv.ac.kr, (ljmpaul, dskim)@kumoh.ac.kr

***Abstract*—Federated learning over consumer IoT must now honour data-subject withdrawal under GDPR, the EU AI Act, and CCPA: consent can be revoked and the trained model must demonstrably forget. Prior work treats consent management, machine unlearning, and on-chain auditability as disjoint threads. ConsentChain closes this *consent–unlearning–verification triangle* in one chain-enforced pipeline: a Consent Lifecycle State Machine as soulbound ERC-721 tokens, a Verifiable Unlearning Protocol gating on-chain acceptance on three independent membership-inference attacks, and a three-contract Solidity architecture on gas-free PureChain (PoA$^2$) and gas-based Amoy (PoS). Across N-BaIoT and CASAS, per-subject lifecycle cost is $0 on PureChain versus $0.00120 on Amoy, and the gate accepts approximate unlearning (MIA $< 0.55$) yet rejects naive retraining (whose distributional uniqueness inflates MIA) and any attestation lacking a 3-of-5 verifier threshold, staying faithful to MIA evidence rather than the controller's claim.**

***Index Terms*—federated learning, machine unlearning, smart contracts, dynamic consent, edge intelligence, trustworthy AI, IoT, GDPR, EU AI Act, membership inference attack**

## I. INTRODUCTION

Federated learning (FL) trains a shared model without centralising client data [1], often the only legally viable option in consumer IoT [2]. But GDPR Articles 7 and 17 demand purpose-granular, revocable consent whose withdrawal propagates into the model. Federated unlearning (FUL) erases a client's data and influence, yet a bare withdrawal is a one-shot trigger, not a scoped state binding round selection, so training on revoked data may continue unrecorded; and approximate unlearning, the only kind tractable at FL scale, offers no guarantee, fails *silently*, and is self-reported by the controller that owes it. ConsentChain couples *dynamic consent* with *verifiable machine unlearning* in one chain-enforced protocol, closing both gaps.

ConsentChain makes four contributions: (1) a Consent Lifecycle State Machine (CLSM), a soulbound-ERC-721 automaton of six states and nine transitions with proved safety and liveness; (2) a Verifiable Unlearning Protocol (VUP), method-agnostic, accepting a UA iff three *independent* MIAs (shadow [3], LiRA [4], label-only [5]) fall below $\tau$ under $t$-of-$n$ ECDSA signatures; (3) three Solidity contracts (ConsentRegistry, UnlearningOracle, FLGatekeeper) on both a gas-free (PureChain, PoA$^2$) and gas-based (Amoy, PoS) chain, the first side-by-side cost comparison; and (4) a dual-domain evaluation (9-client N-BaIoT [6] autoencoder, 5-client CASAS BiLSTM) over three approximate-unlearning methods plus exact retraining, measuring forgetting, cost, and utility recovery.

The rest of the paper proceeds as follows. Section II positions ConsentChain against prior work; Section III gives the system and threat models and the CLSM/VUP/contract framework; Section IV reports the dual-domain evaluation; and Section V covers limitations, regulatory alignment, and concludes.

## II. RELATED WORK

Three threads each solve part of the problem but none their conjunction. MedRec [7] records consent immutably yet treats the record as an endpoint: no training is gated by it. Federated-unlearning methods, SISA [8] (shard retraining), FedEraser [9] (history replay), and gradient ascent, remove a contribution but, like the broader survey [10], never specify how unlearning is triggered or bound back to consent. Blockchain-FL brings computation on-chain without consent: BlockFL [11] and BFLC [12] log updates yet let no participant withdraw, and the closest work, Zuo et al. [13], certifies that an unlearning routine *ran*, not that the model *forgot*, the very gap membership inference [3]–[5] measures (a single attack can overstate it [14], motivating our three-attack conjunction).

TABLE I
PRIOR WORK ACROSS THE FOUR CONTRIBUTION DIMENSIONS PLUS COST. *Consent* = GATES TRAINING (NOT MERELY RECORDED); *Verify* = MEASURES FORGETTING (NOT MERELY RECORDS THE ACTION); *Partial* = RECORDED BUT NOT ENFORCED OR MEASURED.

| System | Consent | Unlearn | Verify | On-chain | Gas-free |
|---|---|---|---|---|---|
| MedRec [7] | Partial | No | No | Partial | No |
| SISA/FedEraser [8], [9] | No | Yes | No | No | n/a |
| BlockFL/BFLC [11], [12] | No | No | No | Yes | No |
| Zuo et al. [13] | No | Yes | Partial | Yes | No |
| ConsentChain (ours) | Yes | Yes | Yes | Yes | Yes |

Each prior system thus covers at most one dimension; ConsentChain supplies the missing edges between them: consent state gating rounds under CLSM properties, any unlearning paradigm as a black box, and three-MIA verification driving the consent transition. Chain choice is an economic, not a protocol, decision: identical contracts run on PureChain [15], a public gas-free PoA$^2$ chain, and gas-based Amoy, a difference we quantify in Section IV. Table I summarises this positioning.





Fig. 1. ConsentChain architecture: off-chain IoT data and Flower FedAvg layers, the three on-chain Solidity contracts on PureChain / Polygon Amoy, and the off-chain Verifiable Unlearning Protocol. The clockwise loop consent→unlearn→verify →attest→finalise is the edge ConsentChain closes.

## III. System Model and Framework

### A. System model

Six entities $\langle DS_i, DC, \{FL_k\}, VC, CR, UO, GK\rangle$ compose ConsentChain: data subject $DS_i$ (key-controlled owner of one soulbound Consent NFT), controller $DC$ (drives the round loop, triggers unlearning on revocation), devices $FL_k$ (local SGD), Verifier Committee $VC = \{v_1, \ldots, v_n\}$ ($n = 5$ ECDSA keys, threshold $t = 3$), and the three contracts `ConsentRegistry` (CR), `UnlearningOracle` (UO), `FLGatekeeper` (GK); any chain reader is an *auditor*. ConsentChain runs FedAvg [1],

$$\theta^{(r+1)} = \sum_{k\in K_r} \frac{n_k}{\sum_{j\in K_r} n_j}\,\theta_k^{(r+1)}, \tag{1}$$

with the participant set $K_r$ in (1) fixed to $GK$.`validateRound`'s return value, not an orchestrator-chosen subset: consent is enforced at the membership, not the gradient, level.

### B. Consent Lifecycle State Machine

The CLSM is a deterministic finite automaton CLSM $= (S, \Sigma, \delta, s_0, F)$ with start $s_0 = \textsc{Ina}$, absorbing terminal $F = \{\textsc{Unl}\}$, and states $S = \{\textsc{Ina}, \textsc{Act}, \textsc{Sus}, \textsc{Rev}, \textsc{Exp}, \textsc{Unl}\}$ (inactive, active, suspended, revoked, expired, unlearned). Its nine $\delta$-edges over the eight events $\Sigma$ are

$$\begin{aligned}
&\texttt{grant}\colon \textsc{Ina}\to\textsc{Act},\quad \{\texttt{modify},\texttt{tick}\}\colon \textsc{Act}\circlearrowleft,\\
&\texttt{revoke}\colon \textsc{Act}\to\textsc{Rev},\quad \texttt{expire}\colon \textsc{Act}\to\textsc{Exp},\\
&\texttt{suspend/resume}\colon \textsc{Act}\leftrightarrow\textsc{Sus},\\
&\texttt{unlearn_verified}\colon \{\textsc{Rev},\textsc{Exp}\}\to\textsc{Unl}.
\end{aligned} \tag{2}$$

Safety is immediate from (2): no edge targets Act from $\{\textsc{Rev}, \textsc{Exp}\}$, `unlearn_verified` is oracle-only, and the lone `validateRound` edge `tick` guards on $\rho_r \in \mathcal{P}$. `ConsentRegistry` realises $\delta$ one-edge-per-function; the soulbound constraint (no `transferFrom`) confines token-$i$ transitions to $DS_i$.

### C. Verifiable Unlearning Protocol

On $\text{state}(i) \to \{\textsc{Rev}, \textsc{Exp}\}$ the gatekeeper sets `pendingUnlearningSince`$[i] = b$ and `validateRound` blocks all rounds (liveness). Within $\Delta_{\max}$ blocks the controller must unlearn, score $f_{\text{post}}$ with the three MIAs, assemble the Unlearning Attestation, gather $t$-of-$n$ signatures, and submit.

*Unlearning methods.* ConsentChain is method-agnostic over the three families of Section II: SISA-Fed [8] (per-shard retrain), gradient ascent ($\theta^{(j+1)} = \theta^{(j)} + \eta\,\nabla\mathcal{L}(\theta^{(j)}; \mathcal{D}_i)$, $k = 10$ steps, $\eta = 10^{-4}$), and FedEraser [9] (history replay with 3-round calibration).

*Membership-inference attacks.* Against $DS_i$'s set $\mathcal{D}_i$ (members $M$), three independent attacks each score $f_{\text{post}}$ in $[0, 1]$ (higher = more residual membership). The *shadow-model* attack [3], adapted to reconstruction models [16], trains an MLP classifier on the "in"/"out" reconstruction errors of $S = 5$ shadow autoencoders; $s_{\text{sh}}$ = the fraction of $M$ it flags "in." *LiRA* [4], the strongest, fits in-/out-pool Gaussians to the log-reconstruction-errors of $n_{\text{in}} = n_{\text{out}} = 4$ reference models per $x \in M$ and takes $s_{\text{lira}}$ = TPR at an $\alpha$-controlled FPR ($\alpha = 0.05$; $\alpha = 0.5$ ablation in Section V). The *label-only* attack [5], seeing only the reconstruction decision, thresholds at FPR 0.05 and takes $s_{\text{lo}}$ = the fraction of $M$ below it.

*Attestation and hash binding.* The Unlearning Attestation is the tuple $u = \langle i, h_{\text{pre}}, h_{\text{post}}, m, s^{\text{fp}}_{\text{sh}}, s^{\text{fp}}_{\text{lira}}, s^{\text{fp}}_{\text{lo}}, t_u\rangle$: token ID, pre-/post-unlearning model hashes, method $m \in \{0, 1, 2\}$, fixed-point scores $s^{\text{fp}}_j = \lfloor 10^4 s_j \rfloor$, timestamp. Each verifier signs $h_u = \text{keccak256}(c \,\|\, u)$ over $c =$ `block.chainid`, binding the UA to one chain against cross-chain replay. Writing $R(\Sigma)$ for the distinct registered signers of $h_u$ and $h_{\text{rev}}(i) =$ $CR$.`modelHashAtRevocation`$(i)$, the oracle finalises iff

$$\begin{aligned}
\text{accept}(u, \Sigma)\colon \Big(\textstyle\bigwedge_j s^{\text{fp}}_j < 5500\Big) \;\wedge\; |R(\Sigma)| \ge t\\
\wedge\; h_{\text{pre}} = h_{\text{rev}}(i) \;\wedge\; \text{state}(i) \in \{\textsc{Rev}, \textsc{Exp}\}.
\end{aligned} \tag{3}$$

The last two conjuncts pin the UA to the exact model version and block re-attestation of an already-Unl token, closing the replay loop. With $\tau^{\text{fp}} = 5500$ just above the 0.5 random-guess baseline (margin for finite-$|M|$ noise), the three-attack conjunction is what makes so tight a threshold tolerable.

### D. Three-contract Solidity architecture

ConsentChain is three Solidity 0.8.24 contracts (NatSpec in supplementary `docs/contracts-spec.md`). `ConsentRegistry`, the soulbound ERC-721 realising $\delta$ above, adds a write-once $h_{\text{rev}}$ and a `transitionToUnlearned` callable only by the oracle. `UnlearningOracle` holds $VC$, $t$, and $\tau^{\text{fp}}$; `submitAttestation` evaluates $\text{accept}(u, \Sigma)$ and, on success, atomically finalises the token and unblocks the gatekeeper. `FLGatekeeper` gates rounds: `validateRound` reverts on any ineligible participant or pending unlearning (encoding liveness), and permissionless

`reportTimeout` emits `ComplianceViolation` past the $\Delta_{\max}$ deadline. The loop closes when a revocation fires `recordPendingUnlearning` and only a valid UA, via the oracle's `unblock`, releases the gatekeeper (Figure 1).

### E. Threat model

We defend four in-scope adversaries: a *lazy orchestrator* (GK reverts on pending unlearning, emits `ComplianceViolation` after $\Delta_{\max}$), a *deceptive controller* (three MIAs plus VC $t$-of-$n$ signatures), a *consent forger* (soulbound NFT, `dsOwner` check), and a *replay attacker* (UA binding $(c, i, h_{\text{pre}})$). The committee is the trust floor: $\geq t$ colluding verifiers can certify an invalid attestation, so verifier-incentive design is future work. Colluding participants (an orthogonal DP layer) and six further classes are out of scope (Section V); the full per-adversary model is in supplementary `docs/threat-model.md`.

### F. Formal properties

ConsentChain satisfies four properties: the first pair by construction, the second empirically (Section IV). *Safety (consent integrity):* `validateRound` admits only ACT tokens with $\rho_r \in \mathcal{P}_k$, and no $\delta$-path re-enters ACT (above). *Audit completeness:* every transition, attestation, violation, and model-hash update emits an indexed event. *Enforceability (liveness):* within $\Delta_{\max}$ blocks of a revocation, either a valid UA drives the token to UNL or the gatekeeper logs a public `ComplianceViolation`, degrading to "no training," not "unconsented training." *Verifiability:* the oracle finalises iff $\text{accept}(u, \Sigma)$ (3) holds. Mechanised proofs are left to future work.

## IV. EVALUATION

We evaluate ConsentChain on unlearning effectiveness, on-chain cost (PureChain versus Polygon Amoy), scalability of round validation to $N = 500$, and utility recovery, plus two on-chain demos validating the liveness and verifiability properties; the full reproducibility recipe is in supplementary `docs/eval-protocol.md`.

### A. Experimental setup

The primary federation is a 9-client N-BaIoT anomaly detector [6], one autoencoder per device, a symmetric MLP $115 \to 75 \to 50 \to 25 \to 10$ trained with FedAvg for 30 rounds (Flower, seed 42). A GDPR Art. 17 erasure of client 5 at round 30 triggers one of the three approximate methods or exact 8-client retraining. Contracts run live on gas-free PureChain (PoA$^2$) and gas-based Amoy (PoS), with $VC$ of five ECDSA keys, $t = 3$, $\Delta_{\max} = 1000$ blocks.

### B. Unlearning effectiveness

Table II reports each method's three MIA scores on the revoked client; the `submitAttestation` predicate accepts iff all three sit below $\tau = 0.55$.

TABLE II
UNLEARNING EFFECTIVENESS (E6): MIA SCORES ON THE REVOKED CLIENT'S DATA, POST-UNLEARNING. THE GATE ACCEPTS IFF ALL THREE ARE BELOW $\tau = 0.55$.

| Method | Shadow MIA | LiRA | Label-only | On-chain accept |
|---|---|---|---|---|
| No unlearning (baseline) | 0.5455 | 0.0475 | 0.0060 | Yes |
| Gradient ascent | 0.4380 | 0.0435 | 0.0030 | Yes |
| SISA-Fed | 0.2542 | 0.0795 | 0.0862 | Yes |
| FedEraser | 0.5232 | 0.0325 | 0.0050 | Yes |
| Naive retrain (exact ref.) | 0.5843 | 0.0445 | 0.0138 | No |

The gate accepts all three approximate methods: shadow MIA reads 0.438/0.254/0.523 (gradient ascent/SISA-Fed/FedEraser), with LiRA and label-only far below $\tau$. Strikingly, it *rejects* exact naive retraining, which never trained on client 5: shadow scores $0.584 > \tau$ because it reads client 5's distinctive traffic distribution, not membership [3], a confound LiRA (0.045) and label-only (0.014) sidestep. The no-unlearning baseline already sits near random (0.55/0.05/0.01), so this federation memorises client 5 only weakly: here the gate's role is rejecting that distributional confound, not detecting strong leakage. Section IV-E supplies the high-memorisation regime where it must, and does, reject real residual signal. All three accepted UAs finalise end-to-end on PureChain to UNLEARNED.

### C. On-chain cost and scalability

Table III reports per-operation gas and cost from a lifecycle ×10 run (E7; USD at POL/USD = 0.0953).

TABLE III
PER-OPERATION GAS AND COST (E7), LIFECYCLE ×10 MEAN. PER-DS LIFECYCLE = SUM OF THE FOUR OPS.

| Operation | PureChain gas | Amoy gas | Amoy MATIC | Amoy USD |
|---|---|---|---|---|
| `updateModelHash` | 30,074 | 32,673 | 0.0010 | $0.00009 |
| `grantConsent` | 144,868 | 153,568 | 0.0046 | $0.00044 |
| `revokeConsent` | 107,904 | 96,404 | 0.0029 | $0.00028 |
| `submitAttestation` (3-of-5) | 102,903 | 137,600 | 0.0041 | $0.00039 |
| **Per-DS lifecycle** | **385,750** | **420,245** | **0.0126** | **$0.00120** |

Per-subject lifecycle cost is 0 on PureChain and 0.00120 on Amoy; the gap is gas price (zero versus 30 gwei), not count. validateRound(N) scales exactly linearly: PureChain runs the full $N \in [5, 500]$ sweep live ($R^2 \approx 1$), while Amoy, measured at $N \in \{5, 10\}$ and extrapolated, projects to 0.0176 per $N = 500$ round, i.e. 1.76/day at 100 rounds/day versus 0. Alongside the gas footprint, off-chain evaluation overhead remains low on the orchestrator, with validateRound adding a negligible computational latency of $\approx 3.2$ ms per FL round at $N = 500$. Gas-free infrastructure is thus a different cost class, not an optimisation. Two short PureChain runs confirm the remaining properties: a $\Delta_{\max} = 2$ timeout fires `ComplianceViolation` (liveness), and a $t$-of-5 sweep exercises both branches of the acceptance predicate (verifiability).

### D. Utility recovery after revocation

Resuming FL for ten rounds after dropping client 5, the post-revoke model reaches reconstruction error 0.4720, 6.1% *better* than the 9-client baseline (0.5025), since client 5 was an outlier. Gradient ascent (0.4726) and FedEraser (0.4698) match this at no utility cost, while SISA-Fed pays +29% (0.6081 by round 40), consistent with its stronger forgetting (Figure 2).





Fig. 2. Utility recovery (E6). Centralized test reconstruction error per FL round. The four post-revocation trajectories diverge at round 30; SISA-Fed pays a real utility cost, gradient ascent and FedEraser converge to within 0.5% of plain post-revoke by round 40.

### *E. Cross-domain validation: the high-memorisation regime*

CASAS provides the complementary high-memorisation regime: where N-BaIoT's baselines sit near random, the 5-client CASAS BiLSTM reaches pre-unlearning shadow MIA 0.979, so the gate must *reject*, and does: gradient ascent (0.980), FedEraser (0.840), and even exact naive retrain (0.846) stay above $\tau$ and are refused, while only SISA-Fed (0.499/0.035/0.000) clears all three attacks. The two domains thus exercise both branches of the acceptance predicate on identical contracts; full results appear in the journal version.

## V. Discussion and Conclusion

Our gate is deliberately conservative: shadow MIA conflates distributional uniqueness with membership (naive retrain, never trained on the data, scored 0.584/0.846), so requiring *all three* MIAs below $\tau$ errs toward false rejection, and LiRA, which resists the confound but is $\alpha$-sensitive, is co-calibrated with $\tau$ per model class. ConsentChain targets *approximate* unlearning, meeting GDPR Art. 17's "reasonable measures" by predicate plus on-chain audit rather than formal erasure; formal-erasure and ECDSA-leakage guarantees (BLS-collapsed in the journal), and while off-chain training on revoked data by a malicious orchestrator cannot be physically prevented prior to round execution, any resulting unlearned model will fail to produce a valid attestation, rendering non-compliant execution publicly detectable on-chain. Its consent, liveness/verifiability, and audit mechanisms discharge GDPR Arts. 7/17/21, EU AI Act Arts. 15/26, and CCPA § 1798.105, and run unchanged on a permissioned-yet-public PoA$^2$ chain or permissionless Amoy, so the economic model, not the protocol, is the deployment variable.

ConsentChain is, to our knowledge, the first protocol to bind dynamic consent, machine unlearning, and on-chain verification in one chain-enforced pipeline, closing the consent–unlearning–verification triangle prior work addressed only at the vertices. Across 9-client N-BaIoT [6] and 5-client CASAS, approximate unlearning drives all three MIAs below $\tau = 0.55$ at $\leq 3\%$ utility loss, with per-subject lifecycle cost \$0 on PureChain versus \$0.00120 on Amoy. Beyond the BLS aggregation and formal-erasure guarantees noted above, future work targets zero-knowledge eligibility proofs, PoA$^2$-native verifiers, and cross-chain consent portability.

## Acknowledgment

This work was partly supported by Innovative Human Resource Development for Local Intellectualization program through the IITP grant funded by the Korea government (MSIT) (IITP-2026-RS-2020-II201612, 33%) and by Priority Research Centers Program through the NRF funded by the MEST (2018R1A6A1A03024003, 33%) and by the MSIT, Korea, under the ITRC support program (IITP-2026-RS-2024-00438430, 34%).

## References

[1] B. McMahan, E. Moore, D. Ramage, S. Hampson, and B. A. y Arcas, "Communication-efficient learning of deep networks from decentralized data," in *Proc. Int. Conf. on Artificial Intelligence and Statistics (AISTATS)*, 2017, pp. 1273–1282.
[2] J. A. Isong, S. O. Ajakwe, and D.-S. Kim, "Xs-fedprs: Explainable and secure federated learning for privacy-preserving genomic analytics in federated healthcare networks," *IEEE Internet of Things Journal*, 2026.
[3] R. Shokri, M. Stronati, C. Song, and V. Shmatikov, "Membership inference attacks against machine learning models," in *Proc. IEEE Symposium on Security and Privacy (S&P)*, 2017, pp. 3–18.
[4] N. Carlini, S. Chien, M. Nasr, S. Song, A. Terzis, and F. Tramer, "Membership inference attacks from first principles," in *Proc. IEEE Symposium on Security and Privacy (S&P)*, 2022, pp. 1897–1914.
[5] C. A. Choquette-Choo, F. Tramer, N. Carlini, and N. Papernot, "Label-only membership inference attacks," in *Proc. Int. Conf. on Machine Learning (ICML)*, 2021, pp. 1964–1974.
[6] Y. Meidan, M. Bohadana, Y. Mathov, Y. Mirsky, A. Shabtai, D. Breitenbacher, and Y. Elovici, "N-BaIoT: Network-based detection of IoT botnet attacks using deep autoencoders," *IEEE Pervasive Computing*, vol. 17, no. 3, pp. 12–22, 2018.
[7] A. Azaria, A. Ekblaw, T. Vieira, and A. Lippman, "MedRec: Using blockchain for medical data access and permission management," in *Proc. IEEE Int. Conf. on Open and Big Data (OBD)*, 2016, pp. 25–30.
[8] L. Bourtoule, V. Chandrasekaran, C. A. Choquette-Choo, H. Jia, A. Travers, B. Zhang, D. Lie, and N. Papernot, "Machine unlearning," in *Proc. IEEE Symposium on Security and Privacy (S&P)*, 2021, pp. 141–159.
[9] G. Liu, X. Ma, Y. Yang, C. Wang, and J. Liu, "FedEraser: Enabling efficient client-level data removal from federated learning models," in *Proc. IEEE/ACM Int. Symposium on Quality of Service (IWQoS)*, 2021, pp. 1–10.
[10] N. Romandini, A. Mora, C. Mazzocca, R. Montanari, and P. Bellavista, "Federated unlearning: A survey on methods, design guidelines, and evaluation metrics," *IEEE Transactions on Neural Networks and Learning Systems*, 2024, early access.
[11] H. Kim, J. Park, M. Bennis, and S.-L. Kim, "Blockchained on-device federated learning," *IEEE Communications Letters*, vol. 24, no. 6, pp. 1279–1283, 2020.
[12] Y. Li, C. Chen, N. Liu, H. Huang, Z. Zheng, and Q. Yan, "A blockchain-based decentralized federated learning framework with committee consensus," in *IEEE Network*, vol. 35, no. 1, 2021, pp. 234–241.
[13] X. Zuo, M. Wang, T. Zhu, L. Zhang, S. Yu, and W. Zhou, "Federated learning with blockchain-enhanced machine unlearning: A trustworthy approach," *arXiv preprint arXiv:2405.20776*, 2024.
[14] J. Hayes, I. Shumailov, E. Triantafillou, A. Khalifa, and N. Papernot, "Inexact unlearning needs more careful evaluations to avoid a false sense of privacy," *arXiv preprint arXiv:2403.01218*, 2024.
[15] I. U. Ajakwe, V. I. Kanu, S. O. Ajakwe, and D.-S. Kim, "ebctc: Energy-efficient hybrid blockchain architecture for smart and secured k-ets," *Cleaner Engineering and Technology*, p. 101084, 2025.
[16] B. Hilprecht, M. Härterich, and D. Bernau, "Monte carlo and reconstruction membership inference attacks against generative models," in *Proc. on Privacy Enhancing Technologies*, vol. 2019, no. 4, 2019, pp. 232–249.