ENR 1 一般規則および方式

ENR 1.1 一般規則

1. 総則

我が国の航空規則及び航空交通業務方式は一部の相違を除き下記の国際民間航空機関等の文書の方式に従うものである。

１） 国際民間航空条約第２付属書－航空規則

２） 同第１１付属書－航空交通業務

３） 航空業務方式（文書番号 Doc 4444）
航空交通管理

４） 航空業務方式（文書番号 Doc 8168）
航空機の運航

５） 地区補則手続き（文書番号　Doc 7030）

６） 米連邦航空局便覧－標準計器進入方式基準

2. 計器飛行証明

事業用操縦士又は自家用操縦士の資格についての技能証明を有する者は、その使用する航空機の種類に係る下記の飛行の技能について国土交通の行う計器飛行証明を受けていなければ、下記の飛行を行ってはならない。

ａ） 計器飛行

ｂ） 計器飛行以外の航空機の位置及び針路の測定を計器にのみ依存して行う飛行（「計器航法による飛行」という。）で 110 ㎞又は 30 分のいずれかをこえて行うもの
（例　洋上又は雲上の ＶＦＲ 飛行）

ｃ） 計器飛行方式による飛行

3. 酒精飲料等

3.1 航空機乗組員は、酒精飲料又は麻酔剤その他の薬品の影響により航空機の正常な運航ができないおそれがある間は、その航空業務を行ってはならない。

3.2 次のいずれかに掲げる場合に該当する航空機乗組員は、酒精飲料の影響によって航空機の正常な運航ができないおそれがあるため、航空業務を行わないこと。

a) 身体に血液 1 リットルにつき 0.2 グラム以上又は呼気 1 リットルにつき 0.09 ミリグラム以上のアルコール濃度を保有している場合

b) a) にかかわらず、酒精飲料の影響により、反応速度の遅延など航空機の正常な運航ができないおそれがあると認められる場合

4. 操縦者の見張り義務

航空機の操縦を行っている者は、航空機の航行中は、管制機関の指示に従った航行であるとないとにかかわらず、当該航空機以外の物件を視認できない気象状態の下にある場合を除き、航空機その他の物件と衝突しないように見張りしなければならない。

ENR 1 GENERAL RULES AND PROCEDURES

ENR 1.1 GENERAL RULES

1. General

The Rules of the Air, Air Traffic Service Procedures and Aircraft Operations Procedures adopted in Japan are in conformity with the provisions of the following ICAO and other documents except some parts of difference:-

1) Annex 2 to the Convention on International Civil Aviation -Rules of the Air.
2) Annex 11 to the Convention on International Civil Aviation -Air Traffic Services.
3) Procedures for Air Navigation Services (Doc 4444) -Air Traffic Management.
4) Procedures for Air Navigation Services (Doc 8168) -Aircraft Operations.
5) Regional Supplementary Procedures(Doc 7030)
6) US Manual of Criteria for Standard Instrument Approach Procedures(FAA).

2. Instrument Rating

No person who is the holder of a commercial pilot license or a private pilot license shall conduct the following flights, unless he has received an instrument rating issued by the Minister of Land, Infrastructure, Transport and Tourism appropriate to the aircraft category entered on the holder's license.

a) Instrument flight
b) Flight other than instrument flight in which aircraft position and track are measured depending on the cockpit instruments only, and duration of the flight is more than 110km or 30 minutes whichever is less (This flight is called" instrument navigation flight" -e.g., VFR flight over water or top of clouds.)
c) IFR flight

3. Alcohol beverage, etc.

3.1 No member of the aircrew shall engage in air navigation services while he/she is under the influence of alcohol beverage, drugs or other chemical agents which are likely to impair in anyway his/her ability to perform normal operations of aircraft.

3.2 No member of the aircrew who meets the requirements as follows shall engage in air navigation services because he/she is under the influence of alcohol which are likely to impair in anyway his/her ability to perform normal operations of aircraft.

a) When having blood alcohol concentration of 0.2 g or more per liter or breath alcohol concentration of 0.09 mg or more per liter.

b) Regardless of the criteria of a) , due to the influence of alcohol, while aircrew is unable to normally perform operation of aircraft, such as slow response.

4. Pilot's Vigilance for Avoidance of Collisions

When weather conditions permit, vigilance shall be maintained by each person operating an aircraft in order to see and avoid potential collisions with other aircraft or objects, regardless of whether an operation is conducted under ATC clearance or not.

5. 異常接近報告

機長は、飛行中他の航空機との衝突又は接触のおそれがあったと認められたときは、ENR1.14.3.2 項「異常接近に関する機長報告要領」に従い、発生時の概要を無線で最寄りの交通業務機関に通報し、当該飛行の終了後、速やかに異常接近報告を航空局安全部航空安全推進室長に提出しなければならない。

5. Near Collision Report

A pilot-in-command shall, when he has deemed that his aircraft was involved in danger of collision with any other aircraft during his operation, notify the nearest ATS units of the outline of an incident by radio and submit a "Near Collision Report" to the Director for Air Transport Safety Unit of Civil Aviation Bureau as promptly as practicable upon landing in compliance with the attached "Procedures for Reporting Near Collision by Pilot-in-Command."(See ENR 1.14.3.2)

6. 巡航高度

航空機は、地表又は水面から 900m（3,000ft）〔計器飛行方式の場合は 300m（1,000ft）〕以上の高度で巡航する場合は、下表に定められた巡航高度又は管制機関の指示した高度で飛行しなければならない。

6. Cruising Altitude

When operating above 900m(3,000ft) above ground or water in VFR or above 300m(1,000ft) above ground or water in IFR, and aircraft cruising shall be conducted at an altitude or a flight level appropriate to the track specified in the following table, except otherwise specified by ATC.

飛行方向	From 000° to 179°		From 180° to 359°	
飛行方式	IFR Flights	VFR Flights	IFR Flights	VFR Flights
14,000ft 未満の高度	1,000ft の奇数倍の高度	1,000ft の奇数倍に 500ft を加えた高度	1,000ft の偶数倍の高度	1,000ft の偶数倍に 500ft を加えた高度
ﾌﾗｲﾄﾚﾍﾞﾙ 140 以上 ﾌﾗｲﾄﾚﾍﾞﾙ 290 未満	1,000ft の奇数倍の ﾌﾗｲﾄﾚﾍﾞﾙ	1,000ft の奇数倍に 500ft を加えたﾌﾗｲﾄﾚﾍﾞﾙ	1,000ft の偶数倍の ﾌﾗｲﾄﾚﾍﾞﾙ	1,000ft の偶数倍に 500ft を加えたﾌﾗｲﾄﾚﾍﾞﾙ
『RVSM 許可機のみに適用』 ﾌﾗｲﾄﾚﾍﾞﾙ 290 以上 ﾌﾗｲﾄﾚﾍﾞﾙ 410 以下	1,000ft の奇数倍の ﾌﾗｲﾄﾚﾍﾞﾙ	----	1,000ft の偶数倍の ﾌﾗｲﾄﾚﾍﾞﾙ	----
ﾌﾗｲﾄﾚﾍﾞﾙ 410 超	ﾌﾗｲﾄﾚﾍﾞﾙ 450 に 4,000ft の倍数を加えた ﾌﾗｲﾄﾚﾍﾞﾙ	----	ﾌﾗｲﾄﾚﾍﾞﾙ 430 に 4,000ft の倍数を加えた ﾌﾗｲﾄﾚﾍﾞﾙ	----

Track	From 000°to 179°		From 180°to 359°	
Flight rule	IFR Flights	VFR Flights	IFR Flights	VFR Flights
Below 14,000ft MSL	Any odd thousand foot altitude	Any odd thousand foot altitude plus 500ft	Any even thousand foot altitude	Any even thousand foot altitude plus 500ft
At or above FL140 but below FL290	Any odd thousand foot flight level	Any odd thousand foot flight level plus 500ft	Any even thousand foot flight level	Any even thousand foot flight level plus 500ft
"Only applied to RVSM approved Aircraft" At or above FL290 but at or below FL410	Any odd thousand foot flight level	----	Any even thousand foot flight level	----
Above FL410	Any flight level at 4,000ft intervals beginning at and including FL450	----	Any flight level at 4,000ft intervals beginning at and including FL430	----

7. 高度変更禁止空域

航空機は、航空交通がふくそうする空域として国土交通大臣が告示で指定する空域を有視界飛行方式で飛行する場合は、その巡航高度を変更してはならない。ただし下記の場合はこの限りでない。

a） 悪天候を避けるために必要な場合
b） その他やむを得ない事由がある場合

7. Prohibition of Changing VFR Cruising Altitude

An aircraft shall not change its cruising altitude when operating under VFR within a congested airspace designated by the Minister of Land, Infrastructure, Transport and Tourism, except that changing altitude is necessary-

a) to avoid bad weather conditions, or
b) due to unavoidable circumstances.

8. 速度制限

航空機は、下記の空域においては、指示対気速度 250 ノットを越える速度で飛行してはならない。

a）管制圏

b）進入管制区のうち高度 3,050m（10,000ft）未満の空域

上記の規定にかかわらず、管制機関より上記の速度を超える速度で飛行することを指示された場合及び航行の安全上やむを得ないと認められる事由により上記の速度を越えた速度で飛行する必要のある場合は、当該速度で飛行することができる。ただし、上記規定にかかわらず国土交通大臣の許可を受けた場合はこの限りでない。

8. Aircraft Speed Limitation

Any aircraft shall not be operated at an indicated airspeed of more than 250knots,

a) Within control zone

b) Below 3,050m (10,000ft) above mean sea level within approach control area.

However if aircraft is instructed by ATC to be operated at a greater airspeed than the maximum airspeed prescribed above, the aircraft may be operated at that airspeed, or the minimum safe airspeed to ensure safe operation is greater than the maximum airspeed prescribed above, the aircraft may be operated at that minimum safe airspeed. Above provisions may not be applied if a permission is obtained from the Minister of Land, Infrastructure, Transport and Tourism.

9. 曲技飛行及び航空機の試験をする飛行

航空機は、下記の場合は曲技飛行又は航空機の試験をする飛行を行ってはならない。ただし国土交通大臣の許可を受けた場合はこの限りでない。

a） 人又は家屋の密集している地域の上空
b） 管制区又は管制圏内
c） 当該航空機を中心として半径 500m（1,700ft）以内の最も高い障害物の上端から 500m（1,700ft）未満の高度
d） 高度 3,000m（10,000ft）以上の空域で飛行視程が 8km（5 マイル）未満

9. Acrobatic Flight and Aircraft Test Flight

Unless otherwise authorized by the Minister of Land, Infrastructure, Transport and Tourism, an aircraft shall not be operated in acrobatic flight or aircraft test flight-

a) Over congested area with persons or houses;
b) Within a control area or a control zone;
c) Below an altitude of 500m(1,700ft) above the highest obstacle within 500m(1,700ft) of aircraft;
d) When flight visibility is less than 8km(5 statute miles) within airspace at or above 3,000m(10,000ft) above mean sea level;

10. 超音速飛行

航空機は、下記の場合は超音速飛行を行ってはならない。ただし国土交通大臣の許可を受けた場合はこの限りでない。

a） 人又は家屋の密集している地域の上空
b） 管制区又は管制圏内
c） 衝撃波が地上又は水上の人又は物件に危害を与え、又は損傷を及ぼすおそれのある高度
d） 飛行視程が 10 ㎞未満

10. Flight at Supersonic Speed

Unless otherwise authorized by the Minister of Land, Infrastructure, Transport and Tourism, an aircraft shall not be operated at supersonic speed-

a) Over a congested area of persons or houses;
b) Within a control area or a control zone;
c) At any altitude that will cause public nuisance or damages to persons or properties on the ground or on the sea by sonic boon; or
d) When flight visibility is less than 10km.

11. 操縦練習飛行

航空機は、管制区又は管制圏においては、下記の飛行を行なってはならない。ただし国土交通大臣の許可を受けた場合はこの限りでない。

a） 操縦技能証明を受けていない者が航空機に乗り組んで操縦の練習をする飛行
b） 操縦技能証明を有する者が当該操縦技能証明について限定された範囲の航空機以外の航空機に乗り組んで操縦の練習をする飛行

11. Training Flight for Student Pilot

Unless otherwise authorized by the Minister of Land,Infrastructure, Transport and Tourism, the following flights shall not be conducted within a control area or a control zone.

a) Training flight for pilotage conducted by a person who is not the holder of a certificate, or
b) Training flight for pilotage of any kind of aircraft other than the aircraft for which a person has a license of restricted privileges.

12. 航空交通の安全を阻害するおそれのある飛行

航空機は、管制区又は管制圏においては、下記の航空交通の安全を阻害するおそれのある飛行を行なってはならない。ただし国土交通大臣の許可を受けた場合はこの限りでない。

a） 航空機の姿勢をひんぱんに変更する飛行
b） 失速を伴う飛行
c） 航空機の高度を急激に変更する飛行

12. Prohibition of Hazardous Operation to the Safety of Air Traffic

Unless otherwise authorized by the Minister of Land, Infrastructure, Transport and Tourism, the following flight shall not be conducted within a control area or a control zone.

a) Flight including frequent change of aircraft attitude, or
b) Flight including stall, or
c) Flight including abrupt changes of aircraft altitude.

13. 計器飛行及び計器航法による飛行

航空機は、地上物標を利用して、その位置及び針路を知ることができるときは、計器飛行又は計器航法による飛行を行なってはならない。

13. Instrument Flight and Instrument Navigation Flight

Any aircraft shall not be operated under instrument flight or instrument navigation flight, when its position and track can be determined by recognition of ground references.

14. 計器気象状態における飛行

14.1. 航空機は、計器気象状態においては、管制区、管制圏又は情報圏にあっては計器飛行方式により飛行しなければならず、他の空域にあっては飛行してはならない。ただし、予測できない急激な天候の悪化、その他やむを得ない事由がある場合又は管制機関の許可を受けた場合はこの限りでない。

14.2. 前項ただし書の規定により管制機関の許可を受けて管制圏（特別管制空域を除く）又は情報圏内を飛行する場合（特別有視界飛行）は次の基準により飛行しなければならない。

a) 雲から離れて飛行すること。
b) 飛行視程を 1500 m 以上に維持して飛行すること。
c) 地表又は水面を引き続き視認できる状態で飛行すること。
d) 情報圏を飛行する場合は、飛行場対空援助業務実施機関を経由して、管制機関と連絡を保つこと。

15. 特別管制空域における飛行

15.1. 航空機は、特別管制空域においては計器飛行方式により飛行しなければならない。ただし、管制機関の許可を受けた場合は、この限りではない。

15.2. ただし書の規定により管制機関の許可を受けた場合は、次の基準に従って飛行しなければならない。

a) 有視界気象状態を維持して飛行すること。
b) 当該空域の管制業務を行う機関と常時連絡を保つこと。

16. 管制圏における飛行

航空機は、管制圏内においては、管制圏内にある飛行場からの離陸及びこれに引き続く飛行、並びに着陸及びその着陸のための飛行以外の飛行を行ってはならない。
ただし管制機関の許可を受けた場合はこの限りではない。

14. Flight in IMC

14.1 When weather is IMC, an aircraft shall be operated under IFR within a control area, a control zone or an information zone, and shall not be operated outside a control area and a control zone, except in the case of unavoidable circumstances including unexpected deterioration of weather or otherwise authorized by ATC.

14.2 When an aircraft is authorized to be operated in IMC under special VFR in a control zone (except in a Positive Controlled Airspace) or an information zone in accordance with the exception clause of above paragraph, the following condition shall be observed.

a) Keep clear of clouds
b) Maintaining flight visibility of at least 1500m
c) Continuously in sight of ground or water
d) Maintaining contact with ATC, through AFIS Units, while in an information zone.

15. Flight within Positive Controlled Airspace

15.1 Unless otherwise authorized by ATC, an aircraft shall be operated within a positive controlled airspace under IFR.

15.2 When an aircraft is authorized to be operated within a positive controlled airspace in accordance with the exception clause of above paragraph, the following condition shall be observed.

a) Maintaining VMC
b) Maintaining contact with the ATC unit responsible to the area.

16. Operations within a Control Zone

Unless otherwise authorized by ATC, any aircraft shall not be operated within a control zone except for the purpose of taking off from or landing at an aerodrome within a control zone.

17. 飛行に影響を及ぼすおそれのある行為

17.1 何人も、管制圏、情報圏、高度変更禁止空域又は特別管制空域においては下記の行為を行ってはならない。ただし国土交通大臣の許可を受けた場合はこの限りではない。

a) ロケット、花火、ロックーン等を打上げること。(捜索、救助その他の緊急性がある場合におけるものを除く。)
b) 気球を放し、又は浮揚させること。(玩具用のもの及びこれに類するものを除く。)
c) 凧を揚げること。
d) 模型航空機を飛行させること。
e) 可視光線であるレーザー光を航空機に向かって照射すること。
f) 航空機の集団飛行を行うこと。
g) ハンググライダー又はパラグライダーの飛行を行うこと。

ただし、管制圏又は情報圏での行為については、下記の空域に限る。

i) 進入表面、転移表面、水平表面、延長進入表面、円錐表面若しくは外側水平表面の上空の空域、又は国土交通大臣が告示で定める空域

ii) 緊急用務空域(捜索、救助その他の緊急用務を行う航空機の飛行の安全を確保する必要があるものとして国土交通大臣が指定する空域)

iii) i) 及び ii) 以外の空域で地表又は水面から 150m 以上の高さの空域

17.2 前記の空域以外の下記の空域において、前記の行為(17.1 e)を除く。)を行うとする者はあらかじめ氏名、住所、連絡場所、内容、日時及び場所を国土交通大臣に通報しなければならない。
ただし、ハンググライダー又はパラグライダーの飛行については、下記 i) 及び ii) の空域に限る。

i) 進入表面、転移表面、水平表面、延長進入表面、円錐表面若しくは外側水平表面の上空の空域、又は国土交通大臣が告示で定める空域

ii) 緊急用務空域
iii) 航空路内の地表又は水面から 150 m 以上の高さの空域

iv) 地表又は水面から 250 m 以上の高さの空域

18. 通信機故障の場合の飛行方法

管制区、管制圏又は情報圏を飛行中に通信機の故障があった場合の飛行方法は、管制官から特に指示がある場合を除き、下記によることとする。

18.1 最寄りの管制機関又は対空援助業務実施機関と通信設定を行う。

18.2 前項の通信設定ができなかった場合
(1) 有視界気象状態にある場合((2) に掲げる場合を除く。)は、有視界気象状態を維持して飛行を継続し、安全に着陸できると思われる最寄りの飛行場に着陸し、かつ、その旨直ちに管制機関に対し到着を通報する。

17. Prohibition and Notice Requirement of Operations that Create Collision Hazards to Other Aircraft

17.1 Unless otherwise authorized by the Minister of Land, Infrastructure, Transport and Tourism, no person shall conduct the following operations within a control zone, an information zone, an altitude change prohibited airspace or a positive controlled airspace.

a) To launch rockets, fireworks, rockoons, etc. (except for search and rescue, and other emergency.)
b) To release or fly a balloon. (except a toy balloon or one of similar construction.)
c) To fly a kite.
d) To fly a model aircraft.
e) To aim a laser beam of the visible ray at an aircraft.

f) To conduct a mass flight of aircraft.
g) To operate of a hang-glider or a para-glider.

But concerning the operations within a control zone, an information zone is limited to an airspace in the provisions of i) and ii) listed below.
i) An airspace above an approach surface, a transitional surface, a horizontal surface, an extended approach surface, a conical surface or an outer horizontal surface, or an airspace prescribed by public notice of the Minister of Land, Infrastructure, Transport and Tourism; or
ii) Airspace for aircraft conducting emergency missions (Airspace designated by the Minister of Land, Infrastructure, Transport and Tourism as necessary to ensure the safety of flight of aircraft performing search and rescue, and other emergency missions); or
iii) An airspace above 150m from the ground or water surface other than i) and ii).

17.2 Any person who intends to conduct the operations listed above (except for item 17.1 e)), within the following airspace other than airspace prescribed above, shall notify the Minister of Land, Infrastructure, Transport and Tourism of his name, address, the purpose, date, time and other details in well advance of beginning the operation. But concerning the operation of a hang-glider or a para-glider is limited to an airspace in the provisions of i) and ii) listed below.
i) An airspace above an approach surface, a transitional surface, a horizontal surface, an extended approach surface, a conical surface or an outer horizontal surface, or an airspace prescribed by public notice of the Minister of Land, Infrastructure, Transport and Tourism; or
ii) Airspace for aircraft conducting emergency missions; or
iii) An airspace above 150m from the ground or water surface within an airway; or
iv) An airspace above 250m from the ground or water surface.

18. Pilot Procedures for communication failure

Pilot procedures for communication failure while operating within a control area, a control zone or an information zone shall be as follows, unless otherwise instructed by ATC.

18.1 Attempt shall be made to establish communications with the appropriate air traffic control unit or Aeronautical Mobile Communication and Information Service Unit.

18.2 If this attempt fails,
(1) If in visual meteorological conditions (except in case of (2) below), the aircraft shall continue to fly in visual meteorological conditions and land at the nearest aerodrome where a safe landing is considered possible, then report its arrival to the appropriate air traffic control unit expeditiously.

(2) (1) によることが困難と判断した場合（計器飛行方式により飛行する場合に限る。)、又は計器気象状態の場合は、次のとおりとする。

a) 承認された経路に従って、目的地上空（目的飛行場の上空又は計器進入方式の開始点として特定の航空保安無線施設若しくはフィックスがある場合はその上空）まで飛行する。ただし、レーダー誘導又はオフセットの指示を受けていた場合は、次のいずれかの地点に直行し、承認された経路に戻る。この際、制限空域の中に入らないこと。

i) レーダー誘導又はオフセット開始の際、誘導目標又はオフセットを終了する地点としてフィックスが指示された場合は、当該フィックス

ii) レーダー誘導開始の際、誘導目標として航空路又は経路等が指示された場合は、当該経路にある目的地に向かって最寄りのフィックス

iii) 誘導目標又はオフセットの終了地点の通報がない場合は、レーダー誘導又はオフセット開始前において最後に承認された経路にある目的地に向かって最寄りのフィックス

b) 承認されていた高度若しくは最低高度（最低経路高度、最低通過高度、最低受信可能高度、高度制限による高度を指す。）のいずれか高い高度及び指示されていた速度を維持して、以下の時間まで飛行し、その後通報した飛行計画による高度及び速度を維持して飛行する。ただし、通信機故障の前に、着陸のための降下の指示をされている場合は、当該指示による高度を維持して飛行する。

i) レーダー管制業務が行われていない空域では、義務位置通報点における通報ができなかった時点から２０分間

ii) レーダー管制業務が行われている空域では、次の時間のうち最も遅い時間から７分間

・承認されていた高度若しくは最低高度に到達した時間

・トランスポンダーを 7600 にセットした時間

c) a) 及び b) により目的地上空に到着したときは、既に進入許可が発出されている場合は速やかに、その他の場合は次の時刻まで当該地点の上空で待機した後、降下を開始する。（当該時刻に降下を開始することができなかった場合は、できるだけすみやかに降下を開始する。）

i) 進入開始予定時刻を受領している場合は、その時刻

ii) 進入開始予定時刻を受領していない場合であって、通信機の故障以前に管制機関に対し目的地上空の到着予定時刻を通報しているときは、その時刻

iii) i) 及び ii) 以外の場合は、離陸時刻から飛行計画の第 16 項に記載した所要時間が経過した時刻

d) 通信機が故障する以前に目的地上空に到着し、かつ、当該地点で待機する指示が発出されているときは、次の時刻まで当該地点の上空で待機した後、降下を開始する。（当該時刻に降下を開始することができなかった場合は、できるだけすみやかに降下を開始する。）

i) 進入開始予定時刻を受領している場合は、その時刻

ii) 進入予定時刻を受領していない場合であって、次の指示が与えられる時刻を受領しているときはその時刻

iii) i) 及び ii) 以外の場合は、離陸時刻から飛行計画の第 16 項に記載した所要時間が経過した時刻

(2) If pilot of an IFR flight considers it inadvisable to complete the flight in accordance with (1) above or in instrument meteorological conditions,
the aircraft shall:

a) proceed according to the last assigned route to the point over destination (the airspace right above the destination aerodrome or the appropriate designated navigation aid or fix where an instrument approach will be commenced, if any). However, when being radar vectored or having been directed by ATC to proceed offset, the aircraft shall proceed to:

i) the navigation aid or fix informed as a limit of vector or offset ; or

ii) the nearest navigation aid or fix towards the destination on the airway or route informed as a limit of vector; or

iii) the nearest navigation aid or fix towards the destination on the last cleared route when a limit of vector or offset has not been informed;

then rejoin the last cleared route.

While proceeding to the navigation aid or fix mentioned above, aircraft should avoid restricted/warning areas.

b) maintain the last assigned altitude or minimum altitude (minimum enroute altitude, minimum crossing altitude, minimum reception altitude or altitude restriction) whichever is higher and the last assigned speed for a following period and thereafter adjust altitude and speed in accordance with the filed flight plan;

i) in airspace where radar is not used in the provision of air traffic control, for a period of 20 minutes following the aircraft's failure to report its position over a compulsory reporting point.

ii) in airspace where radar is used in the provision of air traffic control, for a period of 7 minutes following:

- the time the last assigned altitude or minimum altitude is reached; or
- the time the transponder is set to Code 7600 whichever is later.

In a case the aircraft has been issued a descend clearance for approach before the communication failure, maintain the altitude included that clearance.

c) upon arrival at the point over destination in accordance with a) and b) above, commence descent without delay if approach clearance has been issued or commence descent in other cases after holding over the point until the time specified below.
(or commence descent as soon as possible, when descent was impossible at the time.)

i) the expected approach time (EAT), if EAT has been received; or

ii) the estimated time of arrival (ETA), if no EAT has been received but the aircraft has reported to ATC regarding its ETA at the point; or

iii) the time which the total estimated elapsed time (the time inserted to field 16 of flight plan) has elapsed after take-off in cases other than i) and ii) above

d) In a case the aircraft has arrived at the point over destination before the communication failure and an instruction has been issued to hold at the point, commence descent after holding over the point until the time specified below. (or commence descent as soon as possible, when descent was impossible at the time.)

i) the expected approach time (EAT), if EAT has been received; or

ii) the expect further clearance time (EFC), in case where no EAT has been received but EFC has been received; or

iii) the time which the total estimated elapsed time (the time inserted to field 16 of flight plan) has elapsed after take-off in cases other than i) and ii) above

18.3 到着機がターミナル・レーダー及び着陸誘導管制業務によるレーダー誘導中に通信機故障が発生した場合は、第三部飛行場（AD）の通信途絶方式によること。

18.3 When being radar vectored by terminal radar approach control or ground controlled approach, pilot of an arrival aircraft shall comply with the lost communication procedures published in Part 3 Aerodromes (AD).

18.4 飛行場管制の管制下にある場合は、タワーからの指向信号灯による指示にも注意すること。

18.4 Pilot shall keep a watch for such instructions as may be issued by visual signals when forming part of the aerodrome traffic.

19. 不測の事態における一時的な措置

不測の事態において、計器飛行方式又は特別有視界飛行方式により飛行する航空機間に所定の管制間隔が設定できなくなった場合には、所定の管制間隔が再度設定されるまでの間、最低垂直間隔の２分の１の間隔が緊急的に適用されることがあり、この場合は交通情報と併せてその旨が通知される。

Example:
500ft emergency separation applied.〔Traffic information〕

19. Contingency procedure in emergency situation

In case of some contingencies, when it is not possible to ensure the applicable separation between IFR / Special VFR flights, emergency separation of half the applicable vertical separation minimum may be temporarily applied until the applicable separation is ensured. Additionally, all pilots concerned shall be advised that emergency separation is being applied with the relevant traffic information.

Example:
500ft emergency separation applied.[Traffic information]

20. 位置通報

20.1 総則

20.1.1 適用

計器飛行方式及び有視界飛行方式により福岡 FIR 内を飛行する航空機は、すべて定められた地点及び要求された地点において、所定の方法により位置通報を行なわなければならない。

ただし、管制機関により「レーダーコンタクト RADAR CONTACT」を通報されたのちは「レーダーコンタクト・ロスト RADAR CONTACT LOST」又は「レーダー業務を終了します RADAR SERVICE TERMINATED」の通報があるまで、特に指示がない限り位置通報を行なわないことができる。

20.1.2 位置通報は航空機が位置通報点上若しくは線上又は通過直後に行なわなければならない。

20.1.3 位置通報点の訂正

前回位置通報中、予定通過時刻等の内容変更が必要となったときは遅滞なく訂正の通報を行わなければならない。この場合、時間の訂正を要する範囲は、3 分を超える場合とする。

20.2 位置通報方式

20.2.1 洋上を飛行する場合

洋上管制区を飛行する航空機は次の方法によるものとする。

20.2.1.1 標準方式ー位置通報点が特に指定されていない洋上管制区にあって航空機は出発後 30 分及びその後 1 時間の間隔で位置通報を行なわなければならない。ただし、20.2.1.2 による場合はこの限りでない。

20.2.1.2 地区補則方式

20.2.1.2.1 飛行方向が主に東又は西向きの場合、経度 10 度を 1 時間20分以内で通過する対地速度で飛行する航空機については180度子午線から東西に 10 度ごと、それよりも遅い対地速度で飛行する航空機については 180 度子午線から東西に 5 度ごとの経線上で位置通報を行う。

20.2.1.2.2 飛行方向が主に北又は南向きの場合、緯度 10 度を 1 時間 20 分以内で通過する対地速度で飛行する航空機については赤道から南北に 10 度ごと、それよりも遅い対地速度で飛行する航空機については赤道から南北に5度ごとの緯線上で位置通報を行う。

20.2.1.2.3 低速度の航空機については 20.2.1.2.1 及び 20.2.1.2.2 に定めるよりも短い間隔（2 度 30 分毎の経線又は緯線上）で位置通報を要求することがある。

20. Position reporting

20.1 General

20.1.1 Application

All aircraft on IFR and VFR flight within Fukuoka FIR shall make a position report, by the specified manner, of passing each designated reporting point and of passing "on request" reporting point or when so requested on the route to be flown.

However, when informed by ATC that an aircraft is in "RADAR CONTACT", the pilot should discontinue his position report, unless specifically requested otherwise, until he is advised by ATC that "RADAR CONTACT LOST" or "RADAR SERVICE TERMINATED".

20.1.2 These position reports should be made when over or as soon as possible after the aircraft has passed the reporting point or line.

20.1.3 Revision of Position Report

The position report shall be amended without delay if original report is found to be revised (If the original estimated time needs correction by an error in excess of 3 minutes).

20.2 Position Reporting Procedures

20.2.1 For Oceanic Flights

The following procedures shall be observed by aircraft flying within Oceanic control airspace.

20.2.1.1 Standard Procedure-On routes not defined by specified reporting points such as in Oceanic Control Area aircraft shall report position as soon as practicable after the first half hour of flight and at hourly intervals thereafter except when 20.2.1.2 is complied with.

20.2.1.2 Regional Supplementary Procedures

20.2.1.2.1 Flights whose tracks are predominantly East or West shall report over each 5° or 10° (10° will be used if the ground speed of aircraft is such that 10° will be traversed in 1 hour and 20 minutes or less) meridian of longitude extending East and West of 180°

20.2.1.2.2 Flights whose tracks are predominantly North or South shall report over each 5° or 10° (10° will be used if the ground speed of aircraft is such that 10° will be traversed in 1 hour and 20 minutes or less) parallel of latitude extending North and South of the Equator.

20.2.1.2.3 Air traffic services may require specific flights to report frequently than each 5° fix as in 20.2.1.2.1 and 20.2.1.2.2 (each 2° 30') for aircraft with slower ground speeds.

20.2.1.3 ENR3.1、ENR3.5.2 及び下表に示す義務位置通報点を通過する場合並びに管制機関等から要求があった場合、20.2.1.1 及び 20.2.1.2 の方法によらず義務位置通報点及び要求のあった地点で位置通報を行う。

名称	位置	略号又は識別符号
AKISU	*473302.61N/1612000.00E*	–
CUTEE	*462454.00N/1621836.00E*	–
AGEDI	*441000.00N/1550548.06E*	–
KALIG	*425853.89N/1554008.40E*	–

20.2.1.3 Position report shall be made over a compulsory reporting point shown in ENR3.1, ENR3.5.2 and the following table, regardless of 20.2.1.1 and 20.2.1.2. Addiational reports over other points may be requested by the appropriate ATS unit.

DESIGNATION	COORDINATES	ABBEV.or ID
AKISU	*473302.61N/1612000.00E*	-
CUTEE	*462454.00N/1621836.00E*	-
AGEDI	*441000.00N/1550548.06E*	-
KALIG	*425853.89N/1554008.40E*	-

20.2.2 日本国内を飛行する場合

航空交通管制区内を飛行する航空機は次の方法によるものとする。

20.2.2.1 計器飛行方式により飛行する航空機については、ENR3.1、ENR3.5.2 及び下表に示す義務位置通報点並びに管制機関等から要求のあった地点で位置通報を行う。

名称	位置	略号又は識別符号
千歳タカン	*424552.00N/1414025.00E*	ZYT
大子タカン	*364441.47N/1402058.42E*	GOT
美保タカン	*353151.77N/1330538.72E*	JET
御宿タカン	*351102.89N/1402217.14E*	OJT
河和タカン	*344216.54N/1365726.73E*	XMT
岩国タカン	*340930.27N/1321443.81E*	NEU
玖珂タカン	*340447.64N/1320850.31E*	IWT
奄美タカン	*282636.50N/1293500.24E*	ALT
知念タカン	*260938.40N/1274803.92E*	TIT

20.2.2.2 有視界飛行方式により飛行する航空機については、管制機関等から指示があった場合、位置等について通報しなければならない。

20.2.3 通報の名あて

位置通報は当該空域を管轄する管制機関等に対し直接、又は最寄りの管制機関等を通じて行うものとする。

ただし、FIR 境界線上の義務位置通報点において、福岡 FIR を出域して隣接 FIR に入域する場合の位置通報は、入域先の FIR を管轄する管制機関等に対して行うこと。

20.3 位置通報の内容

20.3.1 洋上を飛行し、国際運航を行う航空機は ICAO AIREP 第 1 部の様式を適用し通報しなければならない。

1) 航空機識別符号
2) 現在位置ー 20.2.1.1 及び 20.2.1.2 の方法による場合には飛行方向にかかわらず緯度、経度共に度及び分まで。
3) 通過時刻
4) フライトレベル、又は高度
5) 次の予定通過位置及び予定時刻
6) 5) に引き続く次の予定通過位置

20.2.2 For Domestic Flights

The following procedures shall be observed by aircraft flying within Control Area.

20.2.2.1 Aircrafts flying under IFR shall report their position over a compulsory reporting point shown in ENR3.1, ENR3.5.2 and the following table. Addiational reports over other points may be requested by the appropriate ATS unit.

DESIGNATION	COORDINATES	ABBEV.or ID
CHITOSE TACAN	*424552.00N/1414025.00E*	ZYT
DAIGO TACAN	*364441.47N/1402058.42E*	GOT
MIHO TACAN	*353151.77N/1330538.72E*	JET
ONJUKU TACAN	*351102.89N/1402217.14E*	OJT
KOWA TACAN	*344216.54N/1365726.73E*	XMT
IWAKUNI TACAN	*340930.27N/1321443.81E*	NEU
KUGA TACAN	*340447.64N/1320850.31E*	IWT
AMAMI TACAN	*282636.50N/1293500.24E*	ALT
CHINEN TACAN	*260938.40N/1274803.92E*	TIT

20.2.2.2 Aircrafts flying under VFR shall report their position when requested by the appropriate ATS unit.

20.2.3 Addressing of Position Reports

The position report shall be addressed to the appropriate ATS unit serving the area, directly or through the nearest ATS unit for relay.

However, when leaving Fukuoka FIR and entering adjacent FIR, position reports at each compulsory reporting point on FIR boundaries shall be addressed to the ATS unit serving the airspace about to be entered.

20.3 Contents of Position Report

20.3.1 For oceanic flight on international routes position reports shall be made in compliance with Section 1 of the AIREP Form by ICAO:

1) Aircraft identification
2) Position- Which is expressed in degrees and minutes irrespective of direction on flights, if 20.2.1.1 and 20.2.1.2 are complied with.
3) Time of passing
4) Flight level or altitude
5) Next position and estimated time over
6) Ensuing significant point

20.3.1.1 位置通報以外の通報内容

20.3.1.1.1 運航通報－ AIREP 様式第 2 部に属する全項目、又は部分について関係機関から要求のある場合には次の項目を通報する。

1) 予定到着時刻
2) 燃料保有量

20.3.1.1.2 気象通報－ AIREP 様式第 3 部に属する全項目、又は一部に関し、20.2.1 に規定した位置通報点上についての、下記の全項目又は一部を通報しなければならない。

1) 並以上の乱気流
2) 並以上の着氷
3) 強い山岳波
4) 活発な雷電
5) 強い砂じん嵐
6) 火山灰雲
7) 火山活動
8) その他参考となる事項

20.3.2 前項 20.3.1 以外の飛行の場合（国内飛行）

1) 航空機識別符号
2) 位置通報点名、又はそれに準ずる名称
3) 通過時刻
4) 高度（フィート）、又はフライトレベル
5) 次の位置通報点名及び予定通過時刻
6) その他参考となる事項

20.3.1.1 Additional Contents of the Report

20.3.1.1.1 Operating information-Section 2 of AIREP, or a portion thereof shall be added only when specified by the appropriate ATS unit, aircraft operator, etc.

1) Estimated time of arrival
2) Endurance

20.3.1.1.2 Meteorological information-Section 3 of AIREP, or a portion thereof as appropriate shall be reported based on observations made at such positions as are specified in 20.2.1.

1) Moderate or severe turbulence
2) Moderate or severe icing
3) Severe mountainwave
4) Thunderstorms
5) Heavy dust/sandstorm
6) Volcanic ash cloud
7) Pre-eruption volcanic activity or volcanic eruption
8) Remarks

20.3.2 For flights other than 20.3.1 (Domestic Flights)

1) Aircraft identification
2) Name of reporting point or position
3) Time of passing
4) Altitude in feet or flight level
5) Next position and estimated time over
6) Other referential matter to air traffic

INTENTIONALLY LEFT BLANK