

Curso Data Science



Prof Me Eng Marcelo Bianchi
Data Scientist | Data Engineer | Data Architect



Aula 9 – SVR: Support Vector Regression

Machine Learning

SVR – Support Vector Regression


Support Vector Regression - SVR

- Support Vector Machines support linear and nonlinear regression that we can refer to as SVR
- Instead of trying to fit the largest possible street between two classes while limiting margin violations, SVR tries to fit as many instances as possible on the street while limiting margin violations.
- The width of the street is controlled by a hyper parameter Epsilon.

Support Vector Regression - SVR

- SVR performs linear regression in a higher (dimensional space).
- We can think of SVR as if each data point in the training represents its own dimension. When you evaluate your kernel between a test point and a point in the training set the resulting value gives you the coordinate of your test point in that dimension.
- The vector we get when we evaluate the test point for all points in the training set, \vec{k} is the representation of the test point in the higher dimensional space.
- Once you have that vector you use it to perform a linear regression.

Support Vector Regression - SVR



https://link.springer.com/chapter/10.1007/978-1-4302-5990-9_4

Support Vector Regression - SVR

It requires a training set: $\mathcal{T} = \{\vec{X}, \vec{Y}\}$ which covers the domain of interest and is accompanied by solutions on that domain.

The work of the SVM is to approximate the function we used to generate the training set

$$F(\vec{X}) = \vec{Y}$$

Support Vector Regression - SVR

Building a SVR

1. Collect a training set $\tau = \{\vec{X}, \vec{Y}\}$
2. Choose a kernel and its parameters as well as any regularization needed.
3. Form the correlation matrix, \vec{K}
4. Train your machine, exactly or approximately, to get contraction coefficients $\vec{\alpha} = \{\alpha_i\}$
5. Use those coefficients, create your estimator $f(\vec{X}, \vec{\alpha}, x^*) = y^*$

Support Vector Regression - SVR

Next step is to choose a kernel

- Gaussian

Regularization

- Noise

Support Vector Regression - SVR

Correlation Matrix

$$K_{ij} = \exp \left(\sum_k \theta_k |x_k^i - x_k^j|^2 \right) + \epsilon \delta_{ij}$$

Support Vector Regression - SVR

The main part of the algorithm $\bar{K}\vec{\alpha} = \vec{y}$

\vec{y} is the vector of values corresponding to your training set,

\bar{K} is your correlation matrix

$\vec{\alpha}$ is a set of unknowns we need to solve for.


$$\vec{\alpha} = \bar{K}^{-1}\vec{y}$$

Support Vector Regression - SVR

- Once \vec{a} parameters known - form the estimator
- we use the coefficients we found during the optimization step and the kernel we started off with.
- To estimate the value y^* for a test point, \vec{x}^* - compute the correlation vector \vec{k} ,
- $y^* = \vec{a} \cdot \vec{k}$

$$k_i = \exp \left(\sum_k \theta_k |x_k^i - x_k^*|^2 \right)$$

Support Vector Regression



DataSet and Challenge

	A	B	C	D
1	Position	Level	Salary	
2	Business Analyst	1	45000	
3	Junior Consultant	2	50000	
4	Senior Consultant	3	60000	
5	Manager	4	80000	
6	Country Manager	5	110000	
7	Region Manager	6	150000	
8	Partner	7	200000	
9	Senior Partner	8	300000	
10	C-level	9	500000	
11	CEO	10	1000000	
12				

- Determine if the employee is telling the truth or not. We classified the employee like level 6.5 and we need to find out if the salary is 160.000 pounds per year ?

- # SVR

- # Importing the libraries
- import numpy as np
- import matplotlib.pyplot as plt
- import pandas as pd

- # Importing the dataset
- dataset = pd.read_csv('Position_Salaries.csv')
- X = dataset.iloc[:, 1:2].values
- X = X.reshape(-1, 1)
- y = dataset.iloc[:, 2].values
- y = y.reshape(-1, 1)

- # Splitting the dataset into the Training set and Test set
- """from sklearn.cross_validation import train_test_split
- X_train, X_test, y_train, y_test = train_test_split(X, y, test_size = 0.2, random_state = 0)"""

- # Feature Scaling
- from sklearn.preprocessing import StandardScaler
- sc_X = StandardScaler()

- `sc_y = StandardScaler()`
- `X = sc_X.fit_transform(X)`
- `y = sc_y.fit_transform(y)`


- `# Fitting SVR to the dataset`
- `from sklearn.svm import SVR`
- `regressor = SVR(kernel = 'rbf')`
- `regressor.fit(X, y)`

- `# Predicting a new result`
- `y_pred = regressor.predict([[6.5]])`
- `y_pred = sc_y.inverse_transform(y_pred)`

- `# Visualising the SVR results`
- `plt.scatter(X, y, color = 'red')`
- `plt.plot(X, regressor.predict(X), color = 'blue')`
- `plt.title('Truth or Bluff (SVR)')`
- `plt.xlabel('Position level')`
- `plt.ylabel('Salary')`
- `plt.show()`

- # Visualising the SVR results (for higher resolution and smoother curve)
- `X_grid = np.arange(min(X), max(X), 0.01)` # choice of 0.01 instead of 0.1 step because the data is feature scaled
- `X_grid = X_grid.reshape((len(X_grid), 1))`
- `plt.scatter(X, y, color = 'red')`
- `plt.plot(X_grid, regressor.predict(X_grid), color = 'blue')`
- `plt.title('Truth or Bluff (SVR)')`
- `plt.xlabel('Position level')`
- `plt.ylabel('Salary')`
- `plt.show()`

SVR



Muito obrigado!