



Free Microsoft AZ-104 Practice Questions

Shared by Delgado on 13-08-2026

For More Free Questions and Preparation Resources

Check the Links on Last Page



Question 1

Question Type: MultipleChoice

Case Study: Mix Questions

Mix Questions

AZ-104 Mix Questions IN THIS CASE STUDY

Note: This question is part of a series of questions that present the same scenario. Each question in the series contains a unique solution that might meet the stated goals. Some question sets might have more than one correct solution, while others might not have a correct solution.

After you answer a question in this section, you will NOT be able to return to it. As a result, these questions will not appear in the review screen.

You have a Microsoft Entra tenant named Adatum.com and an Azure Subscription named Subscription1. Adatum.com contains a group named Developers. Subscription1 contains a resource group named Dev.

You need to provide the Developers group with the ability to create Azure Logic Apps in the Dev resource group.

Solution: On Subscription1, you assign the DevTest Labs User role to the Developers group.

Does this meet the goal?

Options:

A- Yes

B- No

Answer:

B

Explanation:

The DevTest Labs User role is a built-in Azure role designed specifically to support operations within Azure DevTest Labs. According to the Microsoft Azure Administrator documentation on built-in roles, this role permits users to connect to, start, stop, restart, and use virtual machines inside a DevTest Lab, but it does not grant permissions to create or manage Azure resources outside of DevTest Labs, such as Azure Logic Apps.

In this scenario, the requirement is to allow the Developers group to create Azure Logic Apps in the Dev resource group. Azure Logic Apps are managed through the Microsoft.Logic resource provider and require permissions such as Microsoft.Logic/workflows/write. These permissions are included in roles like Logic App Contributor or the more general Contributor role at the resource group scope.

The DevTest Labs User role does not include permissions to deploy or manage Logic Apps, even when assigned at the subscription level. Therefore, assigning this role does not meet the stated goal. Microsoft documentation explicitly states that DevTest Labs User is limited to DevTest Lab resources and cannot be used as a general deployment role.

Final Answer: B. No



Question 2

Question Type: MultipleChoice

Note: This question is part of a series of questions that present the same scenario. Each question in the series contains a unique solution that might meet the stated goals. Some question sets might have more than one correct solution, while others might not have a correct solution.

After you answer a question in this section, you will NOT be able to return to it. As a result, these questions will not appear in the review screen.

You have an app named App1 that is installed on two Azure virtual machines named VM1 and VM2. Connections to App1 are managed by using an Azure Load Balancer.

The effective network security configurations for VM2 are shown in the following exhibit.

Priority	Name	Port	Protocol	Source	Destination	Action
100	Allow_131.107.100.50	443	TCP	131.107.100.50	VirtualNetwork	Allow
200	BlockAllOther443	443	Any	Any	Any	Deny
65000	AllowVnetInBound	Any	Any	VirtualNetwork	VirtualNetwork	Allow
65001	AllowAzureLoadBalancerInBound	Any	Any	AzureLoadBalancer	Any	Allow
65500	DenyAllInBound	Any	Any	Any	Any	Deny

You discover that connections to App1 from 131.107.100.50 over TCP port 443 fail. You verify that the Load Balancer rules are configured correctly.

You need to ensure that connections to App1 can be established successfully from

131.107.100.50 over TCP port 443.

Solution: You create an inbound security rule that denies all traffic from the 131.107.100.50 source and has a cost of 64999.

Does this meet the goal?

Options:

A- Yes

B- No

Answer:

B

Explanation:

In the provided NSG configuration for VM2, the effective inbound security rules show the following priorities:

Priority

Name

Port

Protocol

Source

Action

100

Allow_131.107.100.50

443

TCP

131.107.100.50

Allow

200

BlockAllOther443

443

TCP

Any

Deny

65000+

Default rules

Various

Any

Allow/Deny

The problem states that connections from 131.107.100.50 to port 443 fail, even though the Load Balancer rules are correct.

The proposed solution is to create a new inbound rule that denies all traffic from 131.107.100.50 with a priority of 64999. However, this does not solve the problem --- it makes it worse, because:

The rule with priority 64999 has a higher number, meaning it is evaluated later than existing rules.

Since NSG rules are processed in ascending order of priority, the first matching rule applies.

The rule at priority 200 (BlockAllOther443) already denies the connection before the new rule is even evaluated.

To fix the issue, the correct solution would be to modify or remove the "BlockAllOther443" rule, or adjust priorities so that the allow rule for 131.107.100.50 is evaluated first.

Simply adding another deny rule with a lower priority number (higher numeric value) will not override existing denies.

Final Verified Answer: B. No

Question 3

Question Type: MultipleChoice

You have an Azure subscription that contains the resources shown in the following table.

Name	Type	Resource group	Location
RG1	Resource group	Not applicable	Central US
RG2	Resource group	Not applicable	West US
VMSS1	Virtual machine scale set	RG2	West US
Proximity1	Proximity placement group	RG1	West US
Proximity2	Proximity placement group	RG2	Central US
Proximity3	Proximity placement group	RG1	Central US

You need to configure a proximity placement group for VMSS1.

Which proximity placement groups should you use?

Options:

- A- Proximity2 only
- B- Proximity 1, Proximity2, and Proximity3
- C- Proximity 1 and Proximity3 only
- D- Proximity1 only

Answer:

A

Explanation:

Placement Groups is a capability to achieve co-location of your Azure Infrastructure as a Service (IaaS) resources and low network latency among them, for improved application performance.

Azure proximity placement groups represent a new logical grouping capability for your Azure Virtual Machines, which in turn is used as a deployment constraint when selecting where to place your virtual machines. In fact, when you assign your virtual machines to a proximity placement group, the virtual machines are placed in the same data center, resulting in lower and deterministic latency for your applications.

The VMSS should share the same region, even it should be the same zone as proximity groups are located in the same data center. Accordingly, it should be proximity 2 only.

<https://azure.microsoft.com/en-us/blog/introducing-proximity-placement-groups>

Question 4

Question Type: MultipleChoice

You have an Azure subscription named Subscription1 that contains virtual network named VNet1. VNet1 is in a resource group named RG1. A user named User1 has the following roles for Subscription1:

- * Reader
- * Security Admin
- * Security Reader

You need to ensure that User1 can assign the Reader role for VNet1 to other users. What should you do?

Options:

- A- Remove User1 from the Security Reader and Reader roles for Subscription1.
- B- Assign User1 the Owner role for VNet1.
- C- Remove User1 from the Security Reader role for Subscription1. Assign User1 the Contributor role for RG1.
- D- Remove User1 from the Security Reader and Reader roles for Subscription1. Assign User1 the Contributor role for Subscription1

Answer:

B

Explanation:

<https://docs.microsoft.com/en-us/azure/role-based-access-control/rbac-and-directory-admin-roles#:~:text=The%20User%20Access%20Administrator%20role%20enables%20the%20user%20to%20grant,Azure%20subscriptions%20and%20management%20groups.>

Question 5

Question Type: MultipleChoice

You have an Azure Storage account named storage1.

You need to enable a user named User1 to list and regenerate storage account keys for storage1.

Solution: You assign the Storage Account Encryption Scope Contributor Role to User1.

Does this meet the goal?

Options:

A- Yes

B- No

Answer:

B

Explanation:

In Azure, storage account keys are managed through Azure Role-Based Access Control (RBAC) permissions. The ability to list and regenerate storage account keys requires access to specific management operations on the storage account resource, not encryption scopes.

According to Microsoft Azure Administrator documentation, the permissions required to list and regenerate storage account keys are:

Microsoft.Storage/storageAccounts/listkeys/action

Microsoft.Storage/storageAccounts/regeneratekey/action

Only specific built-in roles include these actions, such as:

Owner

Contributor

Storage Account Contributor

However, the role mentioned in the question --- Storage Account Encryption Scope Contributor -- is designed for a different purpose.

From Microsoft's official documentation for Storage Account Encryption Scope Contributor:

"Grants permissions to manage encryption scopes within a storage account. Does not grant access to manage storage account keys or data."

This means that assigning the Storage Account Encryption Scope Contributor role gives the user permissions to configure encryption scopes (for example, enabling or modifying encryption at the blob container level), but not to list or regenerate access keys.

Therefore, the solution fails to meet the requirement of enabling User1 to list and regenerate keys.

To achieve the goal, the correct role would be: Storage Account Contributor

This role explicitly allows managing all storage account properties, including key management.

Key Point (Microsoft Official Documentation Summary):

Storage Account Encryption Scope Contributor Manage encryption scopes only.

Storage Account Contributor Manage storage account settings, including listing and regenerating keys.

Question 6

Question Type: MultipleChoice

You plan to create the Azure web apps shown in the following Table.

Name	Runtime stack
WebApp1	.NET 6 (LTS)
WebApp2	ASP.NET V4.8
WebApp3	PHP 8.1
WebApp4	Python 3.11

What is the minimum number of App Service plans you should create for the web apps?

Options:

- A- 1
- B- 2
- C- 3
- D- 4

Answer:

B

Explanation:

NET Core 3.0: Windows and Linux ASP .NET V4.7: Windows only PHP 7.3: Windows and Linux Ruby 2.6: Linux only Also, you can't use Windows and Linux Apps in the same App Service Plan, because when you create a new App Service plan you have to choose the OS type. You can't mix Windows and Linux apps in the same App Service plan. So, you need 2 ASPs. Reference: <https://docs.microsoft.com/en-us/azure/app-service/overview>

Question 7

Question Type: MultipleChoice

You have an Azure web app named App1. App1 has the deployment slots shown in the following table:

Name	Function
webapp1-prod	Production
webapp1-test	Staging

In webapp1-test, you test several changes to App1.

You back up App1.

You swap webapp1-test for webapp1-prod and discover that App1 is experiencing performance issues.

You need to revert to the previous version of App1 as quickly as possible.

What should you do?

Options:

- A- Redeploy App1
- B- Swap the slots
- C- Clone App1
- D- Restore the backup of App1

Answer:

B

Explanation:

When you swap deployment slots, Azure swaps the Virtual IP addresses of the source and destination slots, thereby swapping the URLs of the slots. We can easily revert the deployment by swapping back. Deployment slots are live apps with their own host names. App content and configurations elements can be swapped between two deployment slots, including the production slot. Deploying your application to a non-production slot has the following benefits:

1. You can validate app changes in a staging deployment slot before swapping it with the production slot.
2. Deploying an app to a slot first and swapping it into production makes sure that all instances of the slot are warmed up before being swapped into production.

Reference: <https://docs.microsoft.com/en-us/azure/app-service/deploy-staging-slots>

Question 8

Question Type: MultipleChoice

You have an Azure subscription.

Users access the resources in the subscription from either home or from customer sites. From home, users must establish a point-to-site VPN to access the Azure resources. The users on the customer sites access the Azure resources by using site-to-site VPNs.

You have a line-of-business app named App1 that runs on several Azure virtual machine. The virtual machines run Windows Server 2016.

You need to ensure that the connections to App1 are spread across all the virtual machines.

What are two possible Azure services that you can use? Each correct answer presents a complete solution.

NOTE: Each correct selection is worth one point.

Options:

- A- a public load balancer
- B- Traffic Manager
- C- an Azure Content Delivery Network (CDN)
- D- an internal load balancer
- E- an Azure Application Gateway

Answer:

D, E

Explanation:

Line of Business WebAPP works on VMs need internal load balancer. So D is needed. Then deploy WebAPP on VMs, check the link.

<https://docs.microsoft.com/en-us/azure/application-gateway/quick-create-portal> So B is needed as well. The original answer is not accomplished.

Question 9

Question Type: MultipleChoice

You need to implement the planned changes for the storage account content. Which containers and file shares can you use to organize the content?

Options:

- A- share1 only
- B- cont1 and share1 only
- C- share1 and share2 only
- D- cont1, share1, and share2 only
- E- cont1, cont2, share1, and share2

Answer:

B

Explanation:

In the scenario, storage1 is configured as StorageV2 with Hierarchical namespace = Yes, while storage2 is configured as StorageV2 with Hierarchical namespace = No.

From Microsoft's Azure Storage Documentation and AZ-104 Study Guide, the following principles apply:

A hierarchical namespace (enabled when the storage account has Azure Data Lake Storage Gen2 capabilities) allows the use of directories within containers to organize data.

The hierarchical namespace provides directory and file-level structure similar to a file system. This is supported only for blob containers, not for Azure Files.

Azure Files (file shares) do not depend on hierarchical namespaces and cannot have directories in the same way Data Lake Gen2 does --- directories can exist inside the share but not in the blob container sense.

The planned change states that you must use directories whenever possible to organize content. Therefore, only storage accounts with hierarchical namespace enabled can use directory structures --- that's storage1.

In this case:

storage1 (Hierarchical namespace = Yes) supports containers (like cont1) and file shares (like share1).

storage2 (Hierarchical namespace = No) does not support directories within blob containers

(Data Lake structure).

Hence, you can use only cont1 (container in storage1) and share1 (file share in storage1) to organize content as required.

This is directly supported by the Microsoft documentation on Data Lake Storage Gen2:

"When you enable the hierarchical namespace for a storage account, you can organize objects into directories and subdirectories. This capability is available only for accounts configured for Data Lake Storage Gen2."

Final Verified Answer: B. cont1 and share1 only



To Get Premium Files for AZ-104 Visit

<https://www.p2pexams.com/products/az-104>

For More Free Questions Visit

<https://www.p2pexams.com/microsoft/pdf/az-104>

20%
DISCOUNT

P2P
exams