



Free Questions for AZ-104

Shared by Quinn on 24-03-2026

For More Free Questions and Preparation Resources

[Check the Links on Last Page](#)



Question 1

Question Type: MultipleChoice

You have an Azure subscription that contains 10 virtual networks. The virtual networks are hosted in separate resource groups.

Another administrator plans to create several network security groups (NSGs) in the subscription.

You need to ensure that when an NSG is created, it automatically blocks TCP port 8080 between the virtual networks.

Solution: You configure a custom policy definition, and then you assign the Azure policy to the subscription.

Does this meet the goal?

Options:

A- Yes

B- No



Answer:

A

Explanation:

In Azure, Azure Policy is a governance tool used to enforce organizational standards and assess compliance across Azure resources. It allows administrators to define and assign policy definitions that automatically audit, deny, or modify resource configurations at deployment or runtime.

In this scenario, the requirement is that every time a Network Security Group (NSG) is created, it should automatically contain a rule that blocks TCP port 8080 traffic between virtual networks.

The Microsoft Azure Policy documentation confirms that you can create a custom policy definition using the `Microsoft.Network/networkSecurityGroups/securityRules` resource type. Within the policy's JSON definition, you can specify conditions such as:

The resource type to which the policy applies (`networkSecurityGroups`).

The enforcement mode (`deny` or `deployIfNotExists`).

The required configuration, such as a specific inbound or outbound rule (in this case, a rule denying TCP 8080).

By using the DeployIfNotExists effect in the policy, Azure automatically ensures that the NSG includes the required rule. If the rule does not exist, Azure deploys it automatically during resource creation.

Assigning this custom policy definition at the subscription level ensures it is inherited by all resource groups and applies to all virtual networks created in that subscription. This meets the goal because the requirement is to enforce a security configuration across all NSGs, regardless of which resource group or virtual network they belong to.

Therefore, configuring and assigning a custom Azure Policy to the subscription fully satisfies the requirement.

Question 2

Question Type: OrderList

You have a windows 11 device named Device1 and an Azure subscription that contains the resources shown in the following table.



Device 1 has Azure PowerShell and Azure Command-Line Interface (CLI) installed.



From Device1, you need to establish a Remote Desktop connection to VM1.

Which three actions should you perform in sequence? To answer, move the appropriate actions from the list of actions to the answer area and arrange them in the correct order.



Answer:

Upgrade Bastion1 to the Standard SKU. From Bastion1, select Native Client Support. From Azure CLI on Device1, run `az network bastion rdp`.

Question 3

Question Type: MultipleChoice

Note: This question is part of a series of questions that present the same scenario. Each question in the series contains a unique solution that might meet the stated goals. Some question sets might have more than one correct solution, while others might not have a correct solution.

After you answer a question in this section, you will NOT be able to return to it. As a result, these questions will not appear in the review screen.

You have an Azure container registry named Registry1 that contains an image named image1.

You receive an error message when you attempt to deploy a container instance by using image1.

You need to be able to deploy a container instance by using image1.

Solution: You set Admin user to Enable for Registry1.

Does this meet the goal?

Options:

A- Yes

B- No

Answer:

A



Explanation:

When deploying an Azure Container Instance (ACI) using an image from an Azure Container Registry (ACR), the deployment must authenticate to the registry to pull the image. By default, ACR is secured, and you cannot pull images anonymously unless they are public.

According to the Azure Administrator study guide, enabling the Admin user option in ACR generates two access credentials (username and password) that can be used for authentication when pulling container images. When the Admin user setting is disabled, you cannot authenticate directly using those credentials, and automated deployments may fail with authentication errors.

By enabling the Admin user setting, Azure creates a service-level user account for the registry with permissions to push and pull images. These credentials can then be referenced securely in your container instance configuration --- either through the Azure portal, ARM template, or CLI parameters such as --registry-username and --registry-password.

This configuration allows ACI to authenticate successfully against the ACR and pull the required image (image1) for deployment.

Therefore, enabling the Admin user for the container registry meets the goal of allowing the deployment of the container instance using image1.

Question 4

Question Type: OrderList

You have an Azure Active Directory (Azure AD) tenant that has the initial domain name.

You have a domain name of contoso.com registered at a third-party registrar.

You need to ensure that you can create Azure AD users that have names containing a suffix of @contoso.com.

Which three actions should you perform in sequence? To answer, move the appropriate cmdlets from the list of cmdlets to the answer area and arrange them in the correct order.



Answer:

Add a custom domain name. Add a record to the public contoso.com DNS zone. Verify the domain.

Question 5



Question Type: MultipleChoice

You have an Azure subscription that contains two resource groups named RG1 and RG2. RG1 contains the resources shown in the following table.



You move VM1 to RG2.

Which resources are in RG2 after the move?

Options:

- A- VM1 only
- B- VM1 and Disk1 only
- C- VM1.NIC1.and Disk1 only
- D- VMI.VNet1, NIC1, and Disk1

Answer:

C

Explanation:

When you move an Azure virtual machine to another resource group, Azure Resource Manager treats the virtual machine as a resource that has required dependencies. For an IaaS VM, the VM resource depends on its network interface (NIC) for connectivity and its managed disks (OS disk and any data disks) for storage. Microsoft Azure Administrator guidance for resource moves explains that a move operation must include any dependent resources that are required for the resource to function after the move. If you attempt to move only the VM object while leaving required dependencies behind, the move would be blocked or the VM would be left in a nonfunctional state.

In this scenario, NIC1 is the network interface used by VM1, and Disk1 is the OS disk used by VM1; both are core dependencies and are moved along with the VM. VNet1 is a separate networking resource that typically hosts multiple subnets and can be shared by many resources; it is not required to move to move a VM, and moving the VNet would be unnecessary and potentially disruptive. Therefore, after moving VM1 from RG1 to RG2, the resources present in RG2 are VM1, NIC1, and Disk1, but not VNet1.

Question 6

Question Type: OrderList



You have an Azure subscription that contains a storage account.

You have an on-premises server named Server1 that runs Windows Server 2016. Server1 has 2 TB of data.

You need to transfer the data to the storage account by using the Azure Import/Export service.

In which order should you perform the actions? To answer, move all actions from the list of actions to the answer area and arrange them in the correct order.

NOTE: More than one order of answer choices is correct. You will receive credit for any of the correct orders you select.



Answer:

Attach an external disk to Server1 and then run waimportexport.exe. From the Azure portal, create an import job. Detach the external disks from Server1 and ship the disks to an Azure data center. From the Azure portal, update the import job.

Question 7

Question Type: MultipleChoice

You have an Azure subscription that contains the virtual networks shown in the following table.



The subscription contains the virtual machines shown in the following table.



All The virtual machines have only private IP addresses.

You deploy an Azure Bastion host named Bastion1 to VNet1.

To which virtual machines can you connect through Bastion1 ?

Options:

- A- VM1 only
- B- VM1 and VM2 only
- C- VM1 and VM3 only
- D- VM1, VM2, and VM3



Answer:

A

Explanation:

Azure Bastion provides secure and seamless RDP/SSH access to virtual machines directly through the Azure portal, without requiring a public IP address on the target VMs. Bastion is deployed per virtual network (VNet) and enables connectivity only to virtual machines within that same VNet.

In the scenario:

Bastion1 is deployed in VNet1.

VM1 is connected to VNet1.

VM2 is connected to VNet2.

VM3 is connected to VNet3.

Even though VNet1, VNet2, and VNet3 are peered, Azure Bastion access does not traverse VNet peering connections. Microsoft explicitly states:

"Azure Bastion provides RDP/SSH access to virtual machines only within the virtual network in which it is deployed. Bastion does not support access to virtual machines in peered virtual networks."

Therefore, Bastion1 can only provide session connectivity to VM1, which is directly connected to VNet1. VM2 (VNet2) and VM3 (VNet3) cannot be reached through Bastion1 even though peering exists, since Bastion connectivity is restricted to its host VNet.



To Get Premium Files for AZ-104 Visit

<https://www.p2pexams.com/products/az-104>

For More Free Questions Visit

<https://www.p2pexams.com/microsoft/pdf/az-104>

20%
DISCOUNT

