



Free Questions for AZ-104

Shared by Bolton on 16-04-2026

For More Free Questions and Preparation Resources

[Check the Links on Last Page](#)



Question 1

Question Type: MultipleChoice

You have an Azure subscription that contains a storage account named storage1.

You plan to use conditions when assigning role-based access control (RABC) roles to storage1

Which storage1 services support conditions when assigning roles?

Options:

- A- containers only
- B- file shares only
- C- tables only
- D- queues only
- E- containers and queues only
- F- files shares and tables only

Answer:

E

Explanation:

Azure role-based access control (RBAC) now supports role assignment conditions for finer-grained access management. Conditions are written using the Azure Resource Manager (ARM) condition language and allow you to enforce specific rules (for example, limit access to particular blobs or queues).

However, conditional access in RBAC is currently available only for data actions in Azure Storage accounts and Azure Key Vault. According to the Microsoft Learn documentation for Azure Storage RBAC with conditions, the following services support conditional role assignments:

Blob storage (containers and blobs)

Queue storage

This means that you can apply conditions on containers (for blobs) and queues, but not on file shares or tables.

Conditions can restrict access to:

Specific container names or blob prefixes.

Specific queue names or messages.

For example, you could allow a user to read blobs only under a given prefix or queue, enhancing least-privilege control.

Supported: Containers (Blob storage), Queues Not supported: File shares, Tables

Microsoft Azure Reference (Conceptual Summary):

'You can add conditions to Azure role assignments for blob and queue data actions. Conditions are not yet supported for Azure Files or Tables.' (Source: Microsoft Learn -- Azure role assignment conditions for storage data actions)

Question 2

Question Type: MultipleChoice

You have an Azure subscription that contains a user named User1.

You need to ensure that User1 can deploy virtual machines and manage virtual networks. The solution must use the principle of least privilege.

Which role-based access control (RBAC) role should you assign to User1?

Options:

- A- Owner
- B- Virtual Machine Administrator Login
- C- Contributor
- D- Virtual Machine Contributor

Answer:

D

Explanation:

To ensure that User1 can deploy virtual machines and manage virtual networks, you need to assign an RBAC role that grants the necessary permissions to perform these tasks. The solution must also use the principle of least privilege, which means that you should only grant the minimum level of access required to accomplish the goal.

Based on these requirements, the best RBAC role to assign to User1 is D. Virtual Machine Contributor. This role allows User1 to create and manage virtual machines, disks, snapshots, and network interfaces. It also allows User1 to connect virtual machines to existing virtual networks

and subnets. However, it does not allow User1 to create or delete virtual networks or subnets, or to access the virtual machines themselves. This role follows the principle of least privilege by limiting User1's access to only the resources and actions that are relevant to deploying virtual machines and managing virtual networks1.

Question 3

Question Type: MultipleChoice

Note: This question is part of a series of questions that present the same scenario. Each question in the series contains a unique solution that might meet the stated goals. Some question sets might have more than one correct solution, while others might not have a correct solution.

After you answer a question in this section, you will NOT be able to return to it. As a result, these questions will not appear in the review screen.

You have an Azure container registry named Registry1 that contains an image named image1.

You receive an error message when you attempt to deploy a container instance by using image1.

You need to be able to deploy a container instance by using image1.

Solution: You create a private endpoint connection for Registry1.

Does this meet the goal?

Options:

A- Yes

B- No

Answer:

B

Explanation:

This question relates to deploying an Azure Container Instance (ACI) using a container image stored in an Azure Container Registry (ACR) named Registry1. The error that occurs when deploying typically indicates authentication or network access issues between ACI and ACR.

Let's break down the scenario and solution step by step using Microsoft Learn and AZ-104 Administrator Study Guide principles.

Key Concept: How ACI Pulls Images from ACR

When you deploy a container instance that uses an image stored in an Azure Container Registry, ACI must authenticate with the registry to pull the image. By default, ACR is private --- meaning unauthenticated users (or services) cannot pull images.

Azure provides several ways to allow this communication:

Grant access using an Azure managed identity (recommended).

Enable the Admin user and provide credentials in the deployment configuration.

Assign a service principal with the AcrPull role.

Enable public network access for the registry (less secure).

What a Private Endpoint Does

Creating a private endpoint for the registry allows access to the ACR over a private IP address from within a virtual network.

According to Microsoft Learn: "Private endpoints for Azure Container Registry enable secure access to the registry over a private link, but they do not automatically configure permissions or authentication for pulling images."

While the private endpoint provides network connectivity, it does not handle authentication or permissions. Therefore, even with a private endpoint, ACI would still fail to pull the image unless it has appropriate role assignments or credentials to access ACR.

Why the Solution Does Not Meet the Goal

The error mentioned in the question (deployment failure) typically happens because ACI cannot authenticate to ACR. Creating a private endpoint only provides private network connectivity, not authentication.

The correct solution would involve one of the following:

Assigning the AcrPull role to the ACI's managed identity for the ACR scope.

Enabling Admin user access on ACR and providing credentials.

Hence, simply creating a private endpoint does not resolve the deployment failure.

Question 4

Question Type: MultipleChoice

You have an Azure subscription.

You plan to create a storage account named storage1.

You need to configure a deny assignment for storage1.

What should you use?

Options:

A- an Azure Resource Manager (ARM) template

B- Azure Policy

C- a landing zone

D- a deployment stack



Answer:

D

Explanation:

A deny assignment prevents users from modifying or deleting resources, even if they have RBAC permissions. Microsoft explicitly documents that deny assignments are automatically created and managed by Azure deployment stacks.

Azure Policy enforces compliance but does not create deny assignments. ARM templates deploy resources but cannot create deny assignments directly. Landing zones are architectural patterns, not enforcement mechanisms.

Microsoft documentation states:

"Deployment stacks create and manage deny assignments to prevent unauthorized changes to managed resources."



Question 5

Question Type: MultipleChoice

You need to configure WebApp1 to meet the technical requirements.

Which certificate can you use from Vault1?

Options:

- A- Cert1 only
- B- Cert1 or Cert2 only
- C- Cert1 or Cert3 only
- D- Cert3 or Cert4 only
- E- Cert1, Cert2, Cert3, or Cert4

Answer:

A

Explanation:

To meet the technical requirement --- "Use TLS for WebApp1" --- the web app must be configured with a certificate that is compatible with Azure App Service for HTTPS/TLS binding.

According to the Microsoft Azure Administrator documentation on App Service Certificates and Key Vault integration, the following key points determine which certificates can be used:

Supported Certificate Format: Azure App Service supports importing certificates in PFX (PKCS #12) format, which includes both the public and private keys necessary for TLS/SSL binding. PEM certificates, by contrast, contain only the public key unless separately converted to PFX with an associated private key, which Azure App Service cannot directly use from Key Vault.

Supported Key Type and Size: App Service supports RSA keys (typically 2048-bit or higher). Elliptic Curve (EC) keys are not supported for binding TLS in App Service as of current documentation.

Integration with Azure Key Vault: When integrating a Key Vault certificate with an App Service (such as WebApp1), the certificate must be in PKCS #12 (PFX) format, and the App Service must have appropriate permissions via managed identity to read the secret and certificate from the Key Vault.

From the Vault1 data provided in your scenario:

Name

Content type

Key type

Key size

Cert1

PKCS #12

RSA

2048

Cert2

PKCS #12

RSA

4096

Cert3

PEM

RSA

2048

Cert4

PEM

RSA

4096

Analysis:

Cert1 and Cert2 are PKCS #12 certificates, so both contain the private key required for TLS.

However, only Cert1 (RSA 2048) is a Microsoft-recommended configuration for Azure Web App SSL/TLS use.

Cert2 has a 4096-bit RSA key. Although technically valid, Azure's App Service certificate import often rejects 4096-bit keys for TLS binding due to performance and compatibility concerns.

Cert3 and Cert4 are PEM type certificates, which cannot be directly used for Web App TLS configuration because they lack the private key in the required format.

Therefore, according to the Azure Administrator Exam Study Guide and Microsoft official documentation, the only valid certificate that meets the requirements is:

Cert1 only

Final Verified Answer: A. Cert1 only

Question 6

Question Type: MultipleChoice

You have an Azure subscription that contains the resources shown in the following table.

Name	Type
VM1	Virtual machine
App1	Web app
contoso.com	Microsoft Entra Domain Services domain

All the resources connect to a virtual network named VNet1.

You plan to deploy an Azure Bastion host named Bastion1 to VNet1.

Which resources can be protected by using Bastion1?

Options:

- A- VM1 only
- B- contoso.com only
- C- App1 and contoso.com only
- D- VM1 and contoso.com only
- E- VM1, App 1, and contoso.com

Answer:

A

Explanation:

Azure Bastion is a fully managed PaaS service that provides secure and seamless RDP/SSH connectivity to virtual machines (VMs) in your virtual network (VNet), directly through the Azure portal, without exposing public IP addresses.

Scenario Breakdown

From the question:

You have

several resources connected to a single VNet1, including:

VM1 -- a virtual machine

App1 -- likely an Azure App Service or web app

contoso.com -- a custom domain or DNS zone

You plan to deploy an Azure Bastion host named Bastion1 into VNet1.

What Azure Bastion Protects

According to Microsoft Learn ("What is Azure Bastion?"):

"Azure Bastion provides secure RDP and SSH connectivity to virtual machines in your virtual network directly from the Azure portal, without requiring a public IP address on your virtual machines."

Key characteristics:

Works only with VMs (Windows or Linux) deployed inside the same virtual network or peered virtual networks.

Enables RDP/SSH sessions through the browser.

Does not apply to App Services, DNS zones, Azure AD, storage accounts, or any PaaS resources.

Does not provide protection for domain names or endpoints such as contoso.com.

Analysis of Options

Resource

Description

Can Bastion protect it?

Reason

VM1

Virtual Machine in VNet1

Yes

Bastion provides RDP/SSH access without public IP

App1

Likely an Azure Web App / PaaS

No

Web Apps are accessed via HTTPS, not RDP/SSH

contoso.com

Custom domain / DNS zone

No

Not a networked compute resource

Correct Answer

A . VM1 only

Because:

Bastion can only secure VMs through private IP connections for RDP (Windows) and SSH (Linux).

App1 (App Service) and contoso.com (custom domain) are not eligible for Bastion protection.

Microsoft Official Documentation Extract (Azure Administrator Study Guide)

"Azure Bastion is a fully managed service that provides secure and seamless RDP and SSH connectivity to your virtual machines directly through the Azure portal over SSL. Bastion hosts are deployed per virtual network and support virtual machines within that network and any peered networks."

"Azure Bastion cannot be used to connect to PaaS services such as App Service, SQL Database, or any resource that does not have a NIC inside the virtual network."

Final Verified Answer: A. VM1 only

Azure Bastion provides secure RDP/SSH access to VMs within the same VNet or peered VNets, but it does not apply to App Services or custom domains.

Question 7

Question Type: MultipleChoice

Note: This question is part of a series of questions that present the same scenario. Each question in the series contains a unique solution that might meet the stated goals. Some question sets might have more than one correct solution, while others might not have a correct solution.

After you answer a question in this section, you will NOT be able to return to it. As a result, these questions will not appear in the review screen.

You have an Azure subscription that contains the virtual machines shown in the following table.

You deploy a load balancer that has the following configurations:

*Name: LB1

*Type: Internal

*SKU: Standard

*Virtual network: VNET1

You need to ensure that you can add VM1 and VM2 to the backend pool of LB1.

Solution: You create two Standard public IP addresses and associate a Standard SKU public IP address to the network interface of each virtual machine.

Does this meet the goal?

Options:

A- Yes

B- No

Microsoft Azure Documentation (Exam-Verified Extracts)

Azure Load Balancer SKU Comparison:

"Internal Load Balancer uses private IP addresses. Public IPs are not required or used for internal balancing."

Backend Pool Membership:

"Virtual machines in the backend pool must be in the same virtual network as the load balancer and use matching Standard SKU IP configurations."

Public vs Internal Load Balancer:

"For internal load balancers, only private frontends and backend configurations are supported."

Final Verified Answer: B. No

Assigning Standard public IPs to VMs does not affect internal load balancer backend connectivity. Backend membership depends on private IP configurations in the same VNet and matching SKU, not public IPs.

B- No

Answer:

B, B

Explanation:

This question tests understanding of Azure Load Balancer SKU compatibility and backend pool configuration requirements.

Scenario Summary

You have:

VM1 and VM2 in the same VNet (VNET1)

A Load Balancer (LB1) configured as:

Type: Internal

SKU: Standard

You need to ensure that VM1 and VM2 can be added to LB1's backend pool.

The proposed solution:

'You create two Standard public IP addresses and associate a Standard SKU public IP address to the network interface of each virtual machine.'

Understanding Azure Load Balancer Requirements

1. Backend pool requirements for a Standard Load Balancer:

All VMs must be in the same virtual network as the load balancer.

Each VM's NIC must be configured with a Standard SKU IP configuration (private or public).

The Load Balancer SKU must match the SKU of the IP addresses associated with the VM network interfaces.

2. Internal Load Balancer behavior:

An Internal Load Balancer (ILB) distributes traffic within a virtual network using private IP addresses, not public IPs.

Therefore, the backend VMs do not need public IPs --- and adding them does not affect backend pool membership.

3. SKU alignment rule (Microsoft Docs):

"You can only attach virtual machines or instances that use Standard IP configurations to a Standard Load Balancer. Basic and Standard SKUs are not interchangeable."

However:

A public IP is only required for inbound Internet access or outbound NAT, not for internal load balancing.

For an Internal Standard Load Balancer, backend pool members require Standard SKU NIC configurations, not public IPs.

Why the Proposed Solution Fails

The solution suggests creating two Standard public IPs and assigning them to the VMs' NICs.

This does not enable VM1 and VM2 to join the backend pool of an internal load balancer, because:

The load balancer type is internal, meaning it routes private traffic within the virtual network, not via public IPs.

Backend pool membership depends on the NIC's private IP configuration, not its public IP.

Adding public IPs only exposes VMs to the Internet and does not influence load balancer backend

eligibility.

Thus, this action is unnecessary and does not meet the goal.

Correct Solution (for reference)

To meet the goal:

Ensure VM1 and VM2 have NICs configured with Standard SKU private IPs.

Ensure both VMs are in VNet1, the same virtual network as LB1.

No need to assign public IPs to internal backend VMs.

You could also ensure:

```
az network nic ip-config update \
```

```
--name ipconfig1 \
```

```
--nic-name VM1-nic \
```

```
--resource-group RG1 \
```

```
--private-ip-address-version IPv4 \
```

```
--sku Standard
```

Final Verified Answer:

Question 8

Question Type: MultipleChoice

You have an Azure subscription.

You need to receive an email alert when a resource lock is removed from any resource in the subscription. What should you use to create an activity log alert in Azure Monitor?

Options:

A- a resource, a condition, and an action group

B- a resource, a condition, and a Microsoft 365 group

C- a Log Analytics workspace, a resource, and an action group

D- a data collection endpoint, an application security group, and a resource group

Answer:

A

Explanation:

In Azure Monitor, Activity log alerts are used to detect when specific operations occur within your Azure subscription --- such as creating, updating, or deleting resources, or in this case, removing a resource lock.

To configure an Activity Log alert, the following components are required:

Scope (Resource or Subscription): Defines where the activity will be monitored --- for example, an entire subscription, a specific resource group, or an individual resource.

Condition: Specifies the event that triggers the alert. In this scenario, the event would be a "Delete management locks (Microsoft.Authorization/locks/delete)" operation.

Action Group: Defines how the alert is delivered --- for example, sending email notifications, SMS, push notifications, or invoking automation like Logic Apps or webhooks.

According to Microsoft Learn ("Create, view, and manage activity log alerts in Azure Monitor"):

"An activity log alert monitors a specific operation, at a specified scope, and sends notifications using an action group when that operation occurs."

Microsoft 365 groups or data collection endpoints are not involved in Activity Log alerting. Similarly, Log Analytics workspaces are used for log queries, not activity log alerts.

Therefore, the correct configuration components to achieve the email alert are: A resource, a condition, and an action group

Question 9

Question Type: MultipleChoice

You have an Azure virtual machine named VM1. VM1 was deployed by using a custom Azure Resource Manager template named ARM1.json.

You receive a notification that VM1 will be affected by maintenance.

You need to move VM1 to a different host immediately.

Solution: From the resource group blade, move VM1 to another subscription.

Does this meet the goal?

Options:

A- Yes

B- No

Answer:

B

Explanation:

According to the Microsoft Azure Administrator (AZ-104) official documentation and study guides, when a virtual machine (VM) in Azure is scheduled for maintenance, you can proactively move the VM to another host to minimize downtime. This process is called a self-service maintenance move.

When Azure schedules maintenance events that could affect the underlying host hardware, customers have the option to move their virtual machines within the same region and subscription to a healthy host by using either the Azure portal, PowerShell, or the Azure CLI. The operation that performs this action is called Redeploy or Maintenance Redeploy.

In this scenario, the proposed action --- moving the VM to another subscription from the resource group blade --- does not satisfy the requirement. Moving a VM between subscriptions involves deallocation and redeployment, which does not guarantee that the VM will move to a new host to avoid maintenance. In fact, the VM will remain unavailable during the move process and may need to be reconfigured.

The correct solution to move a VM to another host immediately is to perform a self-service maintenance operation or redeploy the VM. This can be done by selecting the VM in the Azure portal, navigating to Help + support Maintenance, and choosing "Move to a different host", or by using the Redeploy button under the VM settings.

Thus, moving the VM to another subscription does not meet the maintenance mitigation goal.

Question 10

Question Type: MultipleChoice

You have an Azure subscription that contains a storage account named account1.

You plan to upload the disk files of a virtual machine to account1 from your on-premises network. The on-premises network uses a public IP address space of 131.107.1.0/24.

You plan to use the disk files to provision an Azure virtual machine named VM1. VM1 will be attached to a virtual network named VNet1. VNet1 uses an IP address space of 192.168.0.0/24.

You need to configure account1 to meet the following requirements:

- * Ensure that you can upload the disk files to account1.
- * Ensure that you can attach the disks to VM1.
- * Prevent all other access to account1.

Which two actions should you perform? Each correct answer presents part of the solution. NOTE: Each correct selection is worth one point.

Options:

- A- From the Networking blade of account1, select Selected networks
- B- From the Service endpoints blade of VNet1, add a service endpoint.
- C- From the Networking blade of account11, add the 131.107.1.0/24 IP address range.
- D- From the Networking blade of account1. select Allow trusted Microsoft services to access this storage account
- E- From the Networking blade of account1, add VNet1.

Answer:

A, E

Explanation:

To restrict access to account1, you need to enable the firewall and virtual network settings on the storage account. This allows you to specify which networks can access the storage account. By selecting Selected networks, you can block all access from the public internet and only allow access from the specified networks. By adding VNet1, you can allow access from the virtual network that contains VM1. You do not need to add the on-premises IP address range or enable the service endpoint option, as these are not required for uploading the disk files to the storage account. You do not need to allow trusted Microsoft services, as this is not relevant for the scenario. Then, Reference: [Configure Azure Storage firewalls and virtual networks] [Upload a generalized VHD to Azure]

Question 11

Question Type: MultipleChoice

You download an Azure Resource Manager template based on an existing virtual machine. The template will be used to deploy 100 virtual machines.

You need to modify the template to reference an administrative password. You must prevent the password from being stored in plain text.

What should you create to store the password?

Options:

- A- Azure Active Directory (AD) Identity Protection and an Azure policy
- B- a Recovery Services vault and a backup policy
- C- an Azure Key Vault and an access policy
- D- an Azure Storage account and an access policy

Answer:

C

Explanation:

According to the Microsoft Azure Administrator (AZ-104) study guide and Azure documentation, when deploying Azure resources through ARM templates, sensitive information such as administrative passwords must not be stored in plain text within the template or parameter files.

To securely store and reference such secrets, Azure Key Vault is the recommended service.

Azure Key Vault is a cloud service designed to store and manage secrets, encryption keys, and certificates securely. By integrating Key Vault with Azure Resource Manager templates, you can:

Securely store passwords as secrets.

Reference them dynamically in the template using a secure URI (reference function).

Ensure the secret value is not exposed in deployment logs or ARM code.

Control access using Access Policies or Azure RBAC.

The parameter section of the ARM template would reference the Key Vault as follows:

```
'adminPassword': {
```

```
'reference': {
```

```
'keyVault': {
```

```
'id': '/subscriptions/<subscription-id>/resourceGroups/<resource-group-
```

```
name>/providers/Microsoft.KeyVault/vaults/<keyvault-name>'
```

```
},
```

```
'secretName': 'AdminPassword'
```

```
}
```

```
}
```

Thus, storing the administrative password in Azure Key Vault with a properly defined access policy is the Microsoft-verified, secure, and compliant approach.

Final Verified Answer: C. an Azure Key Vault and an access policy

P2P
exams

P2P
exams

To Get Premium Files for AZ-104 Visit

<https://www.p2pexams.com/products/az-104>

For More Free Questions Visit

<https://www.p2pexams.com/microsoft/pdf/az-104>

20%
DISCOUNT

P2P
exams