

# 1. Introduction

## Official documentation

- A workspace is a directory containing ROS 2 packages. Is a ROS term for the location on the system where it is been developing with ROS 2.

## 1.1 Hierarchy

- Underlay: Is the core space, i.e. the ROS distro install, that contains other workspaces (overlays). It must contain the dependencies of all the packages in your overlay
- Overlay: A secondary workspace where you new packages are added without interfering with the existing workspace that is being extended.
  - It's possible to have several layers of underlays and overlays, with each successive overlay using the packages of its parent underlays.
  - Combining workspaces makes developing against different versions of ROS 2, or against different sets of packages, easier. It also allows the installation of several ROS 2 distributions
  - This is accomplished by sourcing setup files every time you open a new shell, or by adding the source command to your shell startup script once. Without sourcing the setup files, you won't be able to access ROS 2 commands, or find or use ROS 2 packages

## 2. Creating a workspace

1. Create the workspace directory with a src directory inside:
2. Solve the packages dependencies (Only if it was cloned by a repo)
3. Build with Colcon
4. Source:
  - Important: Use a new terminal

```
source ~/<workspace>/install/setup.bash
```

## 3. Directories

- src folder: where the source code is placed
- build folder: where intermediate files are stored.
- install folder: where each package will be installed.
- log folder: where all the logging information is available.