

Estimating Dynamic Functional Network Connectivity in fMRI Data

Bayesian Approach

Davide Fabbri

University of Florence
Department of Statistics and Data Science

December 16, 2021



UNIVERSITÀ
DEGLI STUDI
FIRENZE

DISIA

DIPARTIMENTO DI STATISTICA
INFORMATICA, APPLICAZIONI
"GIUSEPPE PARENTI"

Outline

- ① Background
- ② Bayesian Approach
- ③ Conclusion

① Background

② Bayesian Approach

③ Conclusion

Graphical Models¹

A graphical model represent conditional dependence relationships among random variables. It is composed by two parts:

- A set $\mathbf{X} = \{X_1, \dots, X_p\}$ of random variables with distribution $P(\mathbf{X})$;
- A graph $G = (V, E)$ in which each element of V is associated with one of the random variables in \mathbf{X} , and the element of E is the conditional relationships among this.

¹Lauritzen 1996.

Gaussian Graphical Models

In GGMs we have


$$\mathbf{x}_i \sim N_p(\boldsymbol{\mu}, \boldsymbol{\Omega}^{-1}) \quad i = 1, \dots, n$$

The conditional independence relationships correspond to constraints on the precision matrix $\boldsymbol{\Omega} = \boldsymbol{\Sigma}^{-1}$.

Specifically, the precision matrix $\boldsymbol{\Omega}$ is a symmetric positive definite matrix with off-diagonal entry ω_{ij} equal to zero if there is no edge in G between vertex i and vertex j .

Functional magnetic resonance imaging Data (Booth et al. 2021)

- Indirect measure of neuronal activity by changes in blood oxygenation;
- Time series of blood oxygenation level dependent (BOLD) responses are collected at each location;
- Learn *effective* and *functional* connectivity.



① Background

② Bayesian Approach

③ Conclusion

Regression on *HRF*-convolved Stimulus (Warnick et al. 2018)

Let $\mathbf{Y}_t = (Y_{t1}, \dots, Y_{tV})^T$ be the vector of *fMRI BOLD* responses.

Assuming an experiment with K distinct stimuli,

$$\mathbf{Y}_t = \boldsymbol{\mu} + \sum_{k=1}^K X_t^k \circ \beta_k + \epsilon_t \quad (1)$$

where X_t^k is the vector for the k -th stimulus, $\boldsymbol{\mu}$ the global mean and $\beta_k = (\beta_{1k}, \dots, \beta_{V_k})^T$ the stimulus-specific vector coefficients.

Then we model X_t^k as the convolution,

$$X_{vt}^k = (x_k * h_\lambda)(t) = \int_0^t x_k(\tau) h_\lambda(t - \tau) d\tau$$




Figure 1: In the red rectangle the Regression with HRF (1).

Functional networks and dynamic connectivity (Peterson, Stingo, and Vannucci 2015)

Let $\mathbf{s} = (s_1, \dots, s_T)^T$ denoting the connectivity state at time t ,

$$(\epsilon_t | s_t = s) \sim N_p(0, \Omega_s)$$

where Ω_s is the precision matrix.

The *G-Wishart* prior density $W_G(b, D)$ can be written as

$$p(\Omega | G, b, D) = I_G(b, D)^{-1} |\Omega|^{\frac{b-2}{2}} \exp\left(-\frac{1}{2} \text{tr}(\Omega D)\right)$$

where $b > 2$ is the degrees of freedom parameter, D is a $p \times p$ positive definite symmetric matrix, I_G is the normalizing constant.

Hidden Markov Model (Fine, Singer, and Tishby 1998)

Let X_n and Y_n be discrete-time stochastic processes, the pair (X_n, Y_n) is a hidden Markov model, if:

- X_n is a Markov process with *Hidden* states;
- $p(Y_n \in A \mid X_1 = x_1, \dots, X_n = x_n) = p(Y_n \in A \mid X_n = x_n)$




Figure 2: Schematic of an HMM with $N = 3$. Left shows the temporal sequence. Each S_t^s could be one of N states (Eavani et al. 2013).




Figure 3: Modeling the connectivity states via Hidden Markov Model.

Joint modeling of the connectivity states (Peterson, Stingo, and Vannucci 2015)

Let $\mathbf{g}_{ij} = (g_{ij,1}, \dots, g_{ij,S})^T$ with $g_{ij,s}$ indicating the presence or absence of edge (i,j) in graph G_s .

The *super-graph*, defines the presence of an edge across graphs through a Markov Random Field (MRF) prior,

$$p(\mathbf{g}_{ij} \mid v_{ij}, \Theta) = C(v_{ij}, \Theta)^{-1} \exp(v_{ij} \mathbf{1}^T \mathbf{g}_{ij} + \mathbf{g}_{ij}^T \Theta \mathbf{g}_{ij})$$

with v_{ij} is a sparsity parameter specific and Θ is a symmetric matrix which captures relatedness among networks.




Figure 4: Super-Graph and Dynamic model.

① Background

② Bayesian Approach

③ Conclusion

Conclusion

- In the Bayesian model it is assumed the existence of a structure called *super-graph* which models the relationship between the various temporal states;
- Setting of the priors including an **MRF** for the super-graph and a **G-Wishart** for the precision matrix on each graph;
- With the knowledge of the data obtain a posteriori and so the distribution of the parameters of interest.

References



Lauritzen, Steffen L (1996). *Graphical models*. Vol. 17. Clarendon Press.



Booth, James R. et al. (2021). "Working Memory and Reward in Children with and without Attention Deficit Hyperactivity Disorder (ADHD)". *OpenNeuro*. DOI: [10.18112/openneuro.ds002424.v1.2.0](https://doi.org/10.18112/openneuro.ds002424.v1.2.0).



Warnick, Ryan et al. (2018). "A Bayesian approach for estimating dynamic functional network connectivity in fMRI data". In: *Journal of the American Statistical Association* 113.521, pp. 134–151.



Peterson, Christine, Francesco C Stingo, and Marina Vannucci (2015). "Bayesian inference of multiple Gaussian graphical models". In: *Journal of the American Statistical Association* 110.509, pp. 159–174.



Eavani, Harini et al. (2013). “Unsupervised learning of functional network dynamics in resting state fMRI”. In: *International conference on information processing in medical imaging*. Springer, pp. 426–437.



Fine, Shai, Yoram Singer, and Naftali Tishby (1998). “The hierarchical hidden Markov model: Analysis and applications”. In: *Machine learning* 32.1, pp. 41–62.