

asm1

📁 picoCTF > Reverse Engineering · + Tags

This is the code given. Also, the given value 0x3ef is 1077 in decimal
asm1:

```
<+0>: endbr32
<+4>: push ebp 1007
<+5>: mov ebp,esp 1007
<+7>: cmp DWORD PTR [ebp+0x8], 0x6e6=1766
<+14>: jg 0x11d3 <asm1+38> 1007 is not greater than 1766
<+16>: cmp DWORD PTR [ebp+0x8],0x8=8
<+20>: jne 0x11cb <asm1+30> 1007 is not equal to 8, so it will jump to 30
<+22>: mov eax,DWORD PTR [ebp+0x8]
<+25>: add eax,0x9
<+28>: jmp 0x11ea <asm1+61>
<+30>: mov eax,DWORD PTR [ebp+0x8] 1007 is moved to eax register
<+33>: sub eax,0x9=9 1007-9 is 998
<+36>: jmp 0x11ea <asm1+61> 998 jumped to line 61
<+38>: cmp DWORD PTR [ebp+0x8],0x8f8
<+45>: jne 0x11e4 <asm1+55>
<+47>: mov eax,DWORD PTR [ebp+0x8]
<+50>: sub eax,0x9
<+53>: jmp 0x11ea <asm1+61>
<+55>: mov eax,DWORD PTR [ebp+0x8]
<+58>: add eax,0x9
<+61>: pop ebp 998 turned to hex is 3E6
<+62>: ret 0x3E6
```

the flag is: 0x3e6