TEG SPECIAL HD

TRINCIAERBA FRONTALE
PER TRATTORI DA 18 A 37 CV
FRONT FLAIL MOWER
FOR TRACTORS FROM 18 TO 37 HP



La trinciaerba frontale TEG SPECIAL è adatta per l'applicazione a trattori da 18 a 37 CV di potenza a marchio John Deere, Kubota, Grasshopper, Iseki, Grillo, Toro ed è una macchina che taglia finemente l'erba e piccoli sarmenti con contemporanea rullatura del manto erboso.

Grazie all'elevato numero di giri del rotore e al numero di coltelli di cui dispone la macchina, si riduce l'effetto onda del manto erboso e si svolge una notevole azione mulching. A seconda del lavoro richiesto, con l'applicazione delle lame verticali si ottiene inoltre un'ottima azione di verticut su giardini, prati e aree urbane, dove il residuo tagliato o arieggiato viene distribuito uniformemente su tutta la superficie di taglio.

La regolazione di taglio nelle trinciaerba frontale TEG SPECIAL avviene sulle ruote frontali con alcuni spessori di facile regolazione e sul rullo posteriore mediante una vite e apposita chiave fornita di serie per una regolazione millimetrica, molto utile durante l'azione di verticut per l'entrata nel terreno. Prodotta negli stabilimenti Peruzzo è disponibile anche in versione HD, dotata di struttura rinforzata e coltelli maggiorati.

The TEG SPECIAL front flail mower is suitable for application to tractors from 18 to 37 HP of power branded John Deere, Kubota, Grasshopper, Iseki, Grillo, Toro and is a machine that finely cuts the grass and small shrubs with simultaneous rolling of the turf.

Thanks to the high number of revolutions of the rotor and the number of knives available to the machine, the wave effect of the turf is reduced and a considerable mulching action takes place. Depending on the work required, with the application of vertical blades an excellent verticut action is also obtained on gardens, lawns and urban areas, where the cut or ventilated residue is evenly distributed over the entire cutting surface.

The cutting adjustment in the TEG SPECIAL front flail mower takes place on the front wheels with some thicknesses easy to adjust and on the rear roller by means of a screw and a special key supplied as standard for a millimeter adjustment, very useful during the verticut action for the entry of the blade into the ground. Produced in Peruzzo factories, it is also available in HD version, equipped with reinforced structure and stronger knives.









COMPONENTI TECNICHE TECHNICAL COMPONENTS



Sicurezza anti ribaltamento. *Mower tilting prevention.*



Regolazione di taglio millimetrica.

Millimeter cutting adjustment.



Tripla sovrapposizione dei coltelli. Bilanciatura dinamica totale. Triple overlap of the knives. Dynamic total balancing.



elicoidali rodati a bassa rumorosità. Gearbox with helical and smooth gears at low noise.

Moltiplicatore ad ingranaggi

LAME STANDARD STANDARD BLADES



Coltello "Y" per taglio mulching sp. 4 mm. Flail "Y" for mulching cut with 4 mm thickness.



Coltello "Y" solo per modello Teg Special HD - sp. 5 mm.

Flail "Y" only for Teg Special HD - 5 mm thickness.

LAME ACCESSORIE ON REQUEST BLADES



Coltello "Y" per taglio mulching sp. 4 mm + lama verticut di 3 mm di spessore. Flail "Y" for mulching with 4 mm thickness + verticut blade with 3 mm thickness.



Coltello per verticut da 3 mm di spessore. *Verticut flail with 3 mm thickness.*

Valido solo per / Only for TEG SPECIAL



Mazzetta a paletta robusta di spessore 5 mm per erba alta e piccoli arbusti.

Heavy duty cast flail with 5 mm thickness for high grass and small branches.

Mazzetta con foro / Heavy duty cast flail with hole TEG SPECIAL

Mazzetta con asola / Heavy duty cast flail with button hole TEG SPECIAL HD



PERSONALIZZAZIONI IN BASE AL BRAND DI TRATTORE

CUSTOMIZATION ACCORDING TO THE TRACTOR BRAND



2 KUBOTA

3 GRASSHOPPER

4 ISEKI

5 GRILLO

6 TORO





	MODELLO MODEL	LARGHEZZA DI TAGLIO CUTTING WIDTH (MM)	POTENZA MIN MAX. NECESSARIA MIN MAX. POWER REQUIRED (HP)	POTENZA MIN MAX. NECESSARIA MIN MAX. POWER REQUIRED (KW)	QUANTITÀ COLTELLI "Y" "Y" FLAILS QUANTITY	QUANTITÀ MAZZE HAMMERS QUANTITY
1	TEG SPECIAL HD 1600 JD - F1565/F1570/F1580	1480	25 - 37	18,5 - 27	96	48
	TEG SPECIAL HD 1800 JD - F1565/F1570/F1580	1780	30 - 37	22 - 27	116	58
2	TEG SPECIAL 1600 Kubota - F3560/F2880/F3680	1460	20 - 37	15 - 27	100	50
	TEG SPECIAL HD 1600 Kubota - F3090/F3680/F3890	1480	25 - 37	18,5 - 27	96	48
	TEG SPECIAL HD 1800 Kubota - F3090/F3680/F3890	1780	30 - 37	22 - 27	116	58
3	TEG SPECIAL 1400 Gasshopper 725DT6 - 928D - 930D - 900D	1330	18 - 37	13,5 - 27	88	44
4	TEG SPECIAL 1400 Iseki SF235 - SF237	1330	18 - 37	13,5 - 27	88	44
	TEG SPECIAL HD 1600 Iseki SF450 - SF438	1480	25 - 37	18,5 - 27	96	48
5	TEG SPECIAL HD 1600 Grillo FD2200 TS - FM 2200	1480	25 - 37	18,5 - 27	96	48
6	TEG SPECIAL 1600 Toro Groundmaster 3310/3200/3300	1460	20 - 37	15 - 27	100	50











	MODELLO MODEL	ALTEZZA DI TAGLIO MINIMA E MASSIMA MIN. & MAX CUTTING HEIGHT (MM)	PESO WEIGHT (KG)	PDF / PTO (RPM)	(LxPxH)	DIMENSIONI IMBALLAGGIO PACKAGING DIMENSIONS (LxPxH)
1	TEG SPECIAL HD 1600 JD - F1565/F1570/F1580	25 - 75	250	2600	1790 x 1200 x 550	1800 x 1200 x 650
	TEG SPECIAL HD 1800 JD - F1565/F1570/F1580	25 - 75	290	2600	2120 x 1200 x 550	2320 x 1300 x 650
2	TEG SPECIAL 1600 Kubota - F3560/F2880/F3680	25 - 105	220	2000	1790 x 1110 x 440	1800 x 1200 x 650
	TEG SPECIAL HD 1600 Kubota - F3090/F3680/ F3890	25 - 75	253	2600	1790 x 1200 x 550	1800 x 1200 x 650
	TEG SPECIAL HD 1800 Kubota - F3090/F3680/ F3890	25 - 75	302	2600	2120 x 1200 x 550	2320 x 1300 x 650
3	TEG SPECIAL 1400 Gasshopper 725DT6 - 928D - 930D - 900D	30 - 85	210	2000	1650 x 1410 x 490	1800 x 1500 x 700
4	TEG SPECIAL 1400 Iseki SF235 - SF237	20 - 90	230	2000	1650 x 1110 x 475	1700 x 1000 x 650
	TEG SPECIAL HD 1600 Iseki SF450 - SF438	25 - 75	250	2000	1790 x 1210 x 550	1800 x 1200 x 650
5	TEG SPECIAL HD 1600 Grillo FD2200 TS - FM 2200	25 - 75	230	2000	1790 x 1215 x 550	1800 x 1200 x 650
6	TEG SPECIAL 1600 Toro Groundmaster 3310/3200/3300	20 - 70	210	2000	1790 x 1170 x 490	1800 x 1200 x 650