How Is Apache SkyWalking Powering Istio Observability?

Sheng Wu / @wusheng1108 (twitter)



Sheng Wu

- Founding Engineer, Tetrate
- OSS Strategy Consultant. SkyWalking Consultant
- Apache Member
- Creator, VP and PMC member, Apache SkyWalking
- PMC member of Apache APISIX , Incubator, ShardingSphere, ECharts,
 DolphinScheduler
- Member of CNCF KubeCon Program Committee, 2019/2020



Traces, Logs, Metrics - All In Open Source APM



Jan. 2021

Full
Observability
Landscape




#IstioCon

What SkyWalking Has for Istio?

- Metrics
 - Data Panel
 - Control Panel
 - Topology
 - Alarm
- Tracing
 - Native Tracer
- Logs
 - Access Log



Typical Mesh Deployment






Visualize the Whole Mesh



URI Level Metrics





#IstioCon

1

ALS Solution - Level 1

Understand ALS in k8s




Keys of Access Log Service

- downstream_direct_remote_address: This field is the downstream direct remote address on which the request from the user was received. Note: This is always the physical peer, even if the remote address is inferred from for example the x-forwarded-for header, proxy protocol, etc.
- downstream_remote_address: The remote/origin address on which the request from the user was received.
- downstream_local_address: The local/destination address on which the request from the user was received.
- upstream_remote_address: The upstream remote/destination address that handles this exchange.
- upstream_local_address: The upstream local/origin address that handles this exchange.
- upstream_cluster: The upstream cluster that upstream_remote_address belongs to.




Envoy Sidecar



#IstioCon

Gateway - Ingress







ALS Solution - Level 2

How ALS works on VM



Envoy WASM - Matadata Exchange






a plugin of istio-proxy named metadata-exchange injects the metadata into the HTTP headers (with a prefix like

x-envoy-downstream-)



Use Metadata To Build Topology




Data Panel

Envoy Metrics Service & Tracing



Envoy Load and Internal Failure



#IstioCon



Envoy Native SkyWalking tracer

```
filter chains:
- filters:
 - name: envoy.filters.network.http_connection_manager
   typed_config:
      "@type": type.googleapis.com/envoy.extensions.filters.network.http_connection_manager.v3.HttpConnectionManager
     generate_request_id: true
      tracing:
        provider:
                                                                                      - name: skywalking
         name: envoy.tracers.skywalking
                                                                                        connect timeout: 1s
         typed config:
                                                                                        type: strict_dns
            "@type": type.googleapis.com/envoy.config.trace.v3.SkyWalkingConfig
                                                                                        lb policy: round robin
           grpc service:
                                                                                        http2_protocol_options: {}
             envoy_grpc:
                                                                                        load assignment:
               cluster name: skywalking
                                                                                          cluster name: skywalking
             timeout: 0.250s
                                                                                          endpoints:
            client config:
                                                                                          - lb endpoints:
              service_name: front-envoy
                                                                                            - endpoint:
             instance_name: front-envoy-1
                                                                                                address:
                                                                                                  socket_address:
                                                                                                    address: skywalking-oap
```

port value: 11800

#IstioCon

C++ Native Tracer Library

Config

cpp2sky provides simple configuration for tracer. The detail information is described in official protobuf definition.

```
#include <cpp2sky/config.pb.h>
int main() {
    using namespace cpp2sky;

    static const std::string service_name = "service_name";
    static const std::string instance_name = "instance_name";
    static const std::string oap_addr = "oap:12800";
    static const std::string token = "token";

TracerConfig tracer_config;

config.set_instance_name(instance_name);
    config.set_service_name(service_name);
    config.set_address(oap_addr);
    config.set_token(token);
}
```

https://github.com/SkyAPM/cpp2sky

Create tracer

After you constructed config, then setup tracer. Tracer supports gRPC reporter only, also TLS adopted gRPC reporter isn't available now. TLS adoption and REST tracer will be supported in the future.

```
TracerConfig tracer_config(oap_addr, token);
TracerPtr tracer = createInsecureGrpcTracer(tracer_config);
```




Istio Control Panel

Work with Prometheus and OpenTelemetry



Istio Load and xDS Push Status





Infra Observability

VM nodes



Prometheus Node Exporter Zabbix Agent






Logs And Incoming

Access Log Collection And Visualization



Log of Services



Thank you!

@wusheng841108

https://twitter.com/wusheng1108

https://skywalking.apache.org/

